5-963715-5 ✔ ACTIVE

MQS

TE Internal #: 5-963715-5

Automotive Terminals, Receptacle, Mating Tab Width .63 mm [.025 in], Tab Thickness .63 mm [.025 in], 20 - 18 AWG Wire Size, MQS

View on TE.com >

Terminals & Splices > Automotive Terminals > MQS, RECEPTACLE AND TAB







Terminal Type: **Receptacle**

Mating Tab Width: **.63 mm [.025 in]**

Mating Tab Thickness: **.63 mm [.025 in]**

Terminal Transmits: **0 - 24 A (Low Power)**

Wire Size: **20 - 18 AWG**

All MQS, RECEPTACLE AND TAB (99)

Features

Product Type Features

Receptacle Style	180°
Sealable	No
Primary Locking Feature	Locking Lance

Contact Features

Contact Size	.63mm
Contact Fabrication	Stamped & Formed
Wire Contact Termination Area Plating Material	Gold
Typical Current Rating	7.5 A
Crimp Type	F-Crimp
Terminal Type	Receptacle
Mating Tab Width	.63 mm[.025 in]
Mating Tab Thickness	.63 mm[.025 in]
Interface Plating	Gold (Au)

Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire

Dimensions

Compatible Insulation Diameter Range	1.3 - 1.9 mm[.051 - .074 in]
Wire Size	.5 - .75 mm²
Wire Size Search	18 AWG, 19 AWG, 20 AWG

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature (Max)	80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C[176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F]
Operating Temperature Range	-40 - 120 °C[-40 - 248 °F]

Operation/Application

Conforms to KOMAX Automatic Component Insertion Guideline	Yes, per Version 5.0 (March 2018)
Compatible With Wire Base Material	Copper

Industry Standards

Compatible With Agency/Standards Products	LV214

Packaging Features

Packaging Quantity	10000
Packaging Method	Reel

Other

Terminal Transmits	0 - 24 A (Low Power)

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # CAT-M8793-CH8172
MQS, CONNECTOR HOUSING



TE Part # 6-1579007-1
EXTRACTION TOOL



TE Part # 2209954-2
AIRBAG 24P COVER ASSY



TE Part # 2209954-1
AIRBAG 24P COVER ASSY

TE Part # 1308374-1
EXTRACTION TOOL

TE Part # 2141627-1
4POS MIXED MQS REC

TE Part # 2151491-1
OCEAN_2.0_APPLICATOR-S-055F080O-RSM

TE Part # 2151491-2
OCEAN_2.0_APPLICATOR-S-055F080O-RSA



TE Part # 2278598-3
12POS MQS REC



TE Part # 2294218-1
4POS MQS REC COD A



TE Part # 2305570-1
Strip Terminal Cutter-Side Feed-No Crimp



TE Part # 2390077-1
SDE F MQS PIN/SKT 0.75-0.50mm2 ASSY



TE Part # 2390077-2
SDE F MQS PIN/SKT 0.75-0.50mm2 DIE SET



TE Part # 2837765-1
OCEAN-2.0-APPLICATOR-S-055F080O-RSM



TE Part # 2837765-2
OCEAN-2.0-APPLICATOR-S-055F080O-RSA



TE Part # 5-2151491-1
OCEAN_2.0_APPLICATOR-S-055F080O-RSM



TE Part # 5-2151491-2
OCEAN_2.0_APPLICATOR-S-055F080O-RSA



TE Part # 5-2837765-1
OCEAN-2.0-APPLICATOR-S-055F080O-RSM



TE Part # 5-2837765-2
OCEAN-2.0-APPLICATOR-S-055F080O-RSA



TE Part # 7-2151491-7
OCEAN_2.0_SPARE_PART_KIT-055F080O

Also in the Series | MQS



Automotive Connector Caps & Covers (87)



Automotive Connector Locks & Position Assurance(22)



Automotive Housings(298)



Automotive Terminals(78)



Connector Seals & Cavity Plugs(23)



Insertion & Extraction Tools(42)



Other Automotive Connector Accessories(4)



PCB Headers & Receptacles(140)

Customers Also Bought



TE Part # 160916-3
250 FASTON,REC.,17-14 AWG,PB



TE Part # 1-964302-3
TIMER, RECEPTACLE AND TAB



TE Part # 1564984-3
AMP MCP 2.8K, CONTACT, SWS



TE Part # 2282155-1
7POS,NANOMQS,REC HSG,CODA



TE Part # 1-2141876-3
TAB A 2.8x0.8 CONTACT CF SWS Au



TE Part # 1394044-1
SPEZ RINGZUNGE



TE Part # 1801176-5
2W RECEPTACLE HPSL CONNECTOR GREEN



TE Part # 2109435-2
060/110/250 LIF 36P PLUG ASSY



TE Part # 346102-2
RING TONGUE 0.5-1.0 MM2 0.6 X 15.2 CUSN

Documents

Product Drawings

MQS0,63 Au rec LL unseal. 0,5-0,75

English

CAD Files

Customer View Model

ENG_CVM_CVM_5-963715-5_K.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-963715-5_K.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-963715-5_K.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditionsof use.

Datasheets & Catalog Pages

Micro Quadlok Interconnection System (MQS)

English

Product Specifications

Application Specification

English

Application Specification

English

Application Specification

German