




Terminals & Splices > Spade Terminals



Spade Terminal Type: **Spring Spade Terminal**
Wire Size: **5180 – 13100 CMA**
Stud Size: **#8, M4**

Features

Product Type Features

Stud Size	#8, M4
Sealable	No
Wire Insulation Support Retention Type	Insulation Support

Electrical Characteristics

Voltage Rating	600 V
----------------	-------

Body Features

Insulation Sleeve Color	Yellow
Stripe Color	Yellow

Contact Features

Spade Terminal Type	Spring Spade Terminal
Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Tin

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------



Dimensions

Wire Size	5180 – 13100 CMA
Stud Diameter	4.17 mm[.164 in]
Tongue Thickness	1.07 mm[.042 in]
Product Length	28.2 mm[1.111 in]
Compatible Insulation Diameter (Max)	7.62 mm[.3 in]
Compatible Insulation Diameter Range	6.35 – 7.62 mm[.25 – .3 in]

Usage Conditions

Insulation Option	Partially Insulated
Operating Temperature Range	0 – 105 °C[0 – 221 °F]

Operation/Application

Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin

Industry Standards

Government Qualified Terminal	No
-------------------------------	----

Packaging Features

Packaging Quantity	500
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2392020-1
YELLOW BATTERY HHHT KIT 110V
(59287-2)

TE Part # 2392020-2
YELLOW BATTERY HHHT KIT 220V
(59287-2)

TE Part # 59287-2
HHHT PIDG PG 12-10 ASSY

Also in the Series | PLASTI-GRIP

Compression Connectors(3)


Crimp Wire Pins, Tabs & Ferrules(20)

Ring Terminals(310)

Spade Terminals(158)

Splices(45)

Customers Also Bought



TE Part #52939
[TERM.,PIDG SPR SPD 16-14,1/4](#)



TE Part #53242-1
[PG SPR SPD 22-16COM22-18MIL 10](#)



TE Part #3-640477-2
[02 CIR MTA156 ASSY ON TAPE LF](#)



TE Part #3-640477-3
[03P MTA156 ASSY ON TAPE LF](#)



TE Part #1625995-8
[HSC75 220R 5%](#)



TE Part #1-1744416-0
[10 POS EP II HSG, GLOW WIRE](#)



TE Part #CAT-G7534A-P729A
[Glow Wire Sig GRACE INERTIA Plug](#)



TE Part #7-2266067-7
[OCEAN_2.0_SPARE_PART_KIT-110F180F](#)

Documents

Product Drawings

[TERMINAL,PG SPR SPD 12-10 8](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG_CVM_CVM_52962-2_AB.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_52962-2_AB.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_52962-2_AB.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Application Specification](#)

English

Instruction Sheets

[Instruction Sheet \(U.S.\)](#)

English

[LARGE EXPANSION PRODUCTS \(FOR WIRE INSTULATION WITH 1/16" AND 5/64" WA](#)

English



Agency Approvals

UL Report

English

UL Report

English