




Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Disconnect**
Modular Terminal Block Product Type: **Screw Clamp Terminal Block**
Primary Product Color: **Blue Gray**
Product Spacing: **8 mm [.315 in]**
Number of Positions: **2**

Features

Product Type Features

Modular Terminal Block Product Type	Screw Clamp Terminal Block
-------------------------------------	----------------------------

Configuration Features

Number of Levels	1
Gauge Type	A3-B3
Number of Circuits	1
Block Function	Disconnect
Number of Positions	2

Electrical Characteristics

Power Loss	.58 W
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	300 V
Impulse Withstanding Voltage Rating (IEC)	6000 V
Current Rating (IEC)	18 A
Current Rating (UL)	18 A
Dielectric Withstanding Voltage (Max)	2200 V



Voltage Rating (IEC)	630 V
Voltage Rating (CSA)	300 V
Short-Time Withstanding Current Rating @ 1s	300 A

Body Features

Product Weight	17.6 g[.524 oz]
Primary Product Color	Blue Gray

Mechanical Attachment

DIN Rail Mounting Type	TH35-15, TH35-7.5
Terminal Block Disconnect Type	Lever
Connector Mounting Type	DIN Rail

Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Product Depth	45.6 mm
Tool Size	3.5 mm[.138 in]
Wire Stripping Length	11 mm[.433 in]
Main Circuit Capacity - 2 Rigid Stranded Conductors per Screw Clamp	24 – 14 AWG
Main Circuit Capacity - Twin Ferrule per Screw Clamp	24 – 14 AWG
Main Circuit Capacity - 2 Flexible Conductors per Screw Clamp	24 – 14 AWG
Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	24 – 10 AWG
Main Circuit Capacity - 1 Non-Insulated Ferrule per Screw Clamp	.22 – 4 mm ²
Main Circuit Capacity - 1 Insulated Ferrule per Screw Clamp	.22 – 4 mm ²
Main Circuit Capacity - 1 Flexible Conductor per Screw Clamp	24 – 10 AWG
Product Length	45.6 mm[1.8 in]
Product Height	59.7 mm
Product Spacing	8 mm[.315 in]

Usage Conditions

Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]

Industry Standards

IP Rating	IP20
-----------	------



UL Flammability Rating

UL 94V-0

Product Compliance



For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量超出标准 Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) SVHC > Threshold: Pb (3.5% in 74024578) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

			
---	--	---	---




TE Part # 1SNK900613R0000
PROCAP8



TE Part # 1SNK900001R0000
BAM4



TE Part # 1SNA173523R1100
PC81-10




TE Part # 1SNA168500R1200
PR4




TE Part # 1SNK508960R0000
ES4-SF




TE Part # 1SNK169999R0000
MC812PA



TE Part # 1SNA164800R0300
PR3.G2



TE Part # 1SNK160004R0000
MC812-YL



TE Part # 1SNA168700R2200
PR5



TE Part # 1SNK900624R0000
KCO




TE Part # 1SNK900611R0000
UMH




TE Part # 1SNK900002R0000
BAZ1



TE Part # 1SNA168672R1100
TGA8



TE Part # 1SNK900604R0000
CO




TE Part # 1SNA173220R0500
PR30



TE Part # 1SNA168675R1400
ANT


Also in the Series | **ENTRELEC SNK**



Modular Terminal Blocks(319)



Terminal Block & Strip Conducting Accessories(67)



Terminal Block & Strip Insulating Accessories(31)

Customers Also Bought



TE Part #1SNK140121R0000
MC512PA 111->120 (x10) Horizontal



TE Part #1SNK140061R0000
MC512PA 51->60 (x10) Horizontal



TE Part #1SNK506030R0000
ZS6-OR



TE Part #1SNK510010R0000
ZS16



TE Part #1SNK505320R0000
ZS4-S-BL



TE Part #1SNK140071R0000
MC512PA 61->70 (x10) Horizontal



TE Part #1SNK140101R0000
MC512PA 91->100 (x10) Horizontal



TE Part #1SNK140031R0000
MC512PA 21->30 (x10) Horizontal



TE Part #1SNK140111R0000
MC512PA 101->110 (x10) Horizontal



TE Part #1SNK140041R0000
MC512PA 31->40 (x10) Horizontal

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SNK508419R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SNK508419R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNK508419R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ENTRELEC Terminal Block - Master Catalog

ENTRELEC Terminal Block - Master Catalog

English

1SNK508419R0000

Screw Clamp Terminal Block, Disconnect, Blue Gray, 8 mm [.315 in] Spacing, 2 Position, DIN Rail, -55 – 110 °C [-67 – 230 °F], ENTRELEC SNK



[ZS4-S-R3-T2](#)

English

[SNK SERIES TERMINAL BLOCKS](#)

English