ES-BPC-C 16-25 BK - Connector

1106307

https://www.phoenixcontact.com/us/products/1106307

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connector, Range of articles: BPC, color: black, number of positions: 1, min. conductor cross section: 16 mm^2, max. conductor cross section: 25 mm^2, rated voltage: 1500, rated current: 120 A, Connection method: Crimp, Contact connection type: Socket, min. cable diameter: 7.2 mm, max. cable diameter: 10.7 mm

Your advantages

- Mismatching and short circuit proof
- Touch-proof
- Foolproof mechanism installed
- Safety lock
- 360° free rotation and flexible wiring
- Patented design, with 3 proofs and one rotation

Commercial data

Item number	1106307
Packing unit	20 pc
Minimum order quantity	20 pc
Sales key	AB04
Product key	ABLDBA
GTIN	4063151003456
Weight per piece (including packing)	39.04 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85359000
Country of origin	CN

Technical data

Notes

Safety note

Safety note	• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.
	• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
	• The products are suitable for applications in plant, controller, and electrical device engineering.
	• Assembled products may not be manipulated or improperly opened.
	• Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
	• When using the product in direct connection with third-party manufacturers, the user is responsible.
	• For operating voltages > 50 V AC, conductive connector housings must be grounded
	• Ensure that the protective or functional ground has been properly connected.
	• Observe the corresponding technical data. You will find information: o On the product o On the packing label o In the supplied documentation o Online at phoenixcontact.com/products under the product
	• The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.
	• Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products
	• The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).
	• Operate the connector only when it is fully plugged in and interlocked.
	• Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.

	• Observe the minimum bending radius of the cable. Lay the cable without twisting it.

Product properties

Product type	Connectors for energy storage
Product family	BPC
Number of positions	1

Insulation characteristics

Degree of pollution	2

Electrical properties

Rated voltage (III/2)	1500 V DC
Nominal voltage ATD	1500 (III/2.00) in accordance with IEC 61984
	1000 in accordance with UL 4128
Rated current	120 A (with 25 mm² conductor cross-section, in accordance with IEC 61984)
	76 A (with 16 mm² conductor cross-section, in accordance with IEC 61984)
	120 A (with AWG 4, in accordance with UL 4128)
Nominal voltage U_N	1000 V (in accordance with UL 4128)

Connection data

Connection method	Crimp
Tightening torque	1.5 ... 1.8 Nm

Material specifications

Color	black
Material	Polyamide
	Copper
	Silicon
Flammability rating according to UL 94	V0
Seal material	Silicon

Cable/line

External cable diameter	7.2 mm ... 10.7 mm
Single wire, cross section	16 mm² 25 mm²
Stripping length of the individual wire	23 mm ±1 mm

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	100
Insertion force	≤ 75 N

Environmental and real-life conditions

Ambient conditions

Degree of protection (when plugged in)	IP65 (Mating socket)
Degree of protection (not plugged in)	IP20
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Altitude	4000 m

Standards and regulations


Standards/specifications	IEC 61984:2008
	EN 61984:2008
	UL 4128
	PPP 51090A

Mounting

Assembly instructions	We recommend using the crimping dies and other crimping devices of Jiangsu Bozhiwang Automation Equipment Co., Ltd. for cable crimp connections; address: No. 39 Kun Lun Road, Xin Bei District, Changzhou, Jiangsu Province, China, email: flacz2020@163.com, die model: BZW-6F

Drawings

Dimensional drawing



Classifications

ECLASS

ECLASS-11.0	27060106
ECLASS-12.0	27060106
ECLASS-13.0	27060106

ETIM

ETIM 9.0	EC003250

UNSPSC

UNSPSC 21.0	26121600

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Accessories

ES-FT-BPC-B 16-25 BK - Connector

1130814

https://www.phoenixcontact.com/us/products/1130814



Connector, Range of articles: BPC, color: black, number of positions: 1, rated voltage: 1500, rated current: 120 A, Connection method: Screw connection, Contact connection type: Pin

ES-FT-BPC-S 16-25 BK - Connector

1106304

https://www.phoenixcontact.com/us/products/1106304



Connector, Range of articles: BPC, color: black, number of positions: 1, min. conductor cross section: 16 mm^2, max. conductor cross section: 25 mm^2, rated voltage: 1500, rated current: 120 A, Connection method: Screw connection, Contact connection type: Pin

ES-FT-BPC-C 16-25 BK - Connector

1228823

https://www.phoenixcontact.com/us/products/1228823



Connector, Range of articles: BPC, color: black, number of positions: 1, min. conductor cross section: 16 mm^2, max. conductor cross section: 25 mm^2, rated voltage: 1500, rated current: 120 A, Connection method: Crimp, Contact connection type: Pin

ES-FT-BPC-B/S 16-25 BK - Connector

1231639

https://www.phoenixcontact.com/us/products/1231639



Connector, Range of articles: BPC, color: black, number of positions: 1, min. conductor cross section: 16 mm^2, max. conductor cross section: 25 mm^2, rated voltage: 1500, rated current: 120 A, Connection method: Screw connection, Contact connection type: Pin

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com