



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Feed-Through**
Modular Terminal Block Product Type: **PI-Spring Terminal Block**
Primary Product Color: **Orange**
Product Spacing: **6 mm [.236 in]**
Number of Positions: **3**

Features

Product Type Features

Modular Terminal Block Product Type	PI-Spring Terminal Block
-------------------------------------	--------------------------

Configuration Features

Number of Levels	1
Gauge Type	2.9 mm Dia.
Number of Circuits	1
Block Function	Feed-Through
Number of Positions	3

Electrical Characteristics

Power Loss	1 W
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	600 V
Impulse Withstanding Voltage Rating (IEC)	8000 V
Current Rating (IEC)	32 A
Current Rating (UL)	30 A
Current Rating (CSA)	30 A



Dielectric Withstanding Voltage (Max)	2200 V
Voltage Rating (IEC)	1000 V
Voltage Rating (CSA)	600 V
Short-Time Withstanding Current Rating @ 1s	480 A

Body Features

Product Weight	11 g
Primary Product Color	Orange

Mechanical Attachment

DIN Rail Mounting Type	TH35-15, TH35-7.5
Connector Mounting Type	DIN Rail

Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Main Circuit Capacity - Twin Ferrule per Spring Clamp	26 – 18 AWG
Product Depth	41.1 mm
Tool Size	3.5 mm[.138 in]
Wire Stripping Length	12.5 mm
Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp	26 – 10 AWG
Main Circuit Capacity - 1 Non-Insulated Ferrule per Spring Clamp	26 – 12 AWG
Main Circuit Capacity - 1 Insulated Ferrule per Spring Clamp	26 – 12 AWG
Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp	.5 – 4 mm²
Product Length	41.1 mm
Product Height	72.5 mm
Product Spacing	6 mm[.236 in]

Usage Conditions

Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]

Industry Standards

IP Rating	IP20
UL Flammability Rating	UL 94V-0



Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1SNK900611R0000
UMH




TE Part # 1SNK900002R0000
BAZ1



TE Part # 1SNK900107R0000
CS-R3



TE Part # 1SNK705911R0000
EK2.5-3P



TE Part # 1SNA173220R0500
PR30



TE Part # 1SNK906303R0000
JB6-3



TE Part # 1SNK900612R0000
PROCAP6




TE Part # 1SNK900609R0000
PROCAP5



TE Part # 1SNK900001R0000
BAM4



TE Part # 1SNK906350R0000
JB6-50



TE Part # 1SNA168500R1200
PR4




TE Part # 1SNK150000R0000
MC612




TE Part # 1SNK149999R0000
MC512PA



TE Part # 1SNK900102R0000
BAZH1



TE Part # 1SNA164800R0300
PR3.G2



TE Part # 1SNA168700R2200
PR5



TE Part # 1SNK900205R0000
TP4



TE Part # 1SNK906302R0000
JB6-2




TE Part # 1SNK906304R0000
JB6-4



TE Part # 1SNK900603R0000
JB85-3


Also in the Series | ENTRELEC SNK



Modular Terminal Blocks(319)



Terminal Block & Strip Conducting Accessories(67)



Terminal Block & Strip Insulating Accessories(31)

Customers Also Bought

1SNK706031R0000

PI-Spring Terminal Block, Feed-Through, Orange, 6 mm [.236 in] Spacing, 3 Position, DIN Rail, -55 – 110 °C [-67 – 230 °F], ENTRELEC SNK



TE Part #1SNK706032R0000
ZK4-4P-OR



TE Part #1SNK706152R0000
ZK4-PE-4P



TE Part #2373921-3
CVTY PLUG,PIN DIA 2.5,CVTY DIA,2.5,
BLU



TE Part #2373921-4
CVTY PLUG,PIN DIA 1.6,CVTY DIA,2.0,
GRN



TE Part #6609048-5
6EQ1=F7262 S0

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SNK706031R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SNK706031R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNK706031R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ZK4-3P-OR

English

ENTRELEC Terminal Block - Master Catalog

ENTRELEC Terminal Block - Master Catalog

English

SNK SERIES TERMINAL BLOCKS

English

ENTRELEC Terminal Blocks Catalogue (RUS)

Agency Approvals

Bureau Veritas Marine and Offshore Certificate

1SNK706031R0000

PI-Spring Terminal Block, Feed-Through, Orange, 6 mm [.236 in] Spacing, 3 Position,
DIN Rail, -55 – 110 °C [-67 – 230 °F], ENTRELEC SNK



English