
RLC16-6-4-A

Ruland RLC16-6-4-A, 0.375" x 0.250" Long Slit Coupling, Aluminum, Clamp Style, 0.984" OD, 1.339" length





Description

Ruland RLC16-6-4-A is a clamp style slit coupling with 0.3750" x 0.2500" bores, 0.984" OD, and 1.339" length. It is manufactured from a single piece of material and has two sets of intermittent slit cuts allowing for a maintenance-free coupling with high torsional stiffness in relation to comparable couplings, such as beam type. RLC16-6-4-A is commonly used in precise positioning applications found in semiconductor, medical, and test and measurement equipment. This long style slit coupling has added torque and misalignment capabilities compared to the short style. RLC16-6-4-A is zero-backlash, has a balanced design for reduced vibration at speeds up to 10,000 RPM, and can accommodate all forms of misalignment with light bearing loads. It is manufactured by Reliance Precision Ltd. in their County Cork, Ireland factory from 7075 aluminum for lightweight and low inertia. RLC16-6-4-A is inventoried by Ruland and RoHS3 and REACH compliant.

Product Specifications

Bore (B1)	0.3750 in	**Small Bore (B2)**	0.2500 in
B1 Max Shaft Penetration	0.378 in	**B2 Max Shaft Penetration**	0.378 in
Outer Diameter (OD)	0.984 in	**Bore Tolerance**	+0.001 in / -0.000 in
Length (L)	1.339 in	**Clearance Diameter (C) MAX**	1.059 in
Cap Screw	M3	**Screw Material**	18-8 300 Series Stainless Steel
Hex Wrench Size	2.5 mm	**Screw Finish**	Bright
Seating Torque	1.10 Nm	**Number of Screws**	2
Dynamic Torque Reversing	13.7 lb-in	**Angular Misalignment**	3.0°
Dynamic Torque Non-Reversing	20.8 lb-in	**Parallel Misalignment**	0.016 in
Peak Torque	34.5 in-lb	**Axial Motion**	0.028 in
Torsional Stiffness	34.5 lb-in/Deg	**Moment of Inertia**	0.0106336 lb-in²
Maximum Speed	5,000 RPM	**Full Bearing Support Required?**	Yes
Zero-Backlash?	Yes	**Balanced Design**	Yes
Material Specification	7075-T651 Extruded and Drawn Aluminum Bar	**Temperature**	-110°F to 175°F (-80°C to 80°C)
Finish Specification	SurTec 650	**Manufacturer**	Reliance Precision Limited
Country of Origin	Ireland	**Weight (lbs)**	0.077300
UPC	634529301586	**Tariff Code**	8483.60.8000
UNSPC	31163003		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Prop 65			

⚠**WARNING** This product can expose you to the chemical Nickel (metallic), known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.