



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Ground**
Modular Terminal Block Product Type: **PI-Spring Terminal Block**
Primary Product Color: **Green & Yellow**
Product Spacing: **6 mm [.236 in]**
Number of Positions: **2**

Features

Product Type Features

Modular Terminal Block Product Type	PI-Spring Terminal Block
-------------------------------------	--------------------------

Configuration Features

Number of Levels	1
Gauge Type	2.9 mm Dia.
Number of Circuits	1
Block Function	Ground
Number of Positions	2

Electrical Characteristics

Impulse Withstanding Voltage Rating (IEC)	8000 V
Dielectric Withstanding Voltage (Max)	2200 V
Short-Time Withstanding Current Rating @ 1s	480 A

Body Features

Product Weight	12.6 g[.496 oz]
Primary Product Color	Green & Yellow

Termination Features

Termination Method to Wire & Cable	Spring Terminal
------------------------------------	-----------------

Mechanical Attachment



DIN Rail Mounting Type	TH35-15, TH35-7.5
Connector Mounting Type	DIN Rail

Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Product Depth	41.2 mm[1.622 in]
Tool Size	3.5 mm[.138 in]
Wire Stripping Length	12.5 mm[.492 in]
Main Circuit Capacity - Twin Ferrule per Spring Clamp	26 – 18 AWG
Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp	26 – 10 AWG
Main Circuit Capacity - 1 Non-Insulated Ferrule per Spring Clamp	26 – 12 AWG
Main Circuit Capacity - 1 Insulated Ferrule per Spring Clamp	26 – 12 AWG
Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp	.5 – 4 mm²
Product Length	41.2 mm[1.622 in]
Product Height	62.7 mm[2.468 in]
Product Spacing	6 mm[.236 in]
Wire Size	10 AWG

Usage Conditions

Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

IP Rating	IP20
UL Flammability Rating	UL 94V-0

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold



EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JUNE 2025 (250)
Candidate List Declared Against: JUNE 2025 (250)
Does not contain REACH SVHC

Halogen Content

Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not reviewed for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 1SNK900612R0000 PROCAP6	TE Part # 1SNK900609R0000 PROCAP5	TE Part # 1SNK900001R0000 BAM4	TE Part # 1SNA168500R1200 PR4
TE Part # 1SNK150000R0000 MC612	TE Part # 1SNK705910R0000 EK2.5	TE Part # 1SNK149999R0000 MC512PA	TE Part # 1SNK900659R0000 TO3.5-50-A







TE Part # 1SNK140000R0000
[MC512](#)



TE Part # 1SNK900203R0000
[TP2](#)




TE Part # 1SNA178529R0400
[PR50](#)



TE Part # 1SNA174300R1700
[PR3.Z2](#)




TE Part # 1SNK159999R0000
[MC612PA](#)



TE Part # 1SNK150004R0000
[MC612-YL](#)



TE Part # 1SNK900105R0000
[ES-TC6](#)




TE Part # 1SNK140004R0000
[MC512-YL](#)




TE Part # 1SNK900201R0000
[TC5-R1](#)



TE Part # 1SNK900102R0000
[BAZH1](#)



TE Part # 1SNA164800R0300
[PR3.G2](#)



TE Part # 1SNA168700R2200
[PR5](#)

Also in the Series | **ENTRELEC SNK**



[Modular Terminal Blocks\(319\)](#)




[Terminal Block & Strip Conducting Accessories\(67\)](#)




[Terminal Block & Strip Insulating Accessories\(31\)](#)


Customers Also Bought



TE Part #1SNK512020R0000
[ZS25-BL](#)



TE Part #1SNK705151R0000
[ZK2.5-PE-3P](#)



TE Part #1SNK705020R0000
[ZK2.5-BL](#)



TE Part #1SNK706066R0000
[ZK4-BK](#)



TE Part #1SNK705010R0000
[ZK2.5](#)



TE Part #1SNK708010R0000
[ZK6](#)



TE Part #1SNK705150R0000
[ZK2.5-PE](#)



TE Part #1SNK900606R0000
[LH-J](#)



TE Part #1SNK705210R0000
[ZK2.5-D2](#)



TE Part #1SNK705960R0000
[EK2.5-D2](#)

Documents

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_1SNK706150R0000_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SNK706150R0000_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SNK706150R0000_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[ZK4-PE](#)

English

[ENTRELEC Terminal Block - Master Catalog](#)

[ENTRELEC Terminal Block - Master Catalog](#)

English

[SNK SERIES TERMINAL BLOCKS](#)

English

[ENTRELEC Terminal Blocks Catalogue \(RUS\)](#)

[Essential Entrelec Terminal Blocks](#)

French

[Essential Entrelec Terminal Blocks](#)

1SNK706150R0000

PI-Spring Terminal Block, Ground, Green & Yellow, 6 mm [.236 in] Spacing, 2 Position,
Spring Terminal, Power & Signal, DIN Rail, 10 AWG, ENTRELEC SNK



English

[Essential Entrelec Terminal Blocks](#)

Japanese

[Agency Approvals](#)

[Bureau Veritas Marine and Offshore Certificate](#)

English