





REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN-9A0035~038	2009/04/15	Li Xiu Zhi	Change SR View & Update Note
C	LEN1480368~371	2014/08/06	Vicky	Update Logo



Conn.



Pin Assignments
Front View

7	White	白
6	Green	綠
5	Brown	棕
4	Red	紅
3	Yellow	黃
2	Orange	橘
1	Blue	藍
Conn.	Wire Color	
Pin Out		

CD-07AFFM-SL7AXX

XX :01~99Meters
01 :01Meter
02 :02Meters
:
99 :99Meters

Cable Length(L):01~99Meters

Note:

- * $\varnothing$ Important Dimension To Check
- * Waterproof Rate: IP67
- * Housing: Nylon+GF, Black
- * Female Pin: Copper Alloy, Gold Plated
- * Screw Nut: Nylon+GF, Black
- * O-Ring: EPDM, Black
- * Cable: UL2464 24AWG*7C+Drain+Al/My, Black,PVC Jacket,UV Resistant,OD=5.8
- * Cable Length Tolerance: 01M:±40mm
02M~05M:±60mm
06M~10M:±100mm
11M~30M:±200mm
31M~99M:±500mm

UNIT:mm		TITLE
TOLERANCE	±0.5 mm	Middle Cable Screw 7Pin F Conn F Pin
SCALE	1:1	SIZE A4
REV.	C	WC-REV. A.1
SHEET 1 OF 1		
QC: Inspection item		

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DWG NO	CUSTOMER	DRAWN BY	CHECKED BY	APPROVED BY	DATE
	CD-07AFFM-SL7AXX	ALTW	Vicky	Sam	Rita	2014-08-06
						2014-08-06
						2014-08-06

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.