

ATGBICS AFBR-79EEPZ-HPC Avago Broadcom Compatible
Transceiver QSFP+ 40GBase-CSR4 (850nm MMF 400m MPO DOM)

Brand : ATGBICS

Product code: AFBR-79EEPZ-HPC-C

Product name : AFBR-79EEPZ-HPC Avago Broadcom
Compatible Transceiver QSFP+ 40GBase-CSR4 (850nm MMF
400m MPO DOM)

AFBR-79EEPZ-HPC Avago Broadcom Compatible Transceiver QSFP+ 40GBase-CSR4 (850nm MMF 400m
MPO DOM)

ATGBICS AFBR-79EEPZ-HPC Avago Broadcom Compatible Transceiver QSFP+ 40GBase-CSR4 (850nm
MMF 400m MPO DOM):

ATGBICS Avago Broadcom compatible AFBR-79EEPZ-HPC QSFP+ 40GBase-CSR4 form factor network transceiver supports a distance of up to 400m over multi-mode fibre (MMF) using a wavelength of 850nm via an MPO-12 connector. This product operates within a commercial temperature range. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Avago Broadcom AFBR-79EEPZ-HPC and we proudly offer a compatibility guarantee and limited lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA (Multi-Source Agreement) and IEEE standards & protocols.

Performance		Power	
SFP transceiver type *	Fiber optic	Maximum voltage	3.5 V
Maximum data transfer rate *	40000 Mbit/s	Certificates	
Interface type *	QSFP+	Compliance certificates	TÜV mark, UKCA, UL, US FDA, REACH, Federal Communications Commission (FCC), RoHS, CE
Single-mode fiber (SMF) supported	✗	Certification	CE, FCC, RoHS, REACH
Multi-mode fiber (MMF) supported	✓	Sustainability	
Fiber optic connector	MPO-12	Sustainability compliance	✓
SFP transceiver standard	CSR4	Doesn't contain	Lead
Maximum transfer distance	400 m	Operational conditions	
Wavelength	850 nm	Minimum operating temperature	0 °C
Ethernet LAN	✓	Maximum operating temperature	70 °C
Ethernet interface type	40 Gigabit Ethernet	Operating temperature (T-T)	0 - 70 °C
Fiber ethernet cabling technology	40GBASE	Storage temperature (T-T)	-40 - 85 °C
Digital Diagnostics Monitoring (DDM)	✓	Operating relative humidity (H-H)	0 - 95%
Wavelength-division multiplexing (WDM)	✗	Storage relative humidity (H-H)	0 - 95%
Features		Weight & dimensions	
Product colour	Silver	Width	13.5 mm
Housing material	Metal	Depth	72.4 mm
Plug and Play	✓	Height	18.4 mm
Hot-Plug support	✓	Weight	100 g
Hot-swap	✓	Packaging content	
Easy to install	✓	Quantity per pack	1 pc(s)
Brand compatibility	Avago Technologies	Packaging data	
Power		Package type	Box
Input voltage	3.3 V	Logistics data	
		Country of origin	United Kingdom



Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.