









A1

CCT	A	B
2	5.0	9.9
3	10.0	14.9
4	15.0	19.9
5	20.0	24.9
6	25.0	29.9
7	30.0	34.9
8	35.0	39.9

SHIPPING ARRANGEMENT



- NOTES:
- REFER TO PRODUCT SPECIFICATION: PS-93270-001.
 - MATERIAL: HOUSING - PA66
UL94-V0, COLOUR: BLACK.
TERMINAL: COPPER ALLOY 0.30 REF. THICK - PLATING
HOT TIN DIP.
 - COLOUR STRIPE IS OPTIONAL. AVAILABLE IN THE FOLLOWING
COLOURS: YELLOW, RED, GREEN, BLUE, BLACK & ORANGE.
 - REFER TO PACKAGING SPEC (PK-93270-001)
 - REFER TO APPLICATION SPEC (AS-93270-001)
LAST INSPECTION NUMBER : 14


THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS	SCALE	CURRENT REV DESC:		molex				
mm	20:1							
GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 761927 DRWN: RAHULH3 CHK'D: RAHULH3 APPR: MRAMAKRISHNA 2023/09/18 2023/09/18 2023/09/19		R POWER 10 A, 0.75MM2 BLACK LATI 5MM TERMINAL PITCH (MATL: NYLON PA66)				
ANGULAR TOL ± 0.5 °								
4 PLACES	±			PRODUCT CUSTOMER DRAWING				
3 PLACES	± 0.05							
2 PLACES	± 0.1							
1 PLACE	± 0.2							
0 PLACES	±	INITIAL REVISION:		DOCUMENT NUMBER	DOC TYPE	DOC PART	REVISION	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER		SHEET NUMBER
			A2-SIZE	220958	SEE TABLE	GENERAL MARKET		1 OF 9


2023/09/18	2022/05/30	2209580001	PSD	000	A2
------------	------------	------------	-----	-----	----

SINGLE ROW CODING KEYS OPEN
END WALLS WITH LATCHES

END WALLS OPEN	
FIRST END WALL	LAST END WALL
OPEN	OPEN




- PCB LAYOUT FOR 4CCT CONNECTOR (WITH NO OPTIONAL POSITIONAL RIB SLOT) (WITH HOLES FOR OPTIONAL INTERNAL LATCHES)
- RECOMMENDED PCB THICKNESS 1.5±0.14




SINGLE ROW CODING KEYS OPTION A
END WALLS WITH POLARIZING RIBS

OPTION A END WALLS	
FIRST END WALL	LAST END WALL
SHORT	CLOSED




- PCB LAYOUT FOR 4CCT CONNECTOR (WITH OPTIONAL POSITIONAL RIB SLOT BETWEEN CCTS 1&2)
- RECOMMENDED PCB THICKNESS 1.5±0.14




2 ROW CODING KEYS OPTION B
END WALLS WITH POLARIZING RIBS

OPTION B END WALLS	
FIRST END WALL	LAST END WALL
CLOSED	SHORT




- PCB LAYOUT FOR 4CCT CONNECTOR (WITH OPTIONAL POSITIONAL RIB SLOT BETWEEN CCTS 3&4)
- RECOMMENDED PCB THICKNESS 1.5±0.14




- NOTES:
1. ALL UNSPECIFIED DIMENSIONS SEE SHEET 1
 2. PCB FEATURES WHEN USED ARE IDENTICAL IN SIZE AND POSITION ACROSS PCB OPTIONS
 3. OPTIONS SHOWN ARE FOR REFERENCE ONLY, FOR PART CONFIGURATIONS SEE SHEETS 4-8
 4. FOR PARTS NOT LISTED ON THIS DRAWING PLEASE CONTACT YOUR MOLEX SALES ENGINEER

1 ROW CODING KEYS OPTION C
END WALLS WITH POLARIZING RIBS

OPTION C END WALLS	
FIRST END WALL	LAST END WALL
OPEN	CLOSED




- PCB LAYOUT FOR 4CCT CONNECTOR (WITH OPTIONAL POSITIONAL RIB SLOT BETWEEN CCTS 1&2)
- RECOMMENDED PCB THICKNESS 1.5±0.14




THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION												
DIMENSION UNITS		SCALE	CURRENT REV DESC:				molex R POWER 10 A, 0.75MM2 BLACK LATI 5MM TERMINAL PITCH (MATL: NYLON PA66)					
mm		1:1										
GENERAL TOLERANCES (UNLESS SPECIFIED)			EC NO: 761927 DRWN: RAHULH3 2023/09/14 CHK'D: RAHULH3 2023/09/18 APPR: MRAMAKRISHNA 2023/09/19 INITIAL REVISION: DRWN: MBN02 2022/05/30 APPR: MRAMAKRISHNA 2023/02/08				PRODUCT CUSTOMER DRAWING					
ANGULAR TOL	±	0.5 °					DOCUMENT NUMBER			DOC TYPE	DOC PART	REVISION
4 PLACES	±						2209580001			PSD	000	A2
3 PLACES	±	0.05										
2 PLACES	±	0.1										
1 PLACE	±	0.2										
0 PLACES	±		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER	
				A2-SIZE	220958	SEE TABLE	GENERAL MARKET	2 OF 9				

1 ROW CODING KEYS OPTION D
END WALLS WITH POLARIZING RIBS




OPTION D END WALLS	
FIRST END WALL	LAST END WALL
CLOSED	OPEN

- PCB LAYOUT FOR 4CCT CONNECTOR (WITH OPTIONAL POSITIONAL RIB SLOT BETWEEN CCTS 3&4)
- RECOMMENDED PCB THICKNESS 1.5±0.14




1 ROW CODING KEYS
OPTION E END WALLS




OPTION E END WALLS	
FIRST END WALL	LAST END WALL
CLOSED	CLOSED

- PCB LAYOUT FOR 4CCT CONNECTOR (WITH NO OPTIONAL POSITIONAL RIB SLOTS)
- RECOMMENDED PCB THICKNESS 1.5±0.14




1 ROW CODING KEYS OPTION F
END WALLS WITH POLARIZING RIBS



OPTION F END WALLS	
FIRST END WALL	LAST END WALL
NARROW FLUSH	OPEN

OPTION F: FIRST END NARROW FLUSH
LAST END WALL OPEN
SHOWN WITH SINGLE ROW CODING KEYS
RIB SHOWN BETWEEN CCTS 3&4





- NOTES:
1. ALL UNSPECIFIED DIMENSIONS SEE SHEET 1
 2. PCB FEATURES WHEN USED ARE IDENTICAL IN SIZE AND POSITION ACROSS PCB OPTIONS
 3. OPTIONS SHOWN ARE FOR REFERENCE ONLY, FOR PART CONFIGURATIONS SEE SHEETS 4-8
 4. FOR PARTS NOT LISTED ON THIS DRAWING PLEASE CONTACT YOUR MOLEX SALES ENGINEER

1 ROW CODING KEYS OPTION G
END WALLS WITH POLARIZING RIBS

OPTION G END WALLS	
FIRST END WALL	LAST END WALL
OPEN	NARROW FLUSH

OPTION G: FIRST END OPEN
LAST END WALL NARROW FLUSH
SHOWN WITH SINGLE ROW CODING KEYS
RIB SHOWN BETWEEN CCTS 3&4



THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
DIMENSION UNITS		SCALE		CURRENT REV DESC:					
mm		1:1							
GENERAL TOLERANCES (UNLESS SPECIFIED)									
ANGULAR TOL		± 0.5 °							
4 PLACES		±							
3 PLACES		± 0.05							
2 PLACES		± 0.1							
1 PLACE		± 0.2							
0 PLACES		±							
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER	
				A2-SIZE		220958		SEE TABLE	
								CUSTOMER	
								GENERAL MARKET	
								SHEET NUMBER	
								3 OF 9	

molex




R POWER 10 A, 0.75MM2 BLACK LATI
5MM TERMINAL PITCH (MATL: NYLON PA66)

PRODUCT CUSTOMER DRAWING



DOCUMENT NUMBER	DOC TYPE	DOC PART	REVISION
2209580001	PSD	000	A2

DOCUMENT STATUS	P1	RELEASE DATE	2023/09/19	05:47:59
-----------------	----	--------------	------------	----------

2 CIRCUIT

PART NUMBER	HOUSING USED	TERMINAL No.	TERMINAL VOID POSITION	REMOVED CODING KEYS	CONFIGURATION	LATCH BETWEEN	POLARIZING RIB BETWEEN	FIRST ENDWALL	LAST ENDWALL	COLOUR STRIPE
220958-0001	220850-0002	93268-0004	NONE	NONE		NONE	NONE	OPEN	OPEN	NONE
220958-0002	220851-2002	93268-0004	NONE	NONE		CCT 1 & 2	NONE	OPEN	OPEN	NONE
220958-0003	220852-7202	93268-0004	NONE	NONE		CCT 1 & 2	NONE	OPEN	OPEN	NONE

KEYING, CODING & LATCH IDENTIFICATION VIEWED IN MATING DIRECTION




NOTES

- 1. + DENOTES TERMINAL VOIDED POSITION
⊕ DENOTES TERMINAL LOADED POSITION
| DENOTES POLARIZING RIB POSITION
- 2. MOLEX HOUSING NO. FOR REFERENCE ONLY

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
DIMENSION UNITS	SCALE	CURRENT REV DESC:							
mm	1:1								
GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 761927 DRWN: RAHULH3 2023/09/14 CHK'D: RAHULH3 2023/09/18 APPR: MRAMAKRISHNA 2023/09/19 INITIAL REVISION: DRWN: MBN02 2022/05/30 APPR: MRAMAKRISHNA 2023/02/08				R POWER 10 A, 0.75MM2 BLACK LATI 5MM TERMINAL PITCH (MATL: NYLON PA66)			
ANGULAR TOL	± 0.5 °					PRODUCT CUSTOMER DRAWING			
4 PLACES	±					DOCUMENT NUMBER			
3 PLACES	± 0.05					2209580001			
2 PLACES	± 0.1					DOC TYPE DOC PART REVISION			
1 PLACE	± 0.2					PSD 000 A2			
0 PLACES	±					SHEET NUMBER			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER		SHEET NUMBER	
			A2-SIZE	220958	SEE TABLE	GENERAL MARKET		4 OF 9	

4 CIRCUIT

PART NUMBER	HOUSING USED	TERMINAL No.	TERMINAL VOID POSITION	REMOVED CODING KEYS	CONFIGURATION	LATCH BETWEEN	POLARIZING RIB BETWEEN	FIRST ENDWALL	LAST ENDWALL	COLOUR STRIPE
220958-2001	220850-0004	93268-0004	NONE	NONE	⊕ ⊕ ⊕ ⊕ 1234	NONE	NONE	OPEN	OPEN	NONE



THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION															
DIMENSION UNITS		SCALE		CURRENT REV DESC:				molex							
mm		1:1													
GENERAL TOLERANCES (UNLESS SPECIFIED)								EC NO: 761927 DRWN: RAHULH3 2023/09/14 CHK'D: RAHULH3 2023/09/18 APPR: MRAMAKRISHNA 2023/09/19				R POWER 10 A, 0.75MM2 BLACK LATI 5MM TERMINAL PITCH (MATL: NYLON PA66)			
ANGULAR TOL		±	0.5 °	PRODUCT CUSTOMER DRAWING											
4 PLACES		±		DOCUMENT NUMBER		DOC TYPE						DOC PART		REVISION	
3 PLACES		±	0.05	2209580001		PSD						000		A2	
2 PLACES		±	0.1	INITIAL REVISION:											
1 PLACE		±	0.2	DRWN: MBN02 2022/05/30											
0 PLACES		±		APPR: MRAMAKRISHNA 2023/02/08											
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER	
						A2-SIZE		220958		SEE TABLE		GENERAL MARKET		6 OF 9	

