



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Header**

PCB Mount Orientation: **Vertical**

Connector System: **Wire-to-Board**

Number of Positions: **4**

Centerline (Pitch): **5.08 mm [.2 in]**

Features

Product Type Features

Mixed & Hybrid Header	No
Connector Shape	Rectangular
PCB Connector Type	PCB Mount Header
Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Number of Columns	4
Number of Loaded Positions	4
Connector Contact Load Condition	Fully Loaded
PCB Mount Orientation	Vertical
Number of Positions	4
Number of Rows	1



Number of Power Positions	4
---------------------------	---

Electrical Characteristics

Operating Voltage	250 VAC
-------------------	---------

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Contact Underplating Material	Nickel
Contact Underplating Material Thickness	1.27 – 1.79 µm[50 – 70 µin]
Contact Size	2.95mm
PCB Contact Termination Area Plating Material Thickness	3.81 – 5.08 µm[150 – 200 µin]
Contact Shape & Form	Round
Contact Layout	Inline
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material	Pre-Tin
Contact Mating Area Plating Material Thickness	3.81 – 5.08 µm[150 – 200 µin]
Contact Type	Socket
Contact Current Rating (Max)	12 A
PCB Contact Termination Area Plating Material	Pre-Tin

Termination Features

Termination Post & Tail Diameter	1.57 mm[.062 in]
Termination Post & Tail Length	3.94 mm[.155 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Panel Mount Feature	Without
Mating Retention Type	Detent Lock
Mating Alignment Type	Polarization
PCB Mount Alignment	Without
Mating Retention	With
PCB Mount Retention	Without
Connector Mounting Type	Board Mount
Mating Alignment	With

Housing Features



Mating Entry Location	Top
Centerline (Pitch)	5.08 mm[.2 in]
Housing Material	Nylon

Dimensions

Connector Width	9.65 mm[.38 in]
PCB Thickness (Recommended)	1.57 mm[.062 in]
Connector Height	11.18 mm[.44 in]
Connector Length	25.4 mm[1 in]
Profile Height from PCB	11.56 mm[.455 in]

Usage Conditions

Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
UL Rating	Certified, Recognized
Compatible With Approved Standards Products	UL E28476
Glow Wire Rating	Standard Part - Not Glow Wire
UL Flammability Rating	UL 94V-2

Packaging Features

Packaging Quantity	1
Packaging Method	Package

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC



Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 174804-1
M-N-L PIN HDR W/FIX BELT H 4P



TE Part # 1-480426-0
04P CMNL CAP HSG F/H NATL



TE Part # 174552-1
4P C-MNL PIN HDR R/A

Also in the Series | Commercial MATE-N-LOK



Connector Caps & Covers(2)




Connector Contacts(150)



Connector Seals & Cavity Plugs(1)



Insertion & Extraction Tools(3)



PCB Headers & Receptacles(55)




Power Contacts(146)



Rectangular Power Connectors(181)



Standard Circular Connectors(2)




Wire-to-Board Headers & Receptacles
(55)


Customers Also Bought



TE Part #806064-SF
FN2060A-20-08



TE Part #87499-4
02 MODIV HSG COMP SR .100CL



TE Part #1-87499-4
08 MODIV HSG COMP SR .100CL



TE Part #148714-1
ASSY,PIN,EURO,"C/2",L-FREE,



TE Part #9-1617748-2
FCA-210-0919M=M83536/9-019M



TE Part #1617754
FCA-410-1517M=M83536/15-017M



TE Part #1658623-2
14 NOVO MIL 30DP, LEAD FREE



TE Part #1775073-1
SHIELD FINGER 434025N7



TE Part #1775441-5
EMIX CONN., 1.5MM PITCH, RCPT,
HSG, 5P



TE Part #6609104-5
PE0SSSS60=C1130

Documents

Product Drawings
04P CMNL SOK HDR ASSY
English

CAD Files
3D PDF
English

Customer View Model
ENG_CVM_770997-1_C.2d_dxf.zip



English

Customer View Model

[ENG_CVM_770997-1_C.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_770997-1_C.3d_stp.zip](#)

English

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_770997-1_B.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_770997-1_B.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_770997-1_B.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[SOFT_SHELL_PIN_SOCKET_CONNECTORS_STANDARD_DENSITY](#)

English

Product Specifications

[Application Specification](#)

English