VAL-US-240/40-P - Type 1 surge protection plug

2910336

https://www.phoenixcontact.com/us/products/2910336

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



UL Recognized type 1 SPD and IEC type 2 surge protection plug with a varistor and thermal disconnect for use with VAL-US base elements, mechanical and visual fault warning

Product description

Surge protective device replacement plug

Commercial data

Item number	2910336
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CL18
Product key	CL1321
Catalog page	Page 93 (C-4-2019)
GTIN	4055626444482
Weight per piece (including packing)	52.5 g
Weight per piece (excluding packing)	46 g
Customs tariff number	85363030
Country of origin	DE

Technical data

Notes

General	Used in:

Product properties

Product type	Replacement plug
Product family	VALVETRAB MS
IEC test classification	II
	T2
EN type	T2
Type	Male
Number of positions	1
Surge protection fault message	optical

Insulation characteristics

Overvoltage category	III
Pollution degree	2


Electrical properties

Nominal frequency f_N	50 Hz (60 Hz)

Connection data

Connection method	VALVETRAB plug-in system

Dimensions

Dimensional drawing	
Width	17.5 mm
Height	52.4 mm
Depth	55.3 mm
Horizontal pitch	1 Div.

Material specifications

Color	black (RAL 9005)
Flammability rating according to UL 94	V-0
CTI value of material	600
Insulating material	PA 6.6/PBT
Material group	I
Housing material	PA 6.6

	PBT

Protective circuit

Mode of protection	L-N
	L-PEN
	N-PE
Direction of action	1L-N/PE
Nominal voltage U_N	240/415 V AC
Nominal frequency f_N	50 Hz (60 Hz)
Maximum continuous voltage U_C	385 V AC
Residual current I_{PE}	≤ 450 µA
Standby power consumption P_C	≤ 175.00 mVA
Nominal discharge current I_n (8/20) µs	20 kA
Maximum discharge current I_{max} (8/20) µs	40 kA
Short-circuit current rating I_{SCCR}	25 kA
Voltage protection level U_p	≤ 1.8 kV
Residual voltage U_{res}	≤ 1.8 kV (at I_n)
	≤ 1.6 kV (at 10 kA)
	≤ 1.4 kV (at 5 kA)
	≤ 1.3 kV (at 3 kA)
TOV behavior at U_T	415 V AC (5 s / withstand mode)
	440 V AC (120 min / withstand mode)
Max. backup fuse with branch wiring	100 A (gG)

Additional technical data

Maximum discharge current I_{max} (8/20) µs	40 kA

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m (amsl)
Permissible humidity (operation)	5 % ... 95 %
Shock (operation)	25g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)
Vibration (operation)	5g (10 ... 500 Hz / 2.5 h / X, Y, Z)

Approvals

UL specifications

Maximum continuous operating voltage MCOV	385 V AC
Short-circuit current rating (SCCR)	200 kA
Voltage protection rating VPR	1200 V
UL type	type 1
Nominal discharge current I_n	20 kA

Maximum Surge Current per Phase	40 kA
Mode of protection	L-N
	L-G
	N-G
Nominal voltage	240/480 V AC
Power distribution system	Single phase
Nominal frequency	50/60 Hz
SPD Type	1CA

Standards and regulations

Air clearances and creepage distances

Standards/regulations	EN 60664-1 / EN 61643-11
Standards/specifications	IEC 61643-11
Note	2011
Standards/specifications	EN 61643-11
Note	2012

Mounting


Mounting type	on base element

Drawings

Circuit diagram



Dimensional drawing



Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2910336

cUL Recognized
Approval ID: FILE E 330181

UL Recognized
Approval ID: FILE E 330181

cULus Recognized

Classifications

ECLASS

ECLASS-11.0	27130890
ECLASS-13.0	27171292

ETIM

ETIM 8.0	EC002496

UNSPSC

UNSPSC 21.0	39121600

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Accessories

VAL-US-240/40/1+0-FM - Type 1 surge protection device

2910361

https://www.phoenixcontact.com/us/products/2910361



Surge protective device, single channel with remote indicator contact for 240 V AC.

VAL-US-240/40/1+1-FM - Type 1 surge protection device

2910362

https://www.phoenixcontact.com/us/products/2910362



Surge protective device, two channel with remote indicator contact for 240 V AC, 2-wire plus ground.

VAL-US-240/40/2+0-FM - Type 1 surge protection device

2910364

https://www.phoenixcontact.com/us/products/2910364



Surge protective device, two channel with remote indicator contact for 240/480 V split phase AC, 3-wire.

VAL-US-240/40/2+1-FM - Type 1 surge protection device

2910365

https://www.phoenixcontact.com/us/products/2910365



Surge protective device, three channel with remote indicator contact for 240/480 V split phase AC, 3-wire plus ground.

VAL-US-240/40/3+0-FM - Type 1 surge protection device

2910366

https://www.phoenixcontact.com/us/products/2910366



Surge protective device, three-channel with remote indicator contact for 240/480 V split-phase or 240/415 V Wye three-phase AC, 4-wire.

VAL-US-240/40/3+1-FM - Type 1 surge protection device

2910367

https://www.phoenixcontact.com/us/products/2910367



Surge protective device, four channel with remote indicator contact for 240/415 V AC, 4-wire plus ground.

VAL-US-240/40-P - Type 1 surge protection plug

2910336

https://www.phoenixcontact.com/us/products/2910336

VAL-US-480HLD/30/3+1V-FM - Type 1 surge protection device

2910387

https://www.phoenixcontact.com/us/products/2910387



Surge protective device, four channel with remote indicator contact for 480 V AC high-leg DELTA.

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com