DAISY-7X1-O

~25 + 70° oval beam



SPECIFICATION:

Dimensions	279.5 x 39.6 mm
Height	20.3 mm
Fastening	pin, screw, clips
ROHS compliant	yes

MATERIALS:

Component	Type	Material	Colour	Finish	Length
C17538_DAISY-7X1-O	Linear lens	PMMA	clear		19.0
C19642_DAISY-7X1-SHD3-MET-MATT	Shade	PC	metal	matt	
C19641_DAISY-7X1-SHD3-MET	Shade	PC	metal	gloss	
C19315_DAISY-7X1-SHD3-WHT-MATT	Shade	PC	white	matt	
C19314_DAISY-7X1-SHD3-WHT	Shade	PC	white	gloss	
C19313_DAISY-7X1-SHD3-MATT	Shade	PC	black	matt	
C19312_DAISY-7X1-SHD3	Shade	PC	black	gloss	
C18409_DAISY-7X1-SHD-MET-MATT	Shade	PC	metal	matt	279.5
C18167_DAISY-7X1-SHD-MET	Shade	PC	metal	gloss	
C17225_DAISY-7X1-SHD-WHT-MATT	Shade	PC	white	matt	279.5
C17051_DAISY-7X1-SHD-MATT	Shade	PC	black	matt	279.5
C16876_DAISY-7X1-SHD-WHT	Shade	PC	white	gloss	279.5
C16872_DAISY-7X1-SHD	Shade	PC	black	gloss	

ORDERING INFORMATION:

Quantities for one set:

Linear lens 1

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

Component		Qty in box	MOQ	MPQ	Box weight (kg)
C17538_DAISY-7X1-O » Box size: 400 x 300 x 300 mm	Linear lens	312	312	24	7.0
C18409_DAISY-7X1-SHD-MET-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.0
C19641_DAISY-7X1-SHD3-MET » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.1
C17051_DAISY-7X1-SHD-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.3
C19312_DAISY-7X1-SHD3 » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.1
C19642_DAISY-7X1-SHD3-MET-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	5.7
C17225_DAISY-7X1-SHD-WHT-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.6
C19313_DAISY-7X1-SHD3-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	5.8
C19314_DAISY-7X1-SHD3-WHT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.3
C16872_DAISY-7X1-SHD » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.1
C18167_DAISY-7X1-SHD-MET » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.0
C19315_DAISY-7X1-SHD3-WHT-MATT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	6.2
C16876_DAISY-7X1-SHD-WHT » Box size: 595 x 360 x 230 mm	Shade	156	312	24	7.6

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.





See also our general installation guide: www.ledil.com/installation_guide

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LED	LED Line SMD L28W2 TW Module 20mm 2800Lm Daisy 7
FWHM / FWTM	70.0 + 22.0° / 88.0 + 52.0°
Efficiency	70 %
Peak intensity	1.4 cd/lm
LEDs/each optic	2
Light colour/type	Tunable White
Required components:	
C17051_DAISY-7X1-SHD-MATT	





Light distribution files

LED	LED Line SMD L28W2 White Module 20mm 2800Lm Daisy
FWHM / FWTM	70.0 + 22.0° / 88.0 + 52.0°
Efficiency	70 %
Peak intensity	1.4 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
C17051_DAISY-7X1-SHD-MATT	





Light distribution files

LUMILEDS

LED	LUXEON HL2Z
FWHM / FWTM	71.0 + 23.0° / 88.0 + 54.0°
Efficiency	72 %
Peak intensity	1.3 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
C17051_DAISY-7X1-SHD-MATT	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

MST Your solutions

LED	LinLED 280x28mm 1600lm 840 4C 21V DAISY 7x1(ZT25)
FWHM / FWTM	70.0 + 26.0° / 85.0 + 59.0°
Efficiency	72 %
Peak intensity	1.2 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
C16872_DAISY-7X1-SHD





Light distribution files

NICHIA

LED	NCSxE17A
FWHM / FWTM	70.0 + 20.0° / 84.0 + 53.0°
Efficiency	70 %
Peak intensity	1.4 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
C17051_DAISY-7X1-SHD-MATT





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

LUMILEDS

LED	LUXEON 2835 Line
FWHM / FWTM	69.0 + 24.0° / 92.0 + 57.0°
Efficiency	83 %
Peak intensity	1.4 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
C16872_DAISY-7X1-SHD	



Light distribution files

LUMILEDS

LED	LUXEON 5050 HE
FWHM / FWTM	76.0 + 38.0° / 92.0 + 64.0°
Efficiency	86 %
Peak intensity	1.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C17533_DAISY-7X1-SHD-MET-MATT	



LUMILEDS

LED	LUXEON 5050 HE
FWHM / FWTM	76.0 + 38.0° / 92.0 + 64.0°
Efficiency	82 %
Peak intensity	1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C17051_DAISY-7X1-SHD-MATT	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

NICHIA

LED	NCSxE17A
FWHM / FWTM	72.0 + 20.0° / 86.0 + 44.0°
Efficiency	81 %
Peak intensity	1.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C16872_DAISY-7X1-SHD	



Light distribution files

NICHIA

LED	NVSxE21A
FWHM / FWTM	72.0 + 22.0° / 88.0 + 46.0°
Efficiency	80 %
Peak intensity	1.6 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
C16872_DAISY-7X1-SHD	



Light distribution files

OSRAM
Opto Semiconductors

LED	Duris S8
FWHM / FWTM	76.0 + 41.0° / 91.0 + 64.0°
Efficiency	83 %
Peak intensity	1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C16872_DAISY-7X1-SHD	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors

LED	OSCONIQ S 5050
FWHM / FWTM	76.0 + 40.0° / 90.0 + 64.0°
Efficiency	83 %
Peak intensity	1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C16872_DAISY-7X1-SHD	



Light distribution files

SAMSUNG

LED	LM28xB Series
FWHM / FWTM	73.0 + 34.0° / 91.0 + 62.0°
Efficiency	82 %
Peak intensity	1.1 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
C16872_DAISY-7X1-SHD	



Light distribution files

SAMSUNG

LED	LM28xB Series
FWHM / FWTM	73.0 + 34.0° / 91.0 + 62.0°
Efficiency	82 %
Peak intensity	1.1 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
C17051_DAISY-7X1-SHD-MATT	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

SAMSUNG

LED	LM301B
FWHM / FWTM	70.0 + 27.0° / 94.0 + 54.0°
Efficiency	85 %
Peak intensity	1.5 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
C16872_DAISY-7X1-SHD	



SAMSUNG

LED	LM301B
FWHM / FWTM	70.0 + 27.0° / 94.0 + 56.0°
Efficiency	88 %
Peak intensity	1.5 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	
C17051_DAISY-7X1-SHD-MATT	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Poznan, Poland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.