SD FLASH 32GB PLCNEXT MEMORY LIC - Program / configuration memory

1151111

https://www.phoenixcontact.com/us/products/1151111

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Program and configuration memory for storing the application programs, licenses, and other files in the file system of the PLC, plug-in, 32 GB.

Your advantages

- For storing application programs, the licenses, and other files in the file system of the PLC
- Program and configuration memory

Commercial data

Item number	1151111
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DR09
Product key	DRADZA
GTIN	4063151147570
Weight per piece (including packing)	9.7 g
Weight per piece (excluding packing)	9 g
Customs tariff number	85235190
Country of origin	DE

Technical data

Product properties

Product type	Storage medium
Application	Program/configuration memory
Mounting position	vertical

Electrical properties

Maximum power dissipation for nominal condition	0.264 W

Supply

Supply voltage	3.3 V DC
Supply voltage range	2.7 V DC ... 3.6 V DC
Typical current consumption	typ. 80 mA

Material specifications

Housing material	Plastic

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C

Mounting

Mounting position	vertical

Classifications

ECLASS

ECLASS-11.0	27242212
ECLASS-13.0	27242212
ECLASS-12.0	27242212

ETIM

ETIM 9.0	EC000192

UNSPSC

UNSPSC 21.0	32101600

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Accessories

RFC 4072S - Safety controller

1051328

https://www.phoenixcontact.com/us/products/1051328



PLCnext Control with 4 x 10/100/1000 Ethernet, PROFINET controller with integrated PROFIsafe safety controller, PROFINET device, IP20 degree of protection, pluggable parameterization memory

AXC F 3152 - Controller

1069208

https://www.phoenixcontact.com/us/products/1069208



PLCnext Control for the direct control of Axioline F I/Os. With three independent Ethernet interfaces. Complete with connector and bus base module.

SD FLASH 32GB PLCNEXT MEMORY LIC - Program / configuration memory

1151111

https://www.phoenixcontact.com/us/products/1151111

AXC F 2152 - Controller

2404267

https://www.phoenixcontact.com/us/products/2404267



PLCnext Control for the direct control of Axioline F I/Os. With two Ethernet interfaces. Complete with connector and bus base module.

AXC F 1152 - Controller

1151412

https://www.phoenixcontact.com/us/products/1151412



PLCnext Control for the direct control of Axioline F I/Os. With two Ethernet interfaces. Complete with connector and bus base module.

SD FLASH 32GB PLCNEXT MEMORY LIC - Program / configuration memory

1151111

https://www.phoenixcontact.com/us/products/1151111

SOL-SA-PCU-41XX - Controller

1114234

https://www.phoenixcontact.com/us/products/1114234



PLCnext Control based on AXC F 2152. Prepared for a customer-specific application with a power generation plant controller. Basis for the feed-in management of power generation systems that feed into medium- and high-voltage grids. Certified in accordance with VDE-AR-N 4110/4120.

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com