



Connectors > Connector Accessories > Connector Hardware > Double Sided QLPIN Bulkhead



Hardware Accessory Function: **Latching, Locking & Retention**

Connector Hardware Accessory Type: **Quick Lock Pins**

Operating Temperature (Max): **90 °C [194 °F]**

Operating Temperature Range: **-40 – 90 °C [-40 – 194 °F]**

[All Double Sided QLPIN Bulkhead \(6\)](#)

Features

Product Type Features

Hardware Accessory Function	Latching, Locking & Retention
Connector Hardware Accessory Type	Quick Lock Pins

Mechanical Attachment

Thread Size	None
-------------	------

Usage Conditions

Operating Temperature (Max)	90 °C[194 °F]
Operating Temperature Range	-40 – 90 °C[-40 – 194 °F]

Packaging Features

Packaging Method	Box
Packaging Quantity	500

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量超出标准 Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	



Current ECHA Candidate List: JUNE 2025
(250)
Candidate List Declared Against: JAN 2025
(247)
SVHC > Threshold:
Pb (3.5% in Component Part)

Article Safe Usage Statements:
Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # CAT-R131-D743

Double Sided QLPIN Bulkhead


Also in the Series | Rail D-Sub Backshells




Connector Contacts(5)



Connector Hardware(19)



D-Shaped Connectors(10)



D-Sub Backshells & Clamps(55)




Panel Mount D-Sub Connectors(10)

Customers Also Bought




TE Part #GA2K7MCD1
MCD PROBE, 2K OHMS, +/- 0.2C @ 25C




TE Part #1-111446-4
10 UNIV I/O, NO EARS, LEAD FREE




TE Part #1-1437719-2
T01-0540-P05-MALE PLUG CONNECTOR-CRIMP



TE Part #5-1437720-4
T01-CRIMP-P03



TE Part #5-1437720-5
T01-CRIMP-P05=TRIAD



TE Part #5-1437720-7
T01-CRIMP-S05=TRIAD



TE Part #1658621-1
10 NOVO MIL/CTR 15DP, LEAD FREE



TE Part #1-2308321-1
FULL METAL HOODS SIZE 2, (1)



TE Part #1-2308330-1
FULL METAL HOODS SIZE 4 (1)



TE Part #6-1437514-0
8134-HC-12P3=HOLTITE CONTACT 3

Documents

Product Drawings

QL-SET FOR VAR. E LATCH PIN WITH GUIDE 4

English

Datasheets & Catalog Pages

Rail D-Sub Backshells Flyer

English