QPD T 3PE1,5 2X4-9 BK - T distributor

1414707

https://www.phoenixcontact.com/us/products/1414707

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



T distributor, product family: QPD, connection method: IDC connection, number of positions: 3+PE, 0.5 mm^2 ... 1.5 mm^2, 690 V, 17.5 A, PA, black, With two QUICKON nuts, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

Your advantages

- Innovative and time saving - QUICKON fast connection for time saving of up to 80 % for on-site connection
- Robust throughout: housing with IP68/IP69K and IK07 protection for a wide range of applications
- Safer connection with mechanical coding to protect against mismatching, and touch-proof protection in accordance with DIN EN 0105
- Flexible and compact - by connecting connections internally, H and T-distributors can be used to branch master cables or they can be used as star distributors

Commercial data

Item number	1414707
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF50
Product key	BF6DBA
Catalog page	Page 473 (C-2-2019)
GTIN	4055626032016
Weight per piece (including packing)	117.6 g
Weight per piece (excluding packing)	117.6 g
Customs tariff number	85366990
Country of origin	PL

Technical data

Product properties

Product type	Power distributor
Product family	QPD
Type	T distributor
Number of positions	4
Connection profile	3+PE
Position marking	1, 2, 3, PE
Number of connections	2
No. of cable outlets	3
Coding	Coding profile

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Connection data


Connection technology

Connection method	IDC connection
Frequency of connections between conductors of the same cross section	max. 10

Conductor connection

Conductor cross section flexibel	0.5 mm² ... 1.5 mm²
Conductor cross section solid	0.5 mm² ... 1.5 mm²
Connection cross section AWG	20 ... 16
Tightening torque Union nut	8 Nm
Tightening torque Locking nut	5 Nm

Dimensions

Dimensional drawing	
Width	71.1 mm
Height	26 mm
Length	147.8 mm

Electrical properties

Rated surge voltage (II/2)	8 kV
Rated surge voltage (III/2)	8 kV
Rated surge voltage (III/3)	6 kV
Rated current	17.5 A

Contact resistance	< 3 mΩ
rated voltage (II/2)	1000 V
rated voltage (III/2)	1000 V
Rated voltage (III/3)	690 V
Nominal voltage U_N	690 V AC
	690 V DC
Nominal current I_N	17.5 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	max. 50 (QUICKON connections max. 10)

Material specifications

Color	black (RAL 9005)
Material Housing	PA
Material Contact	Cu
Material Contact surface	Silver-plated
Flammability rating according to UL 94	V0
Material wire insulation	PVC /PE / rubber / TPE

Cable/line

Structure of individual litz in acc. with VDE 0295 / smallest wire diameter	VDE 0295 class 1 to 6/min. 0.15 mm
External cable diameter ()	5 mm ... 7 mm
	7 mm ... 9.5 mm
Wire diameter including insulation	1.6 mm ... 3 mm
Position marking	1, 2, 3, PE
Material wire insulation	PVC /PE / rubber / TPE


Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP68 (2 m / 24 h)
	IP69K
Ambient temperature (operation)	-40 °C ... 100 °C
Temperature when conductor connected	-5 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 100 °C


Drawings

Diagram




Derating diagram

Circuit diagram



Dimensional drawing



Dimensional drawing

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1414707

IECEE CB Scheme
Approval ID: DE1-65875

EAC
Approval ID: RU C-DE.BL08.B.00511

DNV GL
Approval ID: TAE00003J5

VDE Zeichengenehmigung
Approval ID: 40029149

UL Listed
Approval ID: E468743

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	600 V	8 A	-	- 16

cUL Listed
Approval ID: E468743

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	600 V	8 A	- 16	-

cULus Listed

Classifications

ECLASS

ECLASS-11.0	27440603
ECLASS-12.0	27440603
ECLASS-13.0	27440603

ETIM

ETIM 9.0	EC002567

UNSPSC

UNSPSC 21.0	39121400

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Mandatory accessories

QPD P 3PE1,5 4-9 BK - Connector

1414703

https://www.phoenixcontact.com/us/products/1414703



Connector, product family: QPD, connection method: IDC connection, number of positions: 3+PE, 0.5 mm^2 ... 1.5 mm^2, 690 V, 17.5 A, PA, black, with QUICKON nut, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

QPD N 3PE1,5 4-9 BK - Nut

1415097

https://www.phoenixcontact.com/us/products/1415097



Nut, product family: QPD, connection method: IDC connection, number of positions: 3+PE, 0.5 mm^2 ... 1.5 mm^2, 690 V, 17.5 A, PA, black, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

Accessories

CP-QPD 3/4X1,5 - Coding profile

1414729

https://www.phoenixcontact.com/us/products/1414729




Coding profile red, for pushing into the QUICKON dome and connector, can be positioned in 90° steps.

GPE 13X 9 WH - Engraving material

0806932

https://www.phoenixcontact.com/us/products/0806932



Engraving material, Sheet, white, unlabeled, can be labeled with: PLOTMARK, ENGRAVING UNIT, CMS-P1-PLOTTER, P1 ENGRAVING UNIT, mounting type: adhesive, lettering field size: 13 x 9 mm, Number of individual labels: 120

EMLP (13X9)R - Label

0819453

https://www.phoenixcontact.com/us/products/0819453



Label, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, lettering field size: 13 x 9 mm, Number of individual labels: 500

QPD QSK BK 3/4X1,5 FS - Protective cap

1414722

https://www.phoenixcontact.com/us/products/1414722

Protective cap, plastic, for QUICKON connection, black, with retaining cord, IP68



QPD QSK 3/4X1,5 - Protective cap

1414723

https://www.phoenixcontact.com/us/products/1414723



Protective cap plastic, for QPD-QUICKON connection 3(4) x 1.5 mm^2, IP50

SEALING PLUG 7X16 RD - Closing cap

1400255

https://www.phoenixcontact.com/us/products/1400255



Closing cap, color: red

QPD W 3PE1,5 4-9 M20 0,5 BK - Panel feed-through

1414675

https://www.phoenixcontact.com/us/products/1414675



Panel feed-through, product family: QPD, connection method: Single wires/ IDC connection, number of positions: 3+PE, M20, Pin, 0.5 mm^2 ... 1.5 mm^2, 690 V, 17.5 A, PA, black, with QUICKON nut, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm, 1.5 mm^2, cable length: 0.5 m

QPD W 3PE1,5 4-9 M20 1,0 BK - Panel feed-through

1414676

https://www.phoenixcontact.com/us/products/1414676



Panel feed-through, product family: QPD, connection method: Single wires/ IDC connection, number of positions: 3+PE, M20, Pin, 0.5 mm^2 ... 1.5 mm^2, 690 V, 17.5 A, PA, black, with QUICKON nut, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm, 1.5 mm^2, cable length: 1 m

QPD T 3PE1,5 2X4-9 BK - T distributor

1414707

https://www.phoenixcontact.com/us/products/1414707

QPD W 3PE1,5 4-9 M20 FC BK - Panel feed-through

1414677

https://www.phoenixcontact.com/us/products/1414677



Panel feed-through, product family: QPD, connection method: Spade connection (For slip-on sleeves according to DIN 46247-2)/ IDC connection, number of positions: 3+PE, M20, Pin, 0.5 mm^2 ... 1.5 mm^2, 690 V, 15 A, PA, black, with QUICKON nut, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm, 1.5 mm^2

QPD C 3PE1,5 1X4-9 BK - Conductor connectors

1414694

https://www.phoenixcontact.com/us/products/1414694



Conductor connectors, product family: QPD, connection method: IDC connection, number of positions: 3+PE, 0.5 mm^2 ... 1.5 mm^2, 690 V, 17.5 A, PA, black, with one QUICKON nut, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

QPD T 3PE1,5 2X4-9 BK - T distributor

1414707

https://www.phoenixcontact.com/us/products/1414707

QPD C 3PE1,5 2X4-9 BK - Conductor connectors

1414696

https://www.phoenixcontact.com/us/products/1414696



Conductor connectors, product family: QPD, connection method: IDC connection, number of positions: 3+PE, 0.5 mm^2 ... 1.5 mm^2, 690 V, 17.5 A, PA, black, With two QUICKON nuts, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

QPD T 3PE1,5 3X4-9 BK - T distributor

1414708

https://www.phoenixcontact.com/us/products/1414708



T distributor, product family: QPD, connection method: IDC connection, number of positions: 3+PE, 0.5 mm^2 ... 1.5 mm^2, 690 V, 17.5 A, PA, black, With three QUICKON nuts, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm

QPD T 3PE1,5 2X4-9 BK - T distributor

1414707

https://www.phoenixcontact.com/us/products/1414707

QPD H 3PE1,5 4X4-9 BK - H distributor

1414715

https://www.phoenixcontact.com/us/products/1414715



H distributor, product family: QPD, connection method: IDC connection, number of positions: 3+PE, 0.5 mm^2 ... 1.5 mm^2, 690 V, 17.5 A, PA, black, with four QUICKON nuts, external cable diameter: 5 mm ... 7 mm and 7 mm ... 9.5 mm, with a sealing bolt

QSS 22 - Socket wrench

1670206

https://www.phoenixcontact.com/us/products/1670206



Allen wrench, for loosening and fastening the QUICKON union nut, WAF 22 mm

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com