



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Fuse**

Modular Terminal Block Product Type: **Screw Clamp Terminal Block**

Primary Product Color: **Gray & Dark Gray**

Product Spacing: **8 mm [ .315 in ]**

Number of Positions: **2**

Features

Product Type Features

|                                     |                            |
|-------------------------------------|----------------------------|
| Modular Terminal Block Product Type | Screw Clamp Terminal Block |
|-------------------------------------|----------------------------|

Configuration Features

|                     |       |
|---------------------|-------|
| Number of Levels    | 1     |
| Gauge Type          | A3-B3 |
| Number of Circuits  | 1     |
| Block Function      | Fuse  |
| Number of Positions | 2     |

Electrical Characteristics

|                                                          |        |
|----------------------------------------------------------|--------|
| Operating Voltage Rating (UL & CSA) (Max) - Main Circuit | 300 V  |
| Impulse Withstanding Voltage Rating (IEC)                | 8000 V |
| Current Rating (IEC)                                     | 6.3 A  |
| Current Rating (UL)                                      | 10 A   |
| Current Rating (CSA)                                     | 6.3 A  |
| Dielectric Withstanding Voltage (Max)                    | 2200 V |



|                      |         |
|----------------------|---------|
| Voltage Rating (IEC) | 630 V   |
| Voltage Rating (CSA) | 300 V   |
| Operating Voltage    | 300 VAC |

Body Features

|                       |                  |
|-----------------------|------------------|
| Product Weight        | 13.3 g[.524 oz]  |
| Primary Product Color | Gray & Dark Gray |

Termination Features

|                                    |                |
|------------------------------------|----------------|
| Termination Method to Wire & Cable | Screw Terminal |
|------------------------------------|----------------|

Mechanical Attachment

|                         |                   |
|-------------------------|-------------------|
| DIN Rail Mounting Type  | TH35-15, TH35-7.5 |
| Connector Mounting Type | DIN Rail          |

Housing Features

|                  |           |
|------------------|-----------|
| Housing Material | Polyamide |
|------------------|-----------|

Dimensions

|                                                                     |                         |
|---------------------------------------------------------------------|-------------------------|
| Product Depth                                                       | 45.6 mm[1.795 in]       |
| Tool Size                                                           | 3.5 mm[.138 in]         |
| Wire Stripping Length                                               | 11 mm[.433 in]          |
| Main Circuit Capacity - 2 Rigid Stranded Conductors per Screw Clamp | 24 – 14 AWG             |
| Main Circuit Capacity - Twin Ferrule per Screw Clamp                | 24 – 14 AWG             |
| Main Circuit Capacity - 2 Flexible Conductors per Screw Clamp       | 24 – 14 AWG             |
| Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp  | 24 – 10 AWG             |
| Main Circuit Capacity - 1 Non-Insulated Ferrule per Screw Clamp     | .22 – 4 mm <sup>2</sup> |
| Main Circuit Capacity - 1 Insulated Ferrule per Screw Clamp         | .22 – 4 mm <sup>2</sup> |
| Main Circuit Capacity - 1 Flexible Conductor per Screw Clamp        | 24 – 10 AWG             |
| Product Length                                                      | 45.6 mm[1.8 in]         |
| Product Height                                                      | 59.7 mm[2.35 in]        |
| Product Spacing                                                     | 8 mm[.315 in]           |
| Wire Size                                                           | 10 AWG                  |

Usage Conditions

|                                |                            |
|--------------------------------|----------------------------|
| Installation Temperature Range | -5 – 40 °C[23 – 104 °F]    |
| Operating Temperature Range    | -55 – 110 °C[-67 – 230 °F] |



Operation/Application

|                     |                |
|---------------------|----------------|
| Circuit Application | Power & Signal |
|---------------------|----------------|

Industry Standards

|                        |          |
|------------------------|----------|
| IP Rating              | IP20     |
| UL Flammability Rating | UL 94V-0 |

Product Compliance

For compliance documentation, visit the product page on TE.com>





|                                               |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                       |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016 | 有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold                                                                         |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2025 (250)<br>Candidate List Declared Against: JUNE 2025 (250)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                                |
| Solder Process Capability                     | Not reviewed for solder process capability                                                                                      |

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



|                                                                                                                                 |                                                                                                                                   |                                                                                                                                    |                                                                                                                                  |
|---------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
|  <p>TE Part # 1SNA008288R1500<br/>FU520</p>    |  <p>TE Part # 1SNA008292R0100<br/>FU520</p>     |  <p>TE Part # 1SNA167546R2200<br/>FU525</p>     |  <p>TE Part # 1SNA168673R1200<br/>TGA8</p>    |
|  <p>TE Part # 1SNA174300R1700<br/>PR3.Z2</p>  |  <p>TE Part # 1SNA167547R2300<br/>FU525</p>    |  <p>TE Part # 1SNA167549R0500<br/>FU525</p>    |  <p>TE Part # 1SNA008289R1600<br/>FU520</p>  |
|  <p>TE Part # 1SNA168674R1300<br/>TGA8</p>   |  <p>TE Part # 1SNK160000R0000<br/>MC812</p>   |  <p>TE Part # 1SNK900613R0000<br/>PROCAP8</p> |  <p>TE Part # 1SNA179371R1600<br/>CN5</p>   |
|  <p>TE Part # 1SNK900001R0000<br/>BAM4</p>   |  <p>TE Part # 1SNA173523R1100<br/>PC81-10</p> |  <p>TE Part # 1SNA168500R1200<br/>PR4</p>     |  <p>TE Part # 1SNA008291R0000<br/>FU520</p> |
|  <p>TE Part # 1SNK508960R0000<br/>ES4-SF</p> |  <p>TE Part # 1SNK900611R0000<br/>UMH</p>     |  <p>TE Part # 1SNK900002R0000<br/>BAZ1</p>    |  <p>TE Part # 1SNA168672R1100<br/>TGA8</p>  |


Also in the Series | ENTRELEC SNK



Modular Terminal Blocks(319)



Terminal Block & Strip Conducting Accessories(67)



Terminal Block & Strip Insulating Accessories(31)

Customers Also Bought



TE Part #1SNK922302R0000  
JB22-2



TE Part #1SNK510020R0000  
ZS16-BL




TE Part #1SNK900401R0000  
PG5




TE Part #1SNK510150R0000  
ZS16-PE




TE Part #1SNK508425R0000  
ZS4-D2-SF1




TE Part #1SNA400813R0000  
MA2.5/5.D2-2CPE



TE Part #1SSA265202R1100  
L26520211000



TE Part #1SNA400817R0000  
MA2.5/5-2CPE



TE Part #1SNA400825R0000  
FEDCP



TE Part #1SNA168410R0700  
RTM7

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_1SNK508410R0000\_A.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_1SNK508410R0000\_A.3d\_igs.zip

1SNK508410R0000

Screw Clamp Terminal Block, Fuse, Gray & Dark Gray, 8 mm [.315 in] Spacing, 2 Position, Screw Terminal, Power & Signal, DIN Rail, ENTRELEC SNK



English

Customer View Model

ENG\_CVM\_CVM\_1SNK508410R0000\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ZS4-SF1

English

ENTRELEC Terminal Block - Master Catalog

ENTRELEC Terminal Block - Master Catalog

English

SNK SERIES TERMINAL BLOCKS

English

ENTRELEC Terminal Blocks Catalogue (RUS)

Essential Entrelec Terminal Blocks

French

Essential Entrelec Terminal Blocks

English

Essential Entrelec Terminal Blocks

Japanese

Agency Approvals

CE Declaration of Conformity

English