Specifications

Eaton GSGB85

Fuse-link, high speed, 85 A, AC 660 V, DC 400 V, BS88, 36 x 95 mm, aR, BS, Ultra fast

General specifications	
PRODUCT NAME	Eaton Bussmann series high speed british standard fuse
CATALOG NUMBER	GSGB85
UPC	051712521055
EAN	5027590502825
PRODUCT LENGTH/DEPTH	19 mm
PRODUCT HEIGHT	35.7 mm
PRODUCT WIDTH	95 mm
PRODUCT WEIGHT	76.9 g
COMPLIANCES	CE
GLOBAL CATALOG	GSGB85

Powering Business Worldwide

Product specifications

AMPERAGE RATING	85 A
BREAKING CAPACITY	100 kA
FUSE INDICATOR	None
INSULATED METAL GRIPPING LUGS (IMGL)	No
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
VOLTAGE TYPE	AC/DC
RATED SWITCHING CAPACITY	100 kA
RATED VOLTAGE AC	660 V
RATED VOLTAGE DC	400 V
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	72 mm
MOUNTING DIMENSION	M8
CURRENT TYPE	AC/DC
CLASS	Class aR
WATT LOSSES	20 W
FUSE SHAPE	Offset dual barrel bolted tags
COLOR	None
CONSTRUCTION SIZE	Other
VOLTAGE RATING	660 V
TYPE	Fuse
APPLICATION	Semiconductor, DC Common bus, DC drives, power converters/rectifiers
FUSE TYPE	GSG
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other

Resources

BROCHURES	eaton-bussmann-series-bs88-high-speed-fuses-product-aid-pa135003en-us.pdf
MCAD MODEL	eaton-hs-bs88-body-fuses-mcad-3d-models-gsgb-75-160a.stp

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.