



Connectors > Contacts > Connector Contacts



Contact Type: **Socket**
Contact Mating Area Plating Material: **Gold (Au)**
Wire Contact Termination Area Plating Material: **Tin**
Contact Size: **Size 16**
Wire Size: **24 – 20 AWG**

Features

Contact Features

Contact Type	Socket
Contact Mating Area Plating Material	Gold (Au)
Wire Contact Termination Area Plating Material	Tin
Contact Size	Size 16
Contact Base Material	Brass
Contact Current Rating (Max)	13 A
Mating Pin Diameter	1.57 mm[.062 in]
Contact Mating Area Plating Material Thickness	.76 µm[30 µin]
Wire Contact Termination Area Plating Thickness	1.27 µm[50 µin]
Wire Contact Termination Area Plating Material Finish	Bright
Contact Orientation	Straight
Contact Underplating Material	Nickel
Contact Underplating Material Thickness	.76 µm[30 µin]

Termination Features



Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	With
-------------------------	------

Dimensions

Wire Size	.2 – .6 mm²
Compatible Insulation Diameter Range	2.03 – 2.54 mm[.08 – .1 in]

Usage Conditions

Operating Temperature Range	-55 – 90 °C[-67 – 194 °F]
-----------------------------	---------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Packaging Features

Packaging Quantity	100
Packaging Method	Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 305183 EXTRACT TOOL TYPE 2 20-16	 TE Part # 200893-2 INSERTION TOOL CONT	 TE Part # 91523-1 CCII TYPE III+ PIN SKT 24-16 ASSY	 TE Part # 539972-1 EXTRACTION TOOL
 TE Part # 58495-2 PROCRIPTER DIE ASSY MULTIMATE	 TE Part # 58495-1 PRO CRIMPER ASSY MULTIMATE		

Also in the Series | AMP Type III+

 Connector Contacts(260)	 Insertion & Extraction Tools(4)	 Power Contacts(260)
--	---	--

Also in the Series | Circular Plastic Connectors Series 1

 Circular Power Connectors(211)	 Connector Contacts(260)	 Power Contacts(260)
---	---	--

Customers Also Bought





TE Part #CAT-D485-CH8172
DEUTSCH DTM Housings



TE Part #WM-8S
WEDGE LOCK, 8P, PLG, ORG, DTM



TE Part #FG9026
OMNI,FG,902-928MHZ 915MHz,6dBd



TE Part #1060-20-0222
PIN, SF, SIZE 20, 16-22, NI/NI



TE Part #66400-4
III+ PIN,24-20,30AU/FL,LP



TE Part #1376109-1
025 TAB CONT



TE Part #1393128-5
PRD-5AY0-120=PRD



TE Part #1609112-1
10CBE1=F7890 M0



TE Part #1676625-5
HSA25 R05 5%

Documents

Product Drawings

III+ SKT,24-20,30AU/FL,SMPACK

English

CAD Files

Customer View Model

ENG_CVM_CVM_66399-9_H.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_66399-9_H.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_66399-9_H.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Instruction Sheets

66399-9

Gold (Au), Socket Contact, 24 – 20 AWG, .2 – .6 mm² Wire, Size 16, Crimp, Brass, Power & Signal, -55 – 90 °C [-67 – 194 °F], AMP Type III+



[Instruction Sheet \(U.S.\)](#)

Japanese

[Instruction Sheet \(U.S.\)](#)

English