Data Sheet

HUBER+SUHNER

RF TERMINATION
Type 6506.26.0002

Description

Standard Termination, Medium Power



Product Configuration

Connector	TNC plug (male)
Interface standards	IEC 60169-17_MIL-STD-348A/313_CECC 22200

Technical Data

Electrical Data

Nominal Impedance	50 Ω		
Frequency range	0 to 6 GHz		
Frequency sub range	DC to 2 GHz	2 to 4 GHz	4 to 6 GHz
VSWR max.	1.1	1.2	1.25
Power rating	6 Watt average power up to 40 ˚C ambient temperature, linearly derated to 0 Watt at 130 ˚C ambient temperature. 1000 Watt peak power , 5 µs pulse, 0.05 % duty cycle		

Mechanical Data

Weight	0.062 kg

Environmental Data

Operating temperature	-40 °C to 130 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	not compliant

Material Data

Piece Part	Material	Surface Plating
Centre contact	Bronze	Gold Plating (without Nickel underplating)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Aluminium	
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00005433

Ordering Information

Single Packaging Packaging	6506.26.0002

Additional Information

Important note	WARNING Beryllia Ceramic Inside! DO NOT sand, scrap or tamper with. Dispose in accordance with all relevant regulations.

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Document: DOC-0000178531 Y / PDO F / date of publication: 28.03.2020 02:18:18 / uncontrolled copy