10ft (3m) DisplayPort 1.2 Cable - 4K x 2K Ultra HD VESA Certified DisplayPort Cable - DP to DP Cable for Monitor - DP Video/Display Cord - Latching DP Connectors

**Product ID:** DISPLPORT10L



This DisplayPort cable provides a secure connection between your DisplayPort equipped devices and is capable of providing higher performance than either HDMI or dual-link DVI.

The DP cable supports high resolutions of up to 4K x 2K (4096 x 2160, 60Hz) with a maximum HBR2 bandwidth of 21.6Gbps, as well as optional audio support. The cable also supports Multi-Stream Transport (MST) for daisy chaining multiple monitors.

The 10-foot cable is DisplayPort (VESA) certified to support DP 1.2 specifications and ensure a high-quality, reliable connection for all of your DisplayPort devices.

The DISPLPORT10L is backed by a StarTech.com lifetime warranty for guaranteed reliability and ensures that digitally protected content is displayed properly, with both HDCP and DPCP capability.

## Certifications, Reports and Compatibility

## Applications

• Connecting a DisplayPort display to a PC or other DisplayPort source

## Features

• HIGH PERFORMANCE CABLE: This 10ft (3m) VESA Certified DisplayPort v1.2 cable supports 4K x 2K (3840x2400p 60Hz), 21.6 Gbps bandwidth, HBR2, 8Ch Audio, Multi-Stream Transport (MST), GTC for precise audio channel timing & 3D Stereo (2560x1600p 120Hz)

• RELIABLE DESIGN: Durable ABS connectors with flexible PVC strain relief & jacket prevents fraying/damage due to bending or rough usage; Metal connector sub-structure provides EMI shielding; Latching DP connectors prevent accidental disconnection

• QUALITY CONSTRUCTION: 28AWG wire with gold-plated connectors for improved signal integrity and reliability; Superior EMI shielding with Al-Mylar foil and copper braid provides higher quality video and audio; Backwards compatible with DP 1.1

• APPLICATIONS: Ideal for home/offices/boardrooms/conference rooms/classrooms; works with your professional workstations with FirePro S9000/7000, W8100/7100/5100 or R5000 graphic cards; Use with 1080p/UHD/4K monitors, projector or large display

• SPECS: 10 ft (3 m)  Black  DisplayPort v1.2  DP Latching Male to Male  28 AWG  PVC cable jacket, ABS connector shell  Shield: Al-Mylar foil with Braid  Protocols: HBR 2, MST, GTC  Lifetime Warranty

| | | |
|---|---|---|
| **Hardware** | | |
| | Warranty | Lifetime |
| | Number of Conductors | 19 |
| | Connector Plating | Nickel |
| | Cable Jacket Material | PVC - Polyvinyl Chloride |
| | Cable Shield Material | Aluminum-Mylar Foil with Braid |
| | Fire Rating | CMG Rated (General Purpose) |
| **Performance** | | |
| | General Specifications | Insertion Rating: 5000 |
| **Connector(s)** | | |
| | Connector A | 1 - DisplayPort (20 pin) |
| | Connector B | 1 - DisplayPort (20 pin) |
| **Environmental** | | |
| | Operating Temperature | 0 to 50 C |
| | Storage Temperature | -20 to 70 C |
| | Humidity | 0 to 95% |
| **Physical** | | |

## Characteristics

| | |
|---|---|
| Color | Black |
| Connector Style | Latching |
| Wire Gauge | 28 AWG |
| Cable Length | 10.0 ft [3.0 m] |
| Cable OD | 0.3 in [7.3 mm] |
| Product Length | 10.0 ft [3.0 m] |
| Product Width | 0.8 in [2.0 cm] |
| Product Height | 0.4 in [1.1 cm] |
| Weight of Product | 7.4 oz [210.0 g] |

## Packaging Information

| | |
|---|---|
| Package Quantity | 1 |
| Package Length | 8.7 in [22.0 cm] |
| Package Width | 7.9 in [20.0 cm] |
| Package Height | 1.3 in [34.0 mm] |
| Shipping (Package) Weight | 7.6 oz [215.0 g] |

## What's in the Box

| | |
|---|---|
| Included in Package | 1 - 10 ft DisplayPort Cable 1.2 with Latches - M/M |

***Product appearance and specifications are subject to change without notice.***