



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: **Receptacle**
Connector & Housing Type: **Receptacle**
Number of Positions: **1**
Terminal Orientation: **Straight**
UL Flammability Rating: **UL 94V-0**

Features

Product Type Features

Sealable	No
Connector & Housing Type	Receptacle

Configuration Features

Number of Positions	1
---------------------	---

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	With

Mechanical Attachment

Mating Alignment Type	Polarization
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)



Housing Features

Housing Material	Nylon
------------------	-------

Dimensions

Product Length	27.8 mm[1.09 in]
----------------	------------------

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	1000
--------------------	------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>




Compatible Parts

 TE Part # 170329-1 250 PL MKII REC. 15-10AWG PTBR	 TE Part # 170334-1 250 PL MIII,REC.,18-14 AWG,PTBR	 TE Part # 170335-1 PL 250 RECEPTACLE 15-10 AWG PTPBR	 TE Part # 170333-1 PL 250 RECEPTACLE 22-18 AWG PTPBR
 TE Part # 724659-2 EXT TOOL FOR POSITIVE .250	 TE Part # 170328-1 250 PL MKII REC. 18-14AWG PTBR	 TE Part # 170327-1 250 PL MKII REC. 22-18AWG PTBR	 TE Part # 3-172076-1 POSITIVE LOCK 250 HOUSING RECEPTACLE


Also in the Series | Mark II

 Automotive Connector Locks & Position Assurance(1)	 Automotive Seals & Cavity Plugs(1)	 Automotive Signal & Power Connector Housings(6)	 Automotive Terminals(1)
 Quick Disconnects(171)			

Also in the Series | Positive Lock 250



Automotive Terminals(1)



Crimp Terminal Housings(176)



Insertion & Extraction Tools(3)



Insulation Boots & Sleeves(5)




Quick Disconnects(171)


Customers Also Bought



TE Part #176271-4
AMP UNIVERSAL POWER PLUG 2P



TE Part #176282-4
AMP UNIVERSAL POWER CAP 2P




TE Part #353249-2
110 PL EX REC. 26-22AWG PTPHBZ



TE Part #1747066-5
GRACE INERTIA CONN 2.5 PLUG HSG 5P NATUR



TE Part #1871867-1
GRACE INERTIA 6.2mm PITCH PLUG 3POS



TE Part #1903684-1
GIC 6.2MM PITCH 1POS CAP HSG NATURAL




TE Part #2381807-6
TRI-SLOT MAG-MATE, SLIM LINE



TE Part #85092-1
PL 187 HOUSING 2P REC NYLON66 NATURAL



TE Part #1-85092-1
POSITIVE LOCK 187 HOUSING RECEPTACLE



TE Part #3-1971883-1
4P HOUSING(HIGH VOLTAGE) MULTI 6P CONN

Documents



CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-172076-1_W.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-172076-1_W.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-172076-1_W.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Positive Lock Receptacles

English

Product Specifications

Application Specification

English

Application Specification

English

Application Specification

Japanese

CRIMP OF MATE-N-LOK PIN CONTACT

Japanese

CRIMP OF MATE-N-LOK PIN CONTACT

English

Application Specification

English

Agency Approvals

UL Report

English