




Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Feed-Through**
Modular Terminal Block Product Type: **Screw Clamp Terminal Block**
Primary Product Color: **Orange**
Product Spacing: **6 mm [.236 in]**
Number of Positions: **2**

Features

Product Type Features

Modular Terminal Block Product Type	Screw Clamp Terminal Block
-------------------------------------	----------------------------

Configuration Features

Number of Levels	1
Gauge Type	A4-B3
Number of Circuits	1
Block Function	Feed-Through
Number of Positions	2

Electrical Characteristics

Power Loss	1.3 W
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	600 V
Impulse Withstanding Voltage Rating (IEC)	8000 V
Current Rating (IEC)	41 A
Current Rating (UL)	30 A
Current Rating (CSA)	30 A



Dielectric Withstanding Voltage (Max)	2200 V
Voltage Rating (IEC)	1000 V
Voltage Rating (CSA)	600 V
Short-Time Withstanding Current Rating @ 1s	720 A

Body Features

Product Weight	10.6 g[.417 oz]
Primary Product Color	Orange

Mechanical Attachment

DIN Rail Mounting Type	TH35-15, TH35-7.5
Connector Mounting Type	DIN Rail

Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Product Depth	47.3 mm
Tool Size	4 mm[.157 in]
Wire Stripping Length	10.5 mm[.413 in]
Main Circuit Capacity - 2 Rigid Stranded Conductors per Screw Clamp	24 – 14 AWG
Main Circuit Capacity - Twin Ferrule per Screw Clamp	24 – 14 AWG
Main Circuit Capacity - 2 Flexible Conductors per Screw Clamp	24 – 14 AWG
Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	24 – 10 AWG
Main Circuit Capacity - 1 Non-Insulated Ferrule per Screw Clamp	.22 – 4 mm ²
Main Circuit Capacity - 1 Insulated Ferrule per Screw Clamp	.22 – 4 mm ²
Main Circuit Capacity - 1 Flexible Conductor per Screw Clamp	24 – 10 AWG
Product Length	47.3 mm[1.86 in]
Product Height	53 mm
Product Spacing	6 mm[.236 in]

Usage Conditions

Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]

Industry Standards

IP Rating	IP20
-----------	------



UL Flammability Rating

UL 94V-0

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 1SNA164800R0300
PR3.G2

TE Part # 1SNA168700R2200
PR5

TE Part # 1SNK900600R0000
SHBS

TE Part # 1SNK900205R0000
TP4



TE Part # 1SNK900624R0000
[KCO](#)



TE Part # 1SNK906302R0000
[JB6-2](#)



TE Part # 1SNK906304R0000
[JB6-4](#)




TE Part # 1SNK900619R0000
[PL6](#)



TE Part # 1SNK900603R0000
[JB85-3](#)




TE Part # 1SNK900203R0000
[TP2](#)



TE Part # 1SNA174300R1700
[PR3.Z2](#)



TE Part # 1SNK159999R0000
[MC612PA](#)



TE Part # 1SNK150004R0000
[MC612-YL](#)



TE Part # 1SNK900105R0000
[ES-TC6](#)



TE Part # 1SNK505910R0000
[ES4](#)



TE Part # 1SNK906305R0000
[JB6-5](#)



TE Part # 1SNK906310R0000
[JB6-10](#)



TE Part # 1SNK900201R0000
[TC5-R1](#)




TE Part # 1SNK900611R0000
[UMH](#)



TE Part # 1SNK900002R0000
[BAZ1](#)

Also in the Series | **ENTRELEC SNK**



[Modular Terminal Blocks\(319\)](#)



[Terminal Block & Strip Conducting Accessories\(67\)](#)



[Terminal Block & Strip Insulating Accessories\(31\)](#)

Customers Also Bought




TE Part #1SNK140121R0000
MC512PA 111->120 (x10) Horizontal



TE Part #1SNK140061R0000
MC512PA 51->60 (x10) Horizontal



TE Part #1SNA400239R1500
M6/8



TE Part #1SNK508419R0000
ZS4-S-R3-T2



TE Part #1SNA125118R1300
M6/8.N



TE Part #1SNK140111R0000
MC512PA 101->110 (x10) Horizontal



TE Part #1SNK508066R0000
ZS10-BK



TE Part #1SNK140041R0000
MC512PA 31->40 (x10) Horizontal



TE Part #1SNK140071R0000
MC512PA 61->70 (x10) Horizontal



TE Part #1SNK140101R0000
MC512PA 91->100 (x10) Horizontal

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SNK506030R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SNK506030R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNK506030R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ZS6-OR

English

ENTRELEC Terminal Block - Master Catalog

1SNK506030R0000

Screw Clamp Terminal Block, Feed-Through, Orange, 6 mm [.236 in] Spacing, 2
Position, DIN Rail, -55 – 110 °C [-67 – 230 °F], ENTRELEC SNK



[ENTRELEC Terminal Block - Master Catalog](#)

English

[SNK SERIES TERMINAL BLOCKS](#)

English

[ENTRELEC Terminal Blocks Catalogue \(RUS\)](#)

[Agency Approvals](#)

[ZK-ZS_ATEX_1SND225112U1006-C-TE](#)

English