

N-Channel Power MOSFET

FEATURES

- Super-Junction technology
- High performance good FOM
- High ruggedness performance
- High commutation performance
- 100% UIS & Rg tested
- RoHS Compliant
- Halogen-free



APPLICATIONS

- Power Supply
- Lighting

KEY PERFORMANCE PARAMETERS		
PARAMETER	VALUE	UNIT
$V_{DS} @ T_{j,max}$	650	V
$R_{DS(on)} (max)$	390	mΩ
$Q_{g,typ}$	21	nC



TO-252 (DPAK)



Note: MSL 3 (Moisture Sensitivity Level) per J-STD-020

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)				
PARAMETER		SYMBOL	LIMIT	UNIT
Drain-Source Voltage		V_{DS}	600	V
Gate-Source Voltage		V_{GS}	± 20	V
Continuous Drain Current (Note 1)	$T_C = 25^\circ\text{C}$	I_D	11	A
	$T_C = 100^\circ\text{C}$		7	A
Pulsed Drain Current (Note 2)		I_{DM}	33	A
Total Power Dissipation @ $T_C = 25^\circ\text{C}$		P_D	125	W
Single Pulse Avalanche Energy (Note 3)		E_{AS}	300	mJ
Single Pulse Avalanche Current (Note 3)		I_{AS}	3.5	A
Operating Junction and Storage Temperature Range		T_J, T_{STG}	- 55 to +150	$^\circ\text{C}$

THERMAL PERFORMANCE			
PARAMETER	SYMBOL	LIMIT	UNIT
Junction to Case Thermal Resistance	$R_{\theta JC}$	1	$^\circ\text{C/W}$
Junction to Ambient Thermal Resistance	$R_{\theta JA}$	50	$^\circ\text{C/W}$

Note: Device on a PCB FR4 with 1 in² (single layer, 2 oz thickness) copper area for drain connection.

ELECTRICAL SPECIFICATIONS (T _A = 25°C unless otherwise noted)						
PARAMETER	CONDITIONS	SYMBOL	MIN	TYP	MAX	UNIT
Static (Note 4)						
Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 1mA	BV _{DSS}	600	--	--	V
Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 1mA	V _{GS(TH)}	3	4.5	5	V
Gate Body Leakage	V _{GS} = ± 20V, V _{DS} = 0V	I _{GSS}	--	--	±100	nA
Zero Gate Voltage Drain Current	V _{DS} = 600V, V _{GS} = 0V	I _{DSS}	--	--	100	μA
Drain-Source On-State Resistance	V _{GS} = 10V, I _D = 3.8A	R _{DS(on)}	--	350	390	mΩ
Dynamic (Note 5)						
Total Gate Charge	V _{DS} = 300V, I _D = 9A, V _{GS} = 10V	Q _g	--	21	--	nC
Gate-Source Charge		Q _{gs}	--	6	--	
Gate-Drain Charge		Q _{gd}	--	10	--	
Input Capacitance	V _{DS} = 300V, V _{GS} = 0V, f = 1.0MHz	C _{iss}	--	783	--	pF
Output Capacitance		C _{oss}	--	27	--	
Reverse Transfer Capacitance		C _{rss}	--	13	--	
Gate Resistance	f = 1.0MHz	R _g	0.6	2	4	Ω
Switching (Note 6)						
Turn-On Delay Time	V _{DD} = 300V, R _G = 10Ω, I _D = 5.5A, V _{GS} = 10V	t _{d(on)}	--	22	--	ns
Turn-On Rise Time		t _r	--	26	--	
Turn-Off Delay Time		t _{d(off)}	--	41	--	
Turn-Off Fall Time		t _f	--	19	--	
Source-Drain Diode (Note 4)						
Body-Diode Continuous Forward Current		I _S	--	--	11	A
Body-Diode Pulsed Current		I _{SM}	--	--	33	A
Forward Voltage	I _S = 11A, V _{GS} = 0V	V _{SD}	--	--	1.5	V
Reverse Recovery Time	I _S = 11A dI _F /dt = 100A/μs	t _{rr}	--	324	--	ns
Reverse Recovery Charge		Q _{rr}	--	4.8	--	μC

Notes:







- Current limited by package.
- Pulse width limited by the maximum junction temperature.
- $L = 50mH, V_{DD} = 50V, R_G = 25\Omega$, Starting $T_J = 25^\circ\text{C}$
- Pulse test: $PW \leq 300\mu s$, duty cycle $\leq 2\%$.
- For DESIGN AID ONLY, not subject to production testing.
- Switching time is essentially independent of operating temperature.

ORDERING INFORMATION

ORDERING CODE	PACKAGE	PACKING
TSM60NC390CP ROG	TO-252 (DPAK)	2,500pcs / 13" Reel






CHARACTERISTICS CURVES

($T_c = 25^\circ\text{C}$ unless otherwise noted)




CHARACTERISTICS CURVES

($T_C = 25^\circ\text{C}$ unless otherwise noted)



PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

TO-252



MARKING DIAGRAM

60NC390 = Device marking
Y = Year Code
WW = Week Code (01~52)
L = Lot Code (1~9,A~Z)
F = Factory Code

NOTES: UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
3. PACKAGE OUTLINE REFERENCE: JEDEC TO-252, VARIATION AA, ISSUE F.
4. MOLDED PLASTIC BODY DIMENSIONS DO NOT INCLUDE MOLD FLASH, PROTRUSION, OR GATE BURRS.
5. DWG NO. REF: HQ2SD07-TO252AA-013 REV B.

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.