

WSD 2.5/SCAN WTR2.5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image

Similar to illustration



The component plug is used to integrate an electrical component in a disconnect terminal block. After soldering the electronic component, the plug can be integrated into the disconnection area of our disconnect terminal blocks and thus changes the disconnect terminal block into a modular terminal block with integrated electronic component.

General ordering data

Version	Component plug (terminal), Plug-in connection, Plugged, dark beige
Order No.	1058760000
Type	WSD 2.5/SCAN WTR2.5
GTIN (EAN)	4008190028398
Qty.	25 ST

WSD 2.5/SCAN WTR2.5

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Approvals

Approvals



ROHS Conform

UL File Number Search [UL Website](#)

Certificate No. (UR) E60693

Dimensions and weights

Depth	29.58 mm	Depth (inches)	1.1646 inch
Height	38.4 mm	Height (inches)	1.5118 inch
Width	5 mm	Width (inches)	0.1968 inch
Net weight	3.68 g		

Temperatures

Storage temperature	-25 °C...55 °C	Ambient temperature	-5 °C...40 °C
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	120 °C

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

Material data

Material	Wemid	Colour	dark beige
UL 94 flammability rating	V-0		

System specifications

Version	Diode module	End cover plate required	No
Number of levels	1	PE connection	No

Additional technical data

Type of fixing	Plugged	Explosion-tested version	No
Type of mounting	Plugged		

CSA rating data

Certificate No. (CSA)	154685-1152890
-----------------------	----------------

Conductors for clamping (rated connection)

Connection direction	top	Type of connection	Plug-in connection
----------------------	-----	--------------------	--------------------

UL rating data

Certificate No. (UR)	E60693
----------------------	--------

WSD 2.5/SCAN WTR2.5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Technical data****Classifications**


ETIM 6.0	EC002018	ETIM 7.0	EC002018
ETIM 8.0	EC002018	ETIM 9.0	EC002018
ETIM 10.0	EC002018	ECLASS 9.0	27-14-11-49
ECLASS 9.1	27-14-11-49	ECLASS 10.0	27-14-11-49
ECLASS 11.0	27-14-11-49	ECLASS 12.0	27-14-11-49
ECLASS 13.0	27-25-03-05	ECLASS 14.0	27-25-03-05
ECLASS 15.0	27-25-03-05		

WSD 2.5/SCAN WTR2.5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com**Accessories****Marker holder**

The marker holder offer the possibility of additional mounting of standard markers with a pitch of 5 or 5.1 mm. The angled holders can be optionally snapped together and could be mounted in all standard marking channels of the Klippon® Connect modular terminal blocks. Fitting marker types could be found under the respective accessories of the designation marking holder.

General ordering data

Type	BZT 1 WS 10/5	Version
Order No.	1805490000	Accessories, Marker holder
GTIN (EAN)	4032248270231	
Qty.	100 ST	
Type	BZT 1 ZA WS 10/5	Version
Order No.	1805520000	Accessories, Marker holder
GTIN (EAN)	4032248270248	
Qty.	100 ST	