

ATGBICS MA-QSFP-40G-LR4 Cisco Meraki Compatible Transceiver
QSFP+ 40GBase-LR4 (1310nm SMF 10km LC DOM)



Brand : ATGBICS

Product code: MA-QSFP-40G-LR4-C

Product name : MA-QSFP-40G-LR4 Cisco Meraki
Compatible Transceiver QSFP+ 40GBase-LR4 (1310nm SMF
10km LC DOM)

MA-QSFP-40G-LR4 Cisco Meraki Compatible Transceiver QSFP+ 40GBase-LR4 (1310nm SMF 10km LC
DOM)

ATGBICS MA-QSFP-40G-LR4 Cisco Meraki Compatible Transceiver QSFP+ 40GBase-LR4 (1310nm SMF
10km LC DOM):

ATGBICS Cisco Meraki compatible MA-QSFP-40G-LR4 QSFP+ 40GBase-LR4 form factor network transceiver supports a distance of up to 10km over single-mode fibre (SMF) using a wavelength of 1310nm via an LC Duplex connector. This product operates within a commercial temperature range. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Cisco Meraki MA-QSFP-40G-LR4 and we proudly offer a compatibility guarantee and limited lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA (Multi-Source Agreement) and IEEE standards & protocols.

Performance		Power	
SFP transceiver type *	Fiber optic	Input voltage	3.3 V
Maximum data transfer rate *	40000 Mbit/s	Maximum voltage	3.5 V
Interface type *	QSFP+	Power consumption (typical)	3.5 W
Single-mode fiber (SMF) supported	✓	Certificates	
Multi-mode fiber (MMF) supported	✗	Compliance certificates	TÜV mark, UKCA, UL, US FDA, REACH, Federal Communications Commission (FCC), RoHS, CE
Fiber optic connector	LC	Certification	CE, FCC, RoHS, REACH
SFP transceiver standard	LR4	Operational conditions	
Maximum transfer distance	10000 m	Minimum operating temperature	0 °C
Wavelength	1310 nm	Maximum operating temperature	70 °C
Ethernet LAN	✓	Operating temperature (T-T)	0 - 70 °C
Ethernet interface type	40 Gigabit Ethernet	Storage temperature (T-T)	-40 - 85 °C
Fiber ethernet cabling technology	40GBASE	Operating relative humidity (H-H)	0 - 95%
Digital Diagnostics Monitoring (DDM)	✓	Storage relative humidity (H-H)	0 - 95%
Wavelength-division multiplexing (WDM)	✗	Weight & dimensions	
Features		Width	13.5 mm
Product colour	Silver	Depth	72.4 mm
Housing material	Metal	Height	18.4 mm
Plug and Play	✓	Weight	100 g
Hot-Plug support	✓	Packaging content	
Hot-swap	✓	Quantity per pack	1 pc(s)
Easy to install	✓	Packaging data	
Brand compatibility	Meraki	Package type	Box
Logistics data			
		Country of origin	United Kingdom

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.