DT1 DIN RAIL SURGE PROTECTION CLASS I+II 12.5 KA, 4+0 MODE, 120 V UN

CATALOG NUMBER

DT115040R



CERTIFICATIONS

FEATURES

- Compact, yet high surge rated pluggable design, using minimum DIN rail width
- External back-up fuse is not required up to 315 A (IEC only)
- Retaining clip ensures enhanced vibration and shock resistance performance
- Red/Green status indication and change-over contacts standard for remote monitoring

PRODUCT ATTRIBUTES

- Nominal System Voltage (Un): 120 V
- Max Continuous Operating Voltage (Uc): 150 V
- Nominal Discharge Current (In), IEC: 20 kA 8/20 µs
- Max Discharge Current (Imax), IEC: 50 kA 8/20 µs
- Impulse Current (Iimp): 12.5 kA 10/350 µs
- Voltage Protection Level (Up): 1000 V
- Response Time: 25 ns Max
- Back-Up Fuse @ Isccr: 250 A @ 50 kA;315 A @ 25 kA
- Frequency: 50 - 60 Hz
- Short Circuit Current Rating (Isccr): 25 kA
- Protection Modes: L-N;N-PE
- Temporary Over Voltage 120 min (Ut/mode): 229 V Safe Fail

Temporary Over Voltage Withstand 5 s (Ut): 175 V

Voltage Protection Rating (VPR): 500 V

Nominal Discharge Current (In), UL: 20 kA 8/20 µs

Replacement Module: DT1150M

Short Circuit Current Rating (SCCR): 200 kA

Technology: Thermal Disconnect

Connection, Solid: #2 max

Connection, Stranded: #4 max

Torque: 3.32 ft·lbf

Humidity: 5 - 95

Temperature: -31 to 185 °F

Enclosure Material: UL® 94V-0 Thermoplastic

Enclosure Rating: IP 20

Mounting: 35 mm top hat DIN rail

Remote Contact Switching Capacity: 0.5 A @ 12 VDC;0.5 A @ 24 VDC;0.5 A @ 48 VDC;1 A @ 125 VAC;1 A @ 250 VAC

Remote Contacts: Yes

Status Indication: Mechanical flag

Depth: 3.35"

Height: 3.54"


Width: 2.84"

Unit Weight: 1.4 lb

Certification Details: UL® 1449 Edition 5 Type 1CA

Complies With: EN 61643-11 Type 1, Type 2;IEC® 61643-11 Class I, Class II

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500

nVent

Our powerful portfolio of brands:

nVent.com **CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.