1-178128-4 ✔ ACTIVE

Dynamic Series | Dynamic 3000 Series

TE Internal #: 1-178128-4

4 Position, Receptacle, Housing, Crimp, Wire-to-Board, UL 94V-0, 5.08 mm [.2 in] Centerline, 1 Row, Wire & Cable, Power & Signal, Dynamic 3000 Series

View on TE.com >

Connectors > Rectangular Connectors > Standard Rectangular Connectors > Receptacle and Tab Housing: 5.08 mm Pitch, 250-600V







Connector Product Type: **Housing**

Connector & Housing Type: **Receptacle**

Connector System: **Wire-to-Board**

UL Flammability Rating: **UL 94V-0**

Number of Positions: **4**

All Receptacle and Tab Housing: 5.08 mm Pitch, 250-600V (64)

Features

Product Type Features

Connector Product Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	4
Number of Rows	1

Body Features

Primary Product Color	Black

Contact Features

Contact Base Material	Copper Alloy

Contact Type	Receptacle

Termination Features

Termination Method to Wire & Cable	Crimp

Mechanical Attachment

Mating Retention	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Centerline (Pitch)	5.08 mm[.2 in]
Housing Material	Polyester GF

Dimensions

Connector Width	22.8 mm[.89 in]
Connector Height	7.15 mm[.28 in]
Connector Length	34.78 mm[1.36 in]

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

Operation/Application

Circuit Application	Power & Signal

Industry Standards

UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	2000
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC

Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 1-1827691-2
DYNATAP 3200 TAP ASSY 24P



TE Part # 1827691-2
DYNATAP 3200 TAP ASSY 24P(P/M) PdNI



TE Part # 1827691-1
DYNATAP 3200 TAP ASSY 24P(F/H) PdNI



TE Part # 8-178563-2
DYNAMIC 4P TAB W/WRAPPING POST



TE Part # 1-1827691-3
DYNATAP 3200 TAP ASSY 24P BOTTOM-MT TIN



TE Part # 1-2491647-8
DYNAMIC 3200 HDR ASSY 4P H PdNi



TE Part # CAT-D9934-A75F
Header Assembly: Wire-to-Board, 15A, gold or tin plated



TE Part # 1-1827691-1
DYNATAP 3200 TAP ASSY 24P(F/H_Sn)



TE Part # CAT-D9934-A75
Contact: Component To Wire; 15A, 28-14 wire size



TE Part # 1827691-3
DYNATAP 3200 TAP ASSY 24P BOTTOM PdNI




TE Part # 1-2491647-7
DYNAMIC 3200 HDR ASSY 4P H PdNi

Also in the Series | Dynamic 3000 Series




Connector Contacts(94)




Connector Hardware(8)



Insertion & Extraction Tools(2)



PCB Headers & Receptacles(290)




PCB Terminal Blocks(5)



Power Contacts(94)




Rectangular Power Connectors(443)



Wire-to-Board Headers & Receptacles (290)

Customers Also Bought



TE Part #CAT-D9934-A75A

Receptacle and Tab Housing: 3.81 mm pitch, 250V



TE Part #CAT-D9934-A75B

Receptacle and Tab Housing: 5.08 mm Pitch, 250-600V



TE Part #1-1827579-1

DYNAMIC 1500T REC HSG 3P X BLACK



TE Part #1827691-2

DYNATAP 3200 TAP ASSY 24P(P/M) PdNI



TE Part #CAT-D9934-A15B

Receptacle and Tab Housing: 2.5 mm Pitch, 250V

Documents

Product Drawings

DYNAMIC 3200 REC HSG 4P SGL

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-178128-4_Y.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-178128-4_Y.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-178128-4_Y.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Product Specification

English

Agency Approvals

Agency Approval Document

English