5-2834006-3 ✔ ACTIVE


Buchanan WireMate

TE Internal #: 5-2834006-3

Poke-In Connectors, Wire-to-Board, 4 mm Centerline, Printed Circuit Board, Height .176 in [4.48 mm], Surface Mount, 18 - 22 AWG Wire Size

View on TE.com >

Connectors > Lighting Connectors > Poke-In Connectors > Poke-In Connector, BUCHANAN WireMate




Connector System: **Wire-to-Board**

Centerline (Pitch): **4 mm**

Connector & Contact Terminates To: **Printed Circuit Board**

Connector Height: **4.48 mm [.176 in]**

Termination Method to Printed Circuit Board: **Surface Mount**

All Poke-In Connector, BUCHANAN WireMate (51)

Features

Product Type Features

Product Line	Poke-In
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board

Electrical Characteristics

Operating Voltage	400 VAC

Body Features

Primary Product Color	Natural

Contact Features

PCB Contact Termination Area Plating Material Finish	Matte
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin-Lead
Contact Current Rating (Max)	6 A

Termination Features

Termination Method to Printed Circuit Board	Surface Mount

Mechanical Attachment

Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	4 mm

Dimensions

Compatible Insulation Diameter Range	2.1 mm
Connector Height	4.48 mm[.176 in]
Wire Size	18 - 22 AWG

Industry Standards

Compatible With Agency/Standards Products	UL
Compatible With Approved Standards Products	UL 1977, UL E28476
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Method	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 245°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent

chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 2834006-3
RELEASE POKE-IN CONNECTOR_3POLES



TE Part # 2324697-3
PUSH GRIP CONNECTOR 3P




TE Part # CAT-L6267-B2125A
LIGHT-N-LOK Modular Latched Mated Connector

Customers Also Bought



TE Part # 206433-1
CPC Connectors, Series 2



TE Part # 206138-8
CLAMP CBL SHELL SIZE 23



TE Part # 66504-9
SOCKET CONTACT, 20 DF



TE Part # 2834006-3
RELEASE POKE-IN CONNECTOR_3POLES



TE Part # 66506-9
PIN CONTACT, 20 DF




TE Part # 640466-1
05P UMNL PIN HDR ASSY V2 NATL



TE Part # 2-1445085-4
micro mnl hdr assy s/row au lf



TE Part # 1546671-6
6P .437" DR BARRIER,W/WIR CLMP



TE Part # 1986242-4
Power Connector, 15.0mm, Green, 4 posn

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-2834006-3_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5-2834006-3_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-2834006-3_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditionsof use.

Datasheets & Catalog Pages

Modular Releasable Poke-in datasheet

English

BUCHANAN WireMate Connectors Brochure

BUCHANAN WireMate Connectors Brochure

English

Modular Releasable Poke-in datasheet (Chinese)

Product Specifications

Application Specification

English

Agency Approvals

UL

English