# Specification Sheet

Part Number: 156-01292



The 360 degree locking enclosure and cable tie dynamically fit a range of bundle sizes.
Clamp can be opened for bundle maintenance.

Low-profile release tab won't interfere with bundle or nearby routing.

The two bundles are allowed to rotate up to 90 degrees from one another.

| | |
|---|---|
| Article Number | 156-01292 |
| Type | T50RLOC15-19-SET |
| Color | Black (BK) |
| Quantity Per | carton |
| Product Description | The Locking Clip creates a full and secure lock completely around a wire bundle ranging from 10-14mm. The fixating fir tree on this clip allows for the clip to be secured into a panel by a 6mm round hole. |
| Short Description | LOC Locking Clamp, 15 - 19 mm, Unassembled to T50R Tie, PA66HIRHSUV, Black, 1000/ctn |
| Global Part Name | T50RLOC15-19-SET-PA66HS/PA66HIRHSUV-BK |

| | |
|---|---|
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 225 |
| Length L (Imperial) | 1.24 |
| Length L (Metric) | 31.6 |
| Fixation Method | Omega Clip |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Bundle Diameter Min (Imperial) | 0.59 |
| Bundle Diameter Min (Metric) | 15.0 |
| Bundle Diameter Max (Imperial) | 0.75 |
| Bundle Diameter Max (Metric) | 19.0 |
| Height H (Imperial) | 1.31 |
| Height H (Metric) | 33.4 |
| Depth D (Imperial) | 0.47 |
| Depth D (Metric) | 12.0 |

| | |
|---|---|
| Material | Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Material Shortcut | PA66HS PA66HIRHSUV |
| Flammability | UL 94 HB |
| Halogen Free | Yes |
| UV Resistant (Yes/No) | Yes |
| Operating Temperature | -40°F to +230°F (-40°C to +110°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 1000 |
| Package Quantity (Metric) | 1000 |
| Customs Number | 3926909988 |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin.

(www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.