Specifications

Eaton 170E8337

Eaton Bussmann series Fuse-link, high speed, 400 A, DC 750 V, size 2, gR, IEC, with indicator, flush end

General specifications	
PRODUCT NAME	Eaton Bussmann series high speed traction fuse
CATALOG NUMBER	170E8337
UPC	051712806640
EAN	5996516002544
PRODUCT LENGTH/DEPTH	130 mm
PRODUCT HEIGHT	77 mm
PRODUCT WIDTH	59 mm
PRODUCT WEIGHT	1051 g
COMPLIANCES	CE RoHS Compliant EAC
CERTIFICATIONS	IEC 60269-4
GLOBAL CATALOG	170E8337

Powering Business Worldwide

Product specifications

AMPERAGE RATING	400 A
BREAKING CAPACITY	100 kA
UTILIZATION CATEGORY	gR (general purpose semiconductor protection)
FUSE INDICATOR	Other
FUSE SIZE	2
CLASS	Class gR
WATT LOSSES	73 W
PRE ARC (I2T)	55000
MOUNTING DIMENSION	M10
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	129 mm
CURRENT TYPE	DC
RATED VOLTAGE DC	750 V
COLOR	None
INTERRUPT RATING	100 kAIC
CONSTRUCTION SIZE	2
PACKAGING TYPE	Standard
VOLTAGE RATING	750 V
TYPE	Fuse
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other

Resources

CATALOGS	Traction fuse-links eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-en-gb.pdf
DECLARATIONS OF CONFORMITY	eaton-high-speed-square-body-fuse-declaration-of-conformity-uk251153en.pdf eaton-high-speed-square-body-fuse-declaration-of-conformity-eu250670en.pdf
MCAD MODEL	eaton-traction-fuses-mcad-3d-models-u0515.stp

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2025 Eaton. All Rights Reserved.