



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**
Mating Tab Width: **4.75 mm [.187 in]**
Mating Tab Thickness: **.51 mm [.02 in]**
Terminal Orientation: **Straight**
Contact Base Material: **Steel**

Features

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	4.75 mm[.187 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Steel
Terminal Plating Material	Nickel
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment



Wire Insulation Support	Without
Mating Retention Type	Hole

Dimensions

Product Length	10.41 mm[.41 in]
Terminal Material Thickness	.51 mm[.02 in]

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 250 °C[-40 – 482 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL
---	---------

Packaging Features

Packaging Quantity	1000
Packaging Method	Loose Piece/Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability





Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides




on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 60006-1 250 FASTON TAB 18-14 AWG BR	 TE Part # 63771-1 187 FASTON TAB NPST	 TE Part # 60006-2 250 FASTON TAB 18-14 AWG TPBR	 TE Part # 42559-1 250 FASTON TAB NPST
 TE Part # 626417-2 250 FASTON REC 22-18 AWG TPBR	 TE Part # 1217002-1 250 FASTON,TAB, NPCST	 TE Part # 41778 250 FASTON TAB 18-14 AWG TPBR	 TE Part # 63402-3 312 FASTON TAB BR
 TE Part # 63402-2 312 FASTON TAB NPST	 TE Part # 63953-1 187 FASTON TAB		


Also in the Series | FASTON 187

 Crimp Terminal Housings(40)	 Insertion & Extraction Tools(1)	 Insulation Boots & Sleeves(1)	 PCB Terminals(42)
--	--	--	--



Quick Disconnects(204)

Customers Also Bought



TE Part #4-160256-2
250 FASTON,REC.,17-14 AWG,PNST



TE Part #794894-3
02P MINI UMNL PLUGS WIRE HOLES




TE Part #926885-1
UNIV.M-N-L.PIN




TE Part #964202-1
STD TIMER CONTACT



TE Part #1703061-1
PLUG, 2 CIRCUIT , UNIVERSAL MATE-N-LOK




TE Part #1703062-1
CAP, 2 CIRCUIT , UNIVERSAL MATE-N-LOK



TE Part #1745082-1
3 POS. TAB ASSY AMP SUPERSEAL 1.5 SRS.



TE Part #1745096-1
AMP SUPERSEAL 1,5 SRS. 2 POS. PLUG ASS'Y



TE Part #1863011-1
01P UMNL PLUG HSG



TE Part #1703061-3
PLUG, 2 CIRCUIT , UNIVERSAL MATE-N-LOK

Documents

Product Drawings
187 FASTON TAB NPST
English

CAD Files
3D PDF
3D
Customer View Model
ENG_CVM_CVM_61960-1_J.2d_dxf.zip

61960-1

Quick Disconnect Tab, Uninsulated, 4.75 mm [.187 in] Tab Width, F-Crimp, Straight, Steel, Nickel Plating, Loose Piece/Carton, Open Barrel, FASTON 187



English

Customer View Model

[ENG_CVM_CVM_61960-1_J.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_61960-1_J.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[FASTON Tabs](#)

English

Product Specifications

[Application Specification](#)

English