QPD H 4PE6,0 4X9-14 BK - H distributor

1411422

https://www.phoenixcontact.com/us/products/1411422

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



QUICKON H-distributor, black, 4+PE-pos., 2.5 mm^2 ... 6.0 mm^2/690 V/40 A, for cable diameter of 9 mm ... 14 mm, with a sealing bolt.

Your advantages

- Innovative and time saving - QUICKON fast connection for time saving of up to 80 % for on-site connection
- Robust throughout: housing with IP68/IP69K and IK07 protection for a wide range of applications
- Safer connection with mechanical coding to protect against mismatching, and touch-proof protection in accordance with DIN EN 0105
- Flexible and compact - by connecting connections internally, H and T-distributors can be used to branch master cables or they can be used as star distributors

Commercial data

Item number	1411422
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF50
Product key	BF6DCC
Catalog page	Page 489 (C-2-2019)
GTIN	4046356932240
Weight per piece (including packing)	574.3 g
Weight per piece (excluding packing)	588 g
Customs tariff number	85366990
Country of origin	PL

Technical data

Mounting

Mounting type	direct screw connection
Wrench size	30 mm

Product properties

Product type	Power distributor
Product family	QPD
Type	H-distributor
Number of positions	5
Connection profile	4+PE
Position marking	1, 2, 3, N, PE
Number of connections	5
No. of cable outlets	4
Coding	Coding profile

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Connection data


Connection technology

Connection method	IDC connection
Frequency of connections between conductors of the same cross section	max. 10

Conductor connection

Conductor cross section flexibel	2.5 mm² ... 6 mm²
Conductor cross section solid	2.5 mm² ... 6 mm²
Connection cross section AWG	14 ... 10
Tightening torque Union nut	15 Nm
Wrench size Union nut	30 mm

Dimensions

Dimensional drawing	
Width	82 mm
Height	40 mm
Length	207.8 mm
Wrench size for mounting	30 mm

Electrical properties

Rated surge voltage (II/2)	8 kV
Rated surge voltage (III/2)	8 kV
Rated surge voltage (III/3)	6 kV
Rated current	40 A
Contact resistance	< 3 mΩ
rated voltage (II/2)	1000 V
rated voltage (III/2)	1000 V
Rated voltage (III/3)	690 V
Nominal voltage U_N	690 V AC
	690 V DC
Nominal current I_N	40 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	max. 50

Material specifications

Color	black (RAL 9005)
Material Housing	PA
Material Contact	Cu
Material Contact surface	Silver-plated
Flammability rating according to UL 94	V0
Material wire insulation	PVC /PE / rubber / TPE

Cable/line

Structure of individual litz in acc. with VDE 0295 / smallest wire diameter	VDE 0295 class 1 to 6/min. 0.15 mm
External cable diameter	9 mm ... 14 mm
Wire diameter including insulation	2.95 mm ... 5 mm
Position marking	1, 2, 3, N, PE
Material wire insulation	PVC /PE / rubber / TPE


Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP68 (2 m / 24 h)
	IP69K (Distance from the nozzle 150 mm)
Ambient temperature (operation)	-40 °C ... 100 °C
Temperature when conductor connected	-5 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 100 °C


Drawings

Diagram




Derating diagram

Dimensional drawing



Dimensional drawing

Circuit diagram



Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1411422

IECEE CB Scheme
Approval ID: DE1-65875

EAC
Approval ID: RU C-DE.BL08.B.00511

DNV GL
Approval ID: TAE00003J5

VDE Zeichengenehmigung
Approval ID: 40029149

UL Listed
Approval ID: E468743

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	600 V	20 A	-	- 12

cUL Listed
Approval ID: E468743

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	600 V	20 A	- 12	-

cULus Listed

Classifications

ECLASS

ECLASS-11.0	27440603
ECLASS-13.0	27440603
ECLASS-12.0	27440603

ETIM

ETIM 9.0	EC002567

UNSPSC

UNSPSC 21.0	39121400

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Accessories

CP-QPD 5X6,0 - Coding profile

1411402

https://www.phoenixcontact.com/us/products/1411402



Coding profile, red, for insertion into the 5-pos. QUICKON dome and connector, can be positioned in 72° increments.

QPD QSK 5X6,0 - Protective cap

1411403

https://www.phoenixcontact.com/us/products/1411403



Protective cap, black plastic, for 5 x 2.5 mm^2 QPD connector, IP50.

QPD QSK BK 5X6,0 FS - Protective cap

1411400

https://www.phoenixcontact.com/us/products/1411400

Protective cap, plastic, for QUICKON connection, black, with retaining cord, IP68




GPE 13X 9 WH - Engraving material

0806932

https://www.phoenixcontact.com/us/products/0806932

Engraving material, Sheet, white, unlabeled, can be labeled with: PLOTMARK, ENGRAVING UNIT, CMS-P1-PLOTTER, P1 ENGRAVING UNIT, mounting type: adhesive, lettering field size: 13 x 9 mm, Number of individual labels: 120



EMLP (13X9)R - Label

0819453

https://www.phoenixcontact.com/us/products/0819453



Label, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, lettering field size: 13 x 9 mm, Number of individual labels: 500

SEALING PLUG 10X16 RD - Closing cap

1400284

https://www.phoenixcontact.com/us/products/1400284



Closing cap, for threads pluggable, color: red

QPD W 4PE6,0 9-14 M25 0,5 BK - Panel feed-through

1410392

https://www.phoenixcontact.com/us/products/1410392



QUICKON panel feed-through, 4+PE-pos., 2.5 mm^2 ... 6.0 mm^2/690 V/40 A, with QUICKON nut, black, for cable diameter of 9 mm ... 14 mm, M25 connection thread with 5 welded-on 6.0 mm^2 cable wires, 0.5 m long, cut flat at the end.

QPD W 4PE6,0 9-14 M25 1,0 BK - Panel feed-through

1410393

https://www.phoenixcontact.com/us/products/1410393



QUICKON panel feed-through, 4+PE-pos., 2.5 mm^2 ... 6.0 mm^2/690 V/40 A, with QUICKON nut, black, for cable diameter of 9 mm ... 14 mm, M25 connection thread with 5 welded-on 6.0 mm^2 cable wires, 1.0 m long, cut flat at the end.

QPD C 4PE6,0 1X9-14 BK - Conductor connectors

1410415

https://www.phoenixcontact.com/us/products/1410415



QUICKON cable connector, with a QUICKON nut, black, 4+PE-pos., 2.5 mm^2 ... 6.0 mm^2/690 V/40 A, for cable diameter of 9 mm ... 14 mm.

QPD C 4PE6,0 2X9-14 BK - Conductor connectors

1410410

https://www.phoenixcontact.com/us/products/1410410



QUICKON cable connector, black, 4+PE-pos., 2.5 mm^2 ... 6.0 mm^2/690 V/40 A, for cable diameter of 9 mm ... 14 mm.

QPD H 4PE6,0 4X9-14 BK - H distributor

1411422

https://www.phoenixcontact.com/us/products/1411422

QPD T 4PE6,0 2X9-14 BK - T distributor

1411416

https://www.phoenixcontact.com/us/products/1411416



QUICKON T-distributor, black, 4+PE-pos., 2.5 mm^2 ... 6.0 mm^2/690 V/40 A, for cable diameter of 9 mm ... 14 mm, with two QUICKON nuts

QPD T 4PE6,0 3X9-14 BK - T distributor

1411414

https://www.phoenixcontact.com/us/products/1411414



QUICKON T-distributor, black, 4+PE-pos., 2.5 mm^2 ... 6.0 mm^2/690 V/40 A, for cable diameter of 9 mm ... 14 mm, with three QUICKON nuts

QPD H 4PE6,0 4X9-14 BK - H distributor

1411422

https://www.phoenixcontact.com/us/products/1411422

QPD N 4PE6,0 9-14 BK - Nut

1410409

https://www.phoenixcontact.com/us/products/1410409



QUICKON nut, black, 4+PE-pos., 2.5 mm^2 ... 6.0 mm^2/690 V/40 A, for cables with a diameter of 9 mm ... 14 mm.

QPD P 4PE6,0 9-14 BK - Connector

1410386

https://www.phoenixcontact.com/us/products/1410386



Connector, product family: QPD, connection method: IDC connection, number of positions: 4+PE, 2.5 mm^2 ... 6 mm^2, 690 V, 40 A, PA, black, with QUICKON nut, external cable diameter: 9 mm ... 14 mm

QPD H 4PE6,0 4X9-14 BK - H distributor

1411422

https://www.phoenixcontact.com/us/products/1411422

QPD P 4PE6,0 9-14 TL BK - Connector

1039564

https://www.phoenixcontact.com/us/products/1039564



Connector, product family: QPD, connection method: IDC connection, number of positions: 4+PE, 2.5 mm^2 ... 6 mm^2, 690 V, 40 A, PA, black, with QUICKON nut, external cable diameter: 9 mm ... 14 mm

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com