Specifications







Eaton C22G25S

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 25 Amps, 80 kA Breaking capacity, class gG/gL, with striker, compatible with a CH22 Modular fuse holder

General specifications	
PRODUCT NAME	Eaton Bussmann series low voltage cylindrical fuse
CATALOG NUMBER	C22G25S
UPC	051712668477
EAN	5027590495394
PRODUCT LENGTH/DEPTH	58 mm
PRODUCT HEIGHT	22 mm
PRODUCT WIDTH	22 mm
PRODUCT WEIGHT	55.9 g
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	IEC 60269
GLOBAL CATALOG	C22G25S

Product specifications

AMPERAGE RATING	25 A
FITTED WITH:	Striker
FUSE SIZE	22 x 58 mm
CURRENT TYPE	AC
BREAKING CAPACITY	80 kA
FREQUENCY RATING - MAX	62 Hz
FREQUENCY RATING - MIN	45 Hz
RATED VOLTAGE AC	690 V
CLASS	Class C gL/gG
FUSE TYPE	C22G
UTILIZATION CATEGORY	gG (cable protection/equipment protection)
FUSE INDICATOR	Top fuse status indicator
WATT LOSSES	3.3 W
CONNECTION	Ferrule end x ferrule end
CONSTRUCTION SIZE	22 mm x 58 mm
FUSE SHAPE	Cylindrical
VOLTAGE TYPE	AC
SUITABLE FOR	CH22 Modular fuse holder
MATERIAL	Ceramic
MOUNTING METHOD	22 x 58 mm CH Modular fuse holder
PACKAGING TYPE	Standard
RELEASE CHARACTERISTIC	Other
QUANTITY	10
VOLTAGE RATING	690 V
TYPE	Fuse
SPECIAL FEATURES	Striker
APPLICATION	• for industrial applications • for general purpose use

Resources

CATALOGS	eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf eaton-bussmann-series-low-voltage-fuses-catalog-ca134002en-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-eu250463en.pdf eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-uk250946en.pdf
TECHNICAL DATA SHEETS	720115 Cylindrical fuses

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.