
DSSK70-008A

80 V, 2 x 35 A Schottky Diode


RoHS



Features:

- Very low V_F
- Extremely low switching losses
- Low I_{RM} values
- Improved thermal behavior
- High reliability circuit operation
- Low voltage peaks for reduced protection circuits
- Low noise switching
- RoHS compliant
- Epoxy meets UL 94 V-0

Pinout Diagram (TO-247)



1: Anode; **2:** Cathode ; **3:** Anode; **tab:** Cathode

Applications:

- Rectifiers in Switch Mode Power Supplies (SMPS)
- Free wheeling diode in low voltage converters

Product Summary

Characteristic	Value	Unit
V_{RRM}	80	V
I_{FAV}	2 x 35	A
V_F	0.65	V

© 2024 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: TK.03/01/2024

Maximum Ratings

Symbol	Characteristics	Condition	Max.	Units
V_{RSM}	Maximum Non-repetitive Reverse Blocking Voltage	T_{VJ} = 25°C	80	V
V_{RRM}	Maximum Repetitive Reverse Blocking Voltage	T_{VJ} = 25°C	80	V
I_{RMS}	RMS Current	per terminal	70	A
$I_{R(max)}$	Reverse Current	V_R = 80 V, T_{VJM} = 25°C	1	mA
		V_R = 80 V, T_{VJM} = 125°C	10	
$I_{FAV(max)}$	Average Forward Current Rectangular d = 0.5	T_C = 159°C, T_{VJM} = 175°C	35	A
$I_{FSM(max)}$	Maximum Forward Surge Current (Half Sine)	t = 10 ms, (50 Hz), T_{VJM} = 45°C	650	A
$P_{tot(max)}$	Total Power Dissipation	T_C = 25°C	215	W
T_{VJ}	Virtual Junction Temperature	–	-55 to +175	°C
T_{op}	Operating Temperature	–	-55 to +150	°C

Electrical Characteristics

Symbol	Characteristics	Conditions	Specification	Units
$V_{F(max)}$	Forward Voltage Drop	I_F = 35 A; Pulse, T_{VJM} = 25°C	0.80	V
		I_F = 70 A; Pulse, T_{VJM} = 25°C	0.89	
		I_F = 35 A; Pulse, T_{VJM} = 125°C	0.65	
		I_F = 70 A; Pulse, T_{VJM} = 125°C	0.75	
$V_{F0(max)}$	Threshold Voltage	T_{VJM} = 175°C	0.49	V
$r_{F(max)}$	Slope Resistance		2.41	mΩ
$C_{J(typ)}$	Junction Capacitance	V_R = 5 V, T_{VJM} = 25°C, f = 1 MHz	1365	pF


Thermal Specifications

Symbol	Characteristics	Condition	Specification	Units
$R_{thJC(max)}$	Thermal Resistance Junction to Case	–	0.7	K/W
$R_{thCH(typ)}$	Thermal Resistance Case to Heat Sink	–	0.3	K/W

© 2024 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: TK.03/01/2024

Characteristic Curves

Figure 1. Maximum Forward Voltage Drop Characteristics



Typical Reverse Current vs. Reverse Voltage




Figure 3. Typical Junction Capacitance vs. Reverse Voltage




Figure 4. Average Forward Current vs. Case Temperature




Figure 5. Forward Power Loss Characteristics






Figure 6. Transient Thermal Impedance




© 2024 Littelfuse, Inc.
Specifications are subject to change without notice.

Part Outline Drawing (TO-247)



Symbol	Inches		Millimeters	
	Min.	Max.	Min.	Max.
A	0.189	0.205	4.80	5.20
A1	0.090	0.10	2.29	2.54
A2	0.075	0.083	1.90	2.10
b	0.043	0.051	1.10	1.30
b1	0.075	0.087	1.91	2.20
b2	0.115	0.126	2.92	3.20
c	0.020	0.027	0.50	0.70
D	0.819	0.840	20.80	21.34
D1	0.686	0.702	17.43	17.83
E	0.620	0.635	15.75	16.13
E1	0.514	0.530	13.06	13.46
E2	0.170	0.190	4.32	4.83
e	0.215 BSC		5.45 BSC	
L	0.781	0.797	19.85	20.25
L1	–	0.177	–	4.49
Ø P	0.140	0.144	3.55	3.65
Ø P1	0.281-	0.285	7.14	7.24
Q	0.220	0.244	5.59	6.19
S	0.242 BSC		6.15 BSC	

Part Number and Marking



D = Diode
S = Schottky Diode
SK = Product Generation
70 = Current Rate
008 = Voltage Rating
A = Package Code
YY = Year
WW = Work Week
Z = Plant Location Code
xxxx = Lot Number

Ordering Information

Part Number	Marking	Packing Mode	Quantity
DSSK70-008A	DSSK70-008A	Tube	30 pcs/ tube

Disclaimer Notice

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications.
Read complete Disclaimer Notice at http://www.littelfuse.com/disclaimer-electronics.

IXYS Part of: Littelfuse
Expertise Applied | Answers Delivered

© 2024 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: TK.03/01/2024