Environmental Monitoring Sensor, Temperature, Humidity, Contact-Closure Inputs for Use with TLNETCARD

MODEL NUMBER: **TLNETEM**



Ensure ideal environmental conditions with remote monitoring of ambient temperature, humidity and contact-closure status on compatible SmartPro® or SmartOnline® UPS systems operating with a TLNETCARD.

Description

Connect a TLNETEM module to a Tripp Lite TLNETCARD on a compatible UPS system and gain the ability to monitor your network's environmental conditions from anywhere in the world. The TLNETEM contains a temperature and humidity sensor as well as a dry contact interface to monitor up to four compatible devices, such as smoke detectors, fire alarms and security systems.

By ensuring the optimum environment in your network closet or data center, the TLNETEM helps prevent equipment failure and costly downtime caused by excessive heat and high-humidity conditions.

Features

Remotely Monitor Your Network Environment

- Allows users to remotely monitor temperature and humidity in network environments
- Helps prevent equipment degradation and failure
- Dry-contact interface enables monitoring of up to four alarm, security and telecom devices

Versatile and Easy Installation

- Integrates easily with a Tripp Lite SmartPro or SmartOnline UPS System operating with a TLNETCARD web management accessory
- Extra-long cable allows the sensor to be mounted up to 12 ft. away from the TLNETCARD

TAA Compliant

- Complies with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Highlights

- Environmental Monitoring Sensor for use with Tripp Lite TLNETCARD enabled UPS systems
- Reports the ambient temperature, humidity and contact closure status of up to four compatible devices
- Simple installation and integration into existing compatible systems
- TAA compliant

System Requirements

- Compatible Tripp Lite SmartPro or SmartOnline UPS system with a TLNETCARD installed
- Web browser or terminal emulator

Package Includes

- TLNETEM Environmental Monitoring Sensor
- Owner's Manual

Specifications

OVERVIEW	
UPC Code	037332191687
PHYSICAL	
Shipping Dimensions (hwd / in.)	1.65 x 6.06 x 6.38
Shipping Dimensions (hwd / cm)	4.19 x 15.39 x 16.21
Shipping Weight (lbs.)	0.55
Shipping Weight (kg)	0.25
COMMUNICATIONS	
Product Compatibility	TLNETCARD
FEATURES & SPECIFICATIONS	
Sensing Capability	Temperature; Humidity
Contact Closure Capability	Contact Closure Input Monitoring
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	2-year limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
https://tripplite.eaton.com

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.