# VAL-US-240D/40-P - Type 1 surge protection plug

2910337

https://www.phoenixcontact.com/us/products/2910337

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



UL Recognized type 1 SPD and IEC type 2 surge protection plug with a varistor and thermal disconnect for use with VAL-US base elements, mechanical and visual fault warning

## Product description

Surge protective device replacement plug

## Commercial data

| | |
|---|---|
| Item number | 2910337 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | CL18 |
| Product key | CL1321 |
| Catalog page | Page 98 (C-4-2019) |
| GTIN | 4055626444499 |
| Weight per piece (including packing) | 44.5 g |
| Weight per piece (excluding packing) | 33 g |
| Customs tariff number | 85363030 |
| Country of origin | DE |

## Technical data

### Notes

| | |
|---|---|
| General | Used in: |

### Product properties

| | |
|---|---|
| Product type | Replacement plug |
| Product family | VALVETRAB MS |
| IEC test classification | II |
| | T2 |
| EN type | T2 |
| Type | Male |
| Number of positions | 1 |
| Surge protection fault message | optical |

Insulation characteristics

| | |
|---|---|
| Overvoltage category | III |
| Pollution degree | 2 |


### Electrical properties

| | |
|---|---|
| Nominal frequency $f_N$ | 50 Hz (60 Hz) |

### Connection data

| | |
|---|---|
| Connection method | VALVETRAB plug-in system |

### Dimensions

| | |
|---|---|
| Dimensional drawing |  |
| Width | 17.5 mm |
| Height | 52.4 mm |
| Depth | 55.3 mm |
| Horizontal pitch | 1 Div. |

### Material specifications

| | |
|---|---|
| Color | black (RAL 9005) |
| Flammability rating according to UL 94 | V-0 |
| CTI value of material | 600 |
| Insulating material | PA 6.6/PBT |
| Material group | I |
| Housing material | PA 6.6 |

| | |
|---|---|
| | PBT |

## Protective circuit

| | |
|---|---|
| Mode of protection | L-L |
| | L-PEN |
| Direction of action | 1L-N/PE |
| Nominal voltage $U_N$ | 240/415 V AC |
| Nominal frequency $f_N$ | 50 Hz (60 Hz) |
| Maximum continuous voltage $U_C$ | 275 V AC |
| Residual current $I_{PE}$ | ≤ 450 µA |
| Standby power consumption $P_C$ | ≤ 120.00 mVA |
| Nominal discharge current $I_n$ (8/20) µs | 20 kA |
| Maximum discharge current $I_{max}$ (8/20) µs | 40 kA |
| Short-circuit current rating $I_{SCCR}$ | 25 kA |
| Voltage protection level $U_p$ | ≤ 1.35 kV |
| Residual voltage $U_{res}$ | ≤ 1.35 kV (at $I_n$) |
| | ≤ 1.1 kV (at 10 kA) |
| | ≤ 1 kV (at 5 kA) |
| | ≤ 0.9 kV (at 3 kA) |
| TOV behavior at $U_T$ | 335 V AC (5 s / withstand mode) |
| | 440 V AC (120 min / safe failure mode) |
| Max. backup fuse with branch wiring | 100 A (gG) |

### Additional technical data

| | |
|---|---|
| Maximum discharge current $I_{max}$ (8/20) µs | 40 kA |

## Environmental and real-life conditions

### Ambient conditions

| | |
|---|---|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -40 °C ... 80 °C |
| Ambient temperature (storage/transport) | -40 °C ... 80 °C |
| Altitude | ≤ 2000 m (amsl) |
| Permissible humidity (operation) | 5 % ... 95 % |
| Shock (operation) | 25g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z) |
| Vibration (operation) | 5g (10 ... 500 Hz / 2.5 h / X, Y, Z) |

## Approvals

### UL specifications

| | |
|---|---|
| Maximum continuous operating voltage MCOV | 275 V AC |
| Short-circuit current rating (SCCR) | 200 kA |
| Voltage protection rating VPR | 1000 V |
| UL type | type 1 |
| Nominal discharge current $I_n$ | 20 kA |
| Maximum Surge Current per Phase | 40 kA |

| | |
|---|---|
| Mode of protection | L-L |
| | L-G |
| Nominal voltage | 240 V AC (Delta) |
| Power distribution system | Single phase |
| Nominal frequency | 50/60 Hz |
| SPD Type | 1CA |

## Standards and regulations

Air clearances and creepage distances

| | |
|---|---|
| Standards/regulations | EN 60664-1 / EN 61643-11 |
| Standards/specifications | IEC 61643-11 |
| Note | 2011 |
| Standards/specifications | EN 61643-11 |
| Note | 2012 |

## Mounting


| | |
|---|---|
| Mounting type | on base element |

## Drawings

Circuit diagram



Dimensional drawing



## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2910337

**cUL Recognized**
Approval ID: FILE E 330181

**UL Recognized**
Approval ID: FILE E 330181

**cULus Recognized**

## Classifications

### ECLASS

| | |
|---|---|
| ECLASS-11.0 | 27130890 |
| ECLASS-13.0 | 27171292 |

### ETIM

| | |
|---|---|
| ETIM 8.0 | EC002496 |

### UNSPSC

| | |
|---|---|
| UNSPSC 21.0 | 39121600 |

## Environmental product compliance

EU RoHS

| | |
|---|---|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |

China RoHS

| | |
|---|---|
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |

EU REACH SVHC

| | |
|---|---|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

## Accessories

### VAL-US-240D/40/1+0-FM - Type 1 surge protection device

2910368

https://www.phoenixcontact.com/us/products/2910368



Surge protective device, single channel with remote indicator contact for 240 V AC DELTA.

### VAL-US-240D/40/2+0-FM - Type 1 surge protection device

2910369

https://www.phoenixcontact.com/us/products/2910369



Surge protective device, two channel with remote indicator contact for 240 V AC corner-grounded DELTA.

## VAL-US-240D/40/3+0-FM - Type 1 surge protection device

2910370

https://www.phoenixcontact.com/us/products/2910370



Surge protective device, three channel with remote indicator contact for 240 V AC DELTA.

## VAL-US-240HLD/40/3+1-FM - Type 1 surge protection device

2910371

https://www.phoenixcontact.com/us/products/2910371



Surge protective device, four channel with remote indicator contact for 240 V AC high-leg DELTA.


Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com



Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com