



A (10 : 1)

RECOMMENDED METAL MASK (FREE)

THICKNESS : 0.1mm
OPEN AREA RATIO:100%



MATING FIFURE(5:1)



NOTES 1. LEAD CO-PLANARITY SHALL BE 0.1mm MAX
2. PLEASE CONSULT HIROSE WHEN THE PRODUCT IS MOUNTED TO FPC.

3	BRASS	CONTACT AREA : Sn PLATING 1μm MIN UNDER PLATING : Cu PLATING 0.3μm MIN				
2	BRASS	CONTACT AREA : Au PLATING 0.05μm MIN LEAD AREA : Au PLATING 0.05μm MIN UNDER PLATING : Ni PLATING 1μm MIN		6	PS	REEL , BLACK
				5	POLYESTER	CLEAR
1	LCP	BLACK , UL94V-0		4	PS	CLEAR
NO.	MATERIAL	FINISH , REMARKS		NO.	MATERIAL	CLEAR

UNITS mm		SCALE 5 : 1		COUNT 1	DESCRIPTION OF REVISIONS DIS-H-00005111	DESIGNED HT. SATO	CHECKED SZ. ONO	DATE 2019071
 HIROSE ELECTRIC CO., LTD.		APPROVED : KI. AKIYAMA		20120702	DRAWING NO. EDC3-335023-01			
		CHECED : HK. UMEHARA		20120702	PART NO. DF50A-2P-1H(51)			
		DESIGNED : ST. SATO		20120629	CODE NO. CL665-1031-4-51			
		DRAWN : MI. SAKIMURA		20120627	 			

