

BUK7C08-55AITE

N-channel TrenchPLUS standard level FET

Rev. 02 — 17 February 2009 **Product data sheet**

1. Product profile

1.1 General description

Standard level N-channel enhancement mode Field-Effect Transistor (FET) in a plastic package using TrenchMOS technology. The devices include TrenchPLUS current sensing and diodes for ElectroStatic Discharge (ESD) protection and temperature sensing. This product has been designed and qualified to the appropriate AEC standard for use in automotive critical applications.

1.2 Features and benefits

- Allows responsive temperature monitoring due to integrated temperature sensor
- Electrostatically robust due to integrated protection diodes
- Low conduction losses due to low on-state resistance
- Q101 compliant
- Reduced component count due to integrated current sensor

1.3 Applications

- Automotive and general purpose power switching
- Fan control
- Electrical Power Assisted Steering (EPAS)
- Variable Valve Timing for engines

1.4 Quick reference data

Table 1. Quick reference



Symbol	Parameter	Conditions		Min	Typ	Max	Unit
V_{DS}	drain-source voltage	$T_j \geq 25$ °C; $T_j \leq 175$ °C		-	-	55	V
I_D	drain current	V_{GS} = 10 V; T_{mb} = 25 °C; see Figure 2; see Figure 3	[1]	-	-	130	A
Static characteristics							
R_{DSon}	drain-source on-state resistance	V_{GS} = 10 V; I_D = 50 A; T_j = 25 °C; see Figure 7; see Figure 8		-	6.8	8	mΩ
I_D/I_{sense}	ratio of drain current to sense current	T_j > -55 °C; T_j < 175 °C; V_{GS} > 5 V		450	500	550	
$S_{F(TSD)}$	temperature sense diode temperature coefficient	I_F = 250 µA; T_j > -55 °C; T_j < 175 °C		-1.4	-1.54	-1.68	mV/K
$V_{F(TSD)}$	temperature sense diode forward voltage	I_F = 250 µA; T_j = 25 °C		648	658	668	mV

[1] Current is limited by power dissipation chip rating.

nexperia

2. Pinning information

Table 2. Pinning information

Pin	Symbol	Description	Simplified outline	Graphic symbol
1	G	gate	 SOT427 (D2PAK)	
2	ISENSE	sense current		
3	A	anode		
4	D	drain		
5	K	cathode		
6	KS	Kelvin source		
7	S	source		
mb	D	mounting base; connected to drain		

3. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
BUK7C08-55AITE	D2PAK	plastic single-ended surface-mounted package (D2PAK); 7 leads (one lead cropped)	SOT427

© Nexperia B.V. 2017. All rights reserved

4. Limiting values

Table 4. Limiting values


In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions		Min	Max	Unit
V_{DS}	drain-source voltage	$T_j \geq 25$ °C; $T_j \leq 175$ °C		-	55	V
V_{DGR}	drain-gate voltage	R_{GS} = 20 kΩ		-	55	V
V_{GS}	gate-source voltage			-20	20	V
I_D	drain current	T_{mb} = 25 °C; V_{GS} = 10 V; see Figure 2; see Figure 3	[1]	-	130	A
			[2]	-	75	A
		T_{mb} = 100 °C; V_{GS} = 10 V; see Figure 2	[2]	-	75	A
I_{DM}	peak drain current	T_{mb} = 25 °C; $t_p \leq 10$ µs; pulsed; see Figure 3		-	522	A
P_{tot}	total power dissipation	T_{mb} = 25 °C; see Figure 1		-	272	W
$I_{GS(CL)}$	gate-source clamping current	continuous		-	10	mA
		pulsed; t_p = 5 ms; δ = 0.01		-	50	mA
$V_{isol(FET-TSD)}$	FET to temperature sense diode isolation voltage			-100	100	V
T_{stg}	storage temperature			-55	175	°C
T_j	junction temperature			-55	175	°C
Source-drain diode						
I_S	source current	T_{mb} = 25 °C	[1]	-	130	A
			[2]	-	75	A
I_{SM}	peak source current	$t_p \leq 10$ µs; pulsed; T_{mb} = 25 °C		-	522	A
Avalanche ruggedness						
$E_{DS(AL)S}$	non-repetitive drain-source avalanche energy	I_D = 75 A; $V_{sup} \leq 55$ V; R_{GS} = 50 Ω; V_{GS} = 10 V; $T_{j(init)}$ = 25 °C; unclamped		-	460	mJ
Electrostatic discharge						
V_{esd}	electrostatic discharge voltage	HBM; C = 100 pF; R = 1.5 kΩ		-	6	kV

[1] Current is limited by power dissipation chip rating.


[2] Continuous current is limited by package.

© Nexperia B.V. 2017. All rights reserved




$$P_{der} = \frac{P_{tot}}{P_{tot(25°C)}} \times 100\,\%$$

Fig 1. Normalized total power dissipation as a function of mounting base temperature



$$V_{GS} \geq 10V$$

Fig 2. Normalized continuous drain current as a function of mounting base temperature



$$T_{mb} = 25°C; I_{DM} \text{ is single pulse}$$

Fig 3. Safe operating area; continuous and peak drain currents as a function of drain-source voltage

© Nexperia B.V. 2017. All rights reserved

5. Thermal characteristics

Table 5. Thermal characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$R_{th(j-a)}$	thermal resistance from junction to ambient	mounted on printed-circuit board; minimum footprint	-	-	50	K/W
$R_{th(j-mb)}$	thermal resistance from junction to mounting base	see Figure 4	-	-	0.55	K/W




Fig 4. Transient thermal impedance from junction to mounting base as a function of pulse duration

© Nexperia B.V. 2017. All rights reserved

6. Characteristics

Table 6. Characteristics


Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static characteristics						
$V_{(BR)DSS}$	drain-source breakdown voltage	I_D = 0.25 mA; V_{GS} = 0 V; T_j = 25 °C	55	-	-	V
		I_D = 0.25 mA; V_{GS} = 0 V; T_j = -55 °C	50	-	-	V
$V_{GS(th)}$	gate-source threshold voltage	I_D = 1 mA; V_{DS} = V_{GS}; T_j = 25 °C; see Figure 9	2	3	4	V
		I_D = 1 mA; V_{DS} = V_{GS}; T_j = 175 °C; see Figure 9	1	-	-	V
		I_D = 1 mA; V_{DS} = V_{GS}; T_j = -55 °C; see Figure 9	-	-	4.4	V
I_{DSS}	drain leakage current	V_{DS} = 40 V; V_{GS} = 0 V; T_j = 25 °C	-	0.1	10	µA
		V_{DS} = 40 V; V_{GS} = 0 V; T_j = 175 °C	-	-	250	µA
$V_{(BR)GSS}$	gate-source breakdown voltage	I_G = 1 mA; V_{DS} = 0 V; T_j > -55 °C; T_j < 175 °C	20	22	-	V
		I_G = -1 mA; V_{DS} = 0 V; T_j > -55 °C; T_j < 175 °C	20	22	-	V
I_{GSS}	gate leakage current	V_{DS} = 0 V; V_{GS} = 10 V; T_j = 25 °C	-	22	1000	nA
		V_{DS} = 0 V; V_{GS} = -10 V; T_j = 25 °C	-	22	1000	nA
		V_{DS} = 0 V; V_{GS} = 10 V; T_j = 175 °C	-	-	10	µA
		V_{DS} = 0 V; V_{GS} = -10 V; T_j = 175 °C	-	-	10	µA
R_{DSon}	drain-source on-state resistance	V_{GS} = 10 V; I_D = 50 A; T_j = 25 °C; see Figure 7; see Figure 8	-	6.8	8	mΩ
		V_{GS} = 10 V; I_D = 50 A; T_j = 175 °C; see Figure 7; see Figure 8	-	-	16	mΩ
$R_{(D\text{-}ISENSE)on}$	drain-ISENSE on-state resistance	V_{GS} = 10 V; I_D = 25 mA; T_j = 25 °C; see Figure 18	1.32	1.55	1.82	Ω
		V_{GS} = 10 V; I_D = 25 mA; T_j = 175 °C; see Figure 18	3.04	3.57	4.19	Ω
$V_{F(TSD)}$	temperature sense diode forward voltage	I_F = 250 µA; T_j = 25 °C	648	658	668	mV
$S_{F(TSD)}$	temperature sense diode temperature coefficient	I_F = 250 µA; T_j > -55 °C; T_j < 175 °C	-1.4	-1.54	-1.68	mV/K
$V_{F(TSD)hys}$	temperature sense diode forward voltage hysteresis	I_F > 125 µA; I_F < 250 µA; T_j = 25 °C	25	32	50	mV
I_D/I_{sense}	ratio of drain current to sense current	V_{GS} > 5 V; T_j > -55 °C; T_j < 175 °C	450	500	550	
Dynamic characteristics						
$Q_{G(tot)}$	total gate charge	I_D = 25 A; V_{DS} = 44 V; V_{GS} = 10 V; T_j = 25 °C; see Figure 14	-	116	-	nC
Q_{GS}	gate-source charge		-	19	-	nC
Q_{GD}	gate-drain charge		-	51	-	nC

© Nexperia B.V. 2017. All rights reserved

Table 6. Characteristics *…continued*


Symbol	Parameter	Conditions	Min	Typ	Max	Unit
C_{iss}	input capacitance	V_{GS} = 0 V; V_{DS} = 25 V; f = 1 MHz; T_j = 25 °C; see Figure 12	-	4200	-	pF
C_{oss}	output capacitance		-	920	-	pF
C_{rss}	reverse transfer capacitance		-	500	-	pF
$t_{d(on)}$	turn-on delay time	V_{DS} = 30 V; R_L = 1.2 Ω; V_{GS} = 10 V; $R_{G(ext)}$ = 10 Ω; T_j = 25 °C	-	35	-	ns
t_r	rise time		-	115	-	ns
$t_{d(off)}$	turn-off delay time		-	155	-	ns
t_f	fall time		-	110	-	ns
L_D	internal drain inductance	measured from upper edge of drain mounting base to centre of die; T_j = 25 °C	-	2.5	-	nH
L_S	internal source inductance	measured from source lead to source bond pad; T_j = 25 °C; lead length 6 mm	-	7.5	-	nH
Source-drain diode						
V_{SD}	source-drain voltage	I_S = 40 A; V_{GS} = 0 V; T_j = 25 °C; see Figure 19	-	0.85	1.2	V
t_{rr}	reverse recovery time	I_S = 20 A; dI_S/dt = -100 A/µs; V_{GS} = -10 V; V_{DS} = 30 V; T_j = 25 °C	-	80	-	ns
Q_r	recovered charge		-	200	-	nC

© Nexperia B.V. 2017. All rights reserved




$T_j = 25°C; t_p = 300\mu s$

Fig 5. Output characteristics: drain current as a function of drain-source voltage; typical values




$T_j = 25°C; I_D = 50A$

Fig 6. Drain-source on-state resistance as a function of gate-source voltage; typical values



$T_j = 25°C; t_p = 300\mu s$


Fig 7. Drain-source on-state resistance as a function of drain current; typical values



$$a = \frac{R_{DSon}}{R_{DSon(25°C)}}$$


Fig 8. Normalized drain-source on-state resistance factor as a function of junction temperature

© Nexperia B.V. 2017. All rights reserved




$I_D = 1mA; V_{DS} = V_{GS}$

Fig 9. Gate-source threshold voltage as a function of junction temperature




$T_j = 25 \quad C; V_{DS} = V_G$

Fig 10. Sub-threshold drain current as a function of gate-source voltage



$T_j = 25°C; V_{DS} = 25V$


Fig 11. Forward transconductance as a function of drain current; typical values



$V_{GS} = 0V; f = 1MHz$


Fig 12. Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values

© Nexperia B.V. 2017. All rights reserved




$V_{DS} = 25V$

Fig 13. Transfer characteristics: drain current as a function of gate-source voltage; typical values




$T_j = 25°C; I_D = 25A$

Fig 14. Gate-source voltage as a function of turn-on gate charge; typical values



$I_F = 250\mu A$


Fig 15. Forward voltage of temperature sense diode as a function of junction temperature; typical values



$V_F \text{ at } T_j = 25°C; I_F = 250\mu A$


Fig 16. Temperature coefficient of temperature sense diode as a function of forward voltage; typical values

© Nexperia B.V. 2017. All rights reserved




$I_D = 25A$

Fig 17. Drain-sense current ratio as a function of gate voltage; typical values



$I_{sense} = 25\ mA$

Fig 18. Drain-ISENSE on-state resistance as function of gate-source voltage; typical values




$V_{GS} = 0V$

Fig 19. Reverse diode current as a function of reverse diode voltage; typical values

© Nexperia B.V. 2017. All rights reserved

7. Package outline

Plastic single-ended surface-mounted package (D2PAK); 7 leads (one lead cropped) **SOT427**



DIMENSIONS (mm are the original dimensions)

UNIT	A	A_1	b	c	D max.	D_1	E	e	L_p	H_D	Q
mm	4.50 4.10	1.40 1.27	0.85 0.60	0.64 0.46	11	1.60 1.20	10.30 9.70	1.27	2.90 2.10	15.80 14.80	2.60 2.20

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT427						~~05-03-09~~ 06-03-16

Fig 20. Package outline SOT427 (D2PAK)

© Nexperia B.V. 2017. All rights reserved

8. Revision history

Table 7. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
BUK7C08-55AITE_2	20090217	Product data sheet	-	BUK7C08_55AITE-01
Modifications:	• The format of this data sheet has been redesigned to comply with the new identity guidelines of NXP Semiconductors. • Legal texts have been adapted to the new company name where appropriate.			
BUK7C08_55AITE-01 (9397 750 11696)	20030819	Product data sheet	-	-

© Nexperia B.V. 2017. All rights reserved

9. Legal information

9.1 Data sheet status

Document status [1][2]	Product status[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.nexperia.com.

9.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

9.3 Disclaimers

General — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — Nexperia products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of a Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia accepts no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

Terms and conditions of sale — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nexperia.com/profile/terms, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by Nexperia. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

9.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

10. Contact information

For more information, please visit: http://www.nexperia.com

For sales office addresses, please send an email to: salesaddresses@nexperia.com

© Nexperia B.V. 2017. All rights reserved

11. Contents

1 Product profile 1
1.1 General description 1
1.2 Features and benefits 1
1.3 Applications 1
1.4 Quick reference data 1
2 Pinning information 2
3 Ordering information 2
4 Limiting values 3
5 Thermal characteristics 5
6 Characteristics 6
7 Package outline 12
8 Revision history 13
9 Legal information 14
9.1 Data sheet status 14
9.2 Definitions 14
9.3 Disclaimers 14
9.4 Trademarks 14
10 Contact information 14

© Nexperia B.V. 2017. All rights reserved

For more information, please visit: http://www.nexperia.com
For sales office addresses, please send an email to: salesaddresses@nexperia.com
Date of release: 17 February 2009