




PIDG

TE Internal #: 2-324075-1

Closed Ring Tongue Terminal, 26 – 22 AWG, #10 Stud, 5 mm [.19 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Partially Insulated

[View on TE.com >](#)

Terminals & Splices > Ring Terminals > PIDG Ring Tongue Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 202 – 810 CMA

Stud Size: #10

[All PIDG Ring Tongue Terminals \(410\)](#)

Features

Product Type Features

|                                        |                             |
|----------------------------------------|-----------------------------|
| Ring Terminal Product Type             | Closed Ring Tongue Terminal |
| Stud Size                              | #10                         |
| Sealable                               | No                          |
| Wire Insulation Support Retention Type | Insulation Support          |

Configuration Features

|                 |   |
|-----------------|---|
| Number of Holes | 1 |
|-----------------|---|

Electrical Characteristics

|                |       |
|----------------|-------|
| Voltage Rating | 300 V |
|----------------|-------|

Body Features

|                |        |
|----------------|--------|
| Product Weight | .237 g |
|----------------|--------|

Contact Features

|                      |          |
|----------------------|----------|
| Barrel Type          | Closed   |
| Terminal Orientation | Straight |



|                           |     |
|---------------------------|-----|
| Terminal Plating Material | Tin |
|---------------------------|-----|

Mechanical Attachment

|                         |      |
|-------------------------|------|
| Wire Insulation Support | With |
|-------------------------|------|

Dimensions

|                                      |                               |
|--------------------------------------|-------------------------------|
| Wire Size                            | 202 – 810 CMA                 |
| Stud Diameter                        | 5 mm[.19 in]                  |
| Tongue Thickness                     | .79 mm[.031 in]               |
| Product Length                       | 18.8 mm[.74 in]               |
| Compatible Insulation Diameter (Max) | 2.08 mm[.082 in]              |
| Compatible Insulation Diameter Range | 1.27 – 2.08 mm[.05 – .082 in] |

Usage Conditions

|                             |                        |
|-----------------------------|------------------------|
| Insulation Option           | Partially Insulated    |
| Operating Temperature Range | 0 – 105 °C[0 – 221 °F] |

Operation/Application

|                                       |        |
|---------------------------------------|--------|
| Compatible With Wire Base Material    | Copper |
| Compatible With Wire Plating Material | Tin    |

Industry Standards

|                               |    |
|-------------------------------|----|
| Government Qualified Terminal | No |
|-------------------------------|----|

Packaging Features

|                    |              |
|--------------------|--------------|
| Packaging Quantity | 4000         |
| Packaging Method   | Tape Mounted |

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                       |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                         |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2025 (250)<br>Candidate List Declared Against: JUNE 2025 (250)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC                                                     |



Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




REPRESENTATION ONLY

TE Part # 46121  
DAHT PG PIDG 26-22 ASSY

Also in the Series | PIDG



Compression Connectors(50)



Crimp Wire Pins, Tabs & Ferrules(39)




Knife Disconnects(11)



Quick Disconnects(38)



Ring Terminals(589)



Spade Terminals(228)



Special Purpose Terminals(1)




Splices(41)

Customers Also Bought



TE Part #NB14474001  
VERSAFIT-3/8-0-FSP



TE Part #1-87631-4  
18 MODIV HSG DR MKRD .100 POL



TE Part #745253-2  
20 DF SCKT CONT,PLTD




TE Part #747275-2  
025 LP HDF STRAIN RELIEF



TE Part #1658614-2  
25 POS HDF RCPT, AP, LEAD FREE



TE Part #1658615-4  
09 POS HDF PLUG, AP, LEAD FREE



TE Part #354559-1  
CONTROL PANEL ASSEMBLY



TE Part #690472-2  
STRIPPER



TE Part #690542-2  
FEED PAWL-MACHINING



TE Part #1320928-4  
STRIP GUIDE

Documents

Product Drawings  
TERMINAL,PIDG R 26-22 10

English

CAD Files  
3D PDF  
English  
Customer View Model  
ENG\_CVM\_2-324075-1\_G.2d\_dxf.zip

English  
Customer View Model  
ENG\_CVM\_2-324075-1\_G.3d\_igs.zip

English  
Customer View Model  
ENG\_CVM\_2-324075-1\_G.3d\_stp.zip

English  
3D PDF

3D



Customer View Model

[ENG\\_CVM\\_CVM\\_2-324075-1\\_F.2d\\_dxf.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_2-324075-1\\_F.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_2-324075-1\\_F.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[PIDG Terminals and Splices Quick Reference Guide](#)

English

Product Specifications

[Application Specification](#)

English