RONDA-S-C

~25° spot beam with holder C compatible with LEDiL HEKLA



SPECIFICATION:

Dimensions	Ø 52.1 mm
Height	17.2 mm
Fastening	socket
ROHS compliant	yes

MATERIALS:

Component	Type	Material	Colour	Finish	Length
F15667_RONDA-S	Single lens	PMMA	clear		49.9
F15635_RONDA-HLD-C	Holder	PC	white		53.9

ORDERING INFORMATION:

Quantities for one set:

Single lens	1
Holder	1

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

Component		Qty in box	MOQ	MPQ	Box weight (kg)
F15667_RONDA-S » Box size: 480 x 280 x 300 mm	Single lens	420	120	30	6.3
F15635_RONDA-HLD-C » Box size: 480 x 280 x 300 mm	Holder	420	120	30	4.1

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



See also our general installation guide: www.ledil.com/installation_guide

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

bridgelux

LED	V11 HD Gen 8
FWHM / FWTM	30.0° / 62.0°
Efficiency	84 %
Peak intensity	1.8 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
Bender Wirth: 633d Hekla





Light distribution files

bridgelux

LED	V4 HD Gen 7
FWHM / FWTM	16.0° / 32.0°
Efficiency	90 %
Peak intensity	6.6 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15253_HEKLA-SOCKET-A





Light distribution files

bridgelux

LED	V6 Gen6
FWHM / FWTM	18.0° / 38.0°
Efficiency	89 %
Peak intensity	4.5 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15253_HEKLA-SOCKET-A





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

bridgelux

LED	V6 HD Gen 7
FWHM / FWTM	20.0° / 39.0°
Efficiency	89 %
Peak intensity	4.3 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15255_HEKLA-SOCKET-C





Light distribution files

bridgelux

LED	V9 HD Gen7
FWHM / FWTM	25.0° / 49.0°
Efficiency	87 %
Peak intensity	2.7 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15859_HEKLA-SOCKET-I





Light distribution files

bridgelux

LED	VERO10
FWHM / FWTM	25.0° / 53.0°
Efficiency	87 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15616_HEKLA-SOCKET-F





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

bridgelux

LED	Vesta TW 13mm (25W) CSP
FWHM / FWTM	32.0° / 76.0°
Efficiency	79 %
Peak intensity	1.3 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
- C16142_HEKLA-SOCKET-K
- Bender Wirth: 492 Typ L8





Light distribution files

bridgelux

LED	Vesta TW 6mm DP
FWHM / FWTM	20.0° / 41.0°
Efficiency	83 %
Peak intensity	3.7 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
- C16142_HEKLA-SOCKET-K
- Bender Wirth: 504 Typ L8





Light distribution files

bridgelux

LED	Vesta TW 9mm (12W) CSP
FWHM / FWTM	26.0° / 55.0°
Efficiency	82 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
- C16142_HEKLA-SOCKET-K
- Bender Wirth: 489 Typ L8





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CITIZEN

LED	CLC020 Series (Dim-To-Warm)
FWHM / FWTM	28.0° / 58.0°
Efficiency	81 %
Peak intensity	1.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C16142_HEKLA-SOCKET-K	





Light distribution files

CITIZEN

LED	CLL02x/CLU02x (LES10)
FWHM / FWTM	26.0° / 54.0°
Efficiency	86 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15255_HEKLA-SOCKET-C	





Light distribution files

CITIZEN

LED	CLU700/701/702/703
FWHM / FWTM	19.0° / 39.0°
Efficiency	87 %
Peak intensity	4.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15255_HEKLA-SOCKET-C	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CITIZEN

LED	CLU7A2/7A3
FWHM / FWTM	15.0° / 31.0°
Efficiency	89 %
Peak intensity	6.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15255_HEKLA-SOCKET-C	





Light distribution files

CREE LEDs

LED	CMA1516
FWHM / FWTM	27.0° / 52.0°
Efficiency	89 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15256_HEKLA-SOCKET-D	





Light distribution files

CREE LEDs

LED	CMA1825
FWHM / FWTM	33.0° / 68.0°
Efficiency	87 %
Peak intensity	1.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15254_HEKLA-SOCKET-B	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CREE LEDs

LED	CMT14xx
FWHM / FWTM	28.0° / 55.0°
Efficiency	88 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15255_HEKLA-SOCKET-C





Light distribution files

CREE LEDs

LED	CMT19xx
FWHM / FWTM	35.0° / 82.0°
Efficiency	82 %
Peak intensity	1.2 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15859_HEKLA-SOCKET-I





Light distribution files

CREE LEDs

LED	CXA/B 13xx
FWHM / FWTM	19.0° / 39.0°
Efficiency	88 %
Peak intensity	4.4 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15956_HEKLA-SOCKET-J





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CREE LEDs

LED	CXA/B 15xx
FWHM / FWTM	25.0° / 50.0°
Efficiency	88 %
Peak intensity	2.7 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15256_HEKLA-SOCKET-D





Light distribution files

LUMILEDS

LED	LUXEON CX Plus CoB L08 (Gen2)
FWHM / FWTM	36.0° / 82.0°
Efficiency	84 %
Peak intensity	1.2 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
Bender Wirth: 637a Hekla





Light distribution files

LUMILEDS

LED	LUXEON CoB 1202HD
FWHM / FWTM	21.0° / 40.0°
Efficiency	89 %
Peak intensity	4.1 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15848_HEKLA-SOCKET-G





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LUMILEDS

LED	LUXEON CoB 1202s
FWHM / FWTM	19.0° / 39.0°
Efficiency	89 %
Peak intensity	4.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15848_HEKLA-SOCKET-G	





Light distribution files

LUMILEDS

LED	LUXEON CoB 1204HD
FWHM / FWTM	27.0° / 51.0°
Efficiency	88 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15858_HEKLA-SOCKET-H	





Light distribution files

LUMILEDS

LED	LUXEON CoB 1205HD
FWHM / FWTM	31.0° / 61.0°
Efficiency	86 %
Peak intensity	1.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15858_HEKLA-SOCKET-H	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LUMILEDS

LED	LUXEON CX Plus CoB - HD S01H4
FWHM / FWTM	18.0° / 37.0°
Efficiency	89 %
Peak intensity	5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
Bender Wirth: 634c Hekla	





Light distribution files

LUMILEDS

LED	LUXEON CX Plus CoB - HD S02H6
FWHM / FWTM	19.0° / 39.0°
Efficiency	90 %
Peak intensity	4.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
Bender Wirth: 634c Hekla	





Light distribution files

LUMILEDS

LED	LUXEON CX Plus CoB - HD S04H9
FWHM / FWTM	26.0° / 51.0°
Efficiency	88 %
Peak intensity	2.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
Bender Wirth: 634c Hekla	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LUMILEDS

LED	LUXEON CX Plus CoB L04 / L05 (Gen2)
FWHM / FWTM	31.0° / 63.0°
Efficiency	87 %
Peak intensity	1.8 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
Bender Wirth: 637a Hekla





Light distribution files

LUMILEDS

LED	LUXEON CX Plus CoB M02 / M03 (Gen2)
FWHM / FWTM	24.0° / 48.0°
Efficiency	88 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
Bender Wirth: 641a Hekla





Light distribution files

LUMILEDS

LED	LUXEON CX Plus CoB S01 (Gen2)
FWHM / FWTM	18.0° / 36.0°
Efficiency	90 %
Peak intensity	5.1 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
Bender Wirth: 634c Hekla





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LUMINUS

LED	CDM-9 (Dim-To-Warm)
FWHM / FWTM	26.0° / 52.0°
Efficiency	82 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
C16142_HEKLA-SOCKET-K
Bender Wirth: 490 Typ L8





Light distribution files

LUMINUS

LED	CXM-4
FWHM / FWTM	16.0° / 33.0°
Efficiency	88 %
Peak intensity	5.6 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15255_HEKLA-SOCKET-C





Light distribution files

LUMINUS

LED	CxM-9 (13.5x13.5)
FWHM / FWTM	27.0° / 55.0°
Efficiency	86 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15255_HEKLA-SOCKET-C





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

PHILIPS

LED	Fortimo SLM L09 CoB
FWHM / FWTM	26.0° / 51.0°
Efficiency	87 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15858_HEKLA-SOCKET-H





Light distribution files

PHILIPS

LED	Fortimo SLM L13 CoB
FWHM / FWTM	33.0° / 77.0°
Efficiency	80 %
Peak intensity	1.3 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
C16142_HEKLA-SOCKET-K
Bender Wirth: 432 Typ L8



PHILIPS

LED	Fortimo SLM L13 CoB
FWHM / FWTM	33.0° / 77.0°
Efficiency	80 %
Peak intensity	1.3 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
C16140_CLAMP-VERO29
Bender Wirth: 432 Typ L8





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

SAMSUNG

LED	LC003D / LC006D / LC009D / LC013D
FWHM / FWTM	27.0° / 55.0°
Efficiency	87 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15255_HEKLA-SOCKET-C





Light distribution files

SAMSUNG

LED	LC010C
FWHM / FWTM	20.0° / 41.0°
Efficiency	88 %
Peak intensity	3.8 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15848_HEKLA-SOCKET-G





Light distribution files

SAMSUNG

LED	LC010C G2
FWHM / FWTM	19.0° / 38.0°
Efficiency	87 %
Peak intensity	4.3 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:
F15255_HEKLA-SOCKET-C





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

SAMSUNG

LED	LC010T (Tunable White)
FWHM / FWTM	26.0° / 56.0°
Efficiency	82 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour/type	Tunable White

Required components:

C16142_HEKLA-SOCKET-K

Bender Wirth: 501 Typ L8





Light distribution files

SAMSUNG

LED	LC016D / LC019D / LC026D / LC033D
FWHM / FWTM	34.0° / 85.0°
Efficiency	79 %
Peak intensity	1.1 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:

F15859_HEKLA-SOCKET-I





Light distribution files

SAMSUNG

LED	LC020C
FWHM / FWTM	24.0° / 48.0°
Efficiency	88 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:

F15848_HEKLA-SOCKET-G





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

SAMSUNG

LED	LC020C G2
FWHM / FWTM	25.0° / 51.0°
Efficiency	85 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15859_HEKLA-SOCKET-I	





Light distribution files

SAMSUNG

LED	LC020T (Tunable white)
FWHM / FWTM	33.0° / 76.0°
Efficiency	79 %
Peak intensity	1.3 cd/lm
LEDs/each optic	1
Light colour/type	Tunable White
Required components:	
C16142_HEKLA-SOCKET-K	
Bender Wirth: 501 Typ L8	





Light distribution files

SEOUL SEMICONDUCTOR

LED	MJT COB LES 6
FWHM / FWTM	19.0° / 39.0°
Efficiency	85 %
Peak intensity	4.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15255_HEKLA-SOCKET-C	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

SEOUL SEMICONDUCTOR

LED	MJT COB LES 9.8
FWHM / FWTM	27.0° / 56.0°
Efficiency	83 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15255_HEKLA-SOCKET-C	





Light distribution files

TRIDONIC

LED	SLE G7 LES09
FWHM / FWTM	26.0° / 52.0°
Efficiency	86 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15255_HEKLA-SOCKET-C	





Light distribution files

TRIDONIC

LED	SLE G7 LES13
FWHM / FWTM	33.0° / 75.0°
Efficiency	81 %
Peak intensity	1.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15859_HEKLA-SOCKET-I	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

TRIDONIC

LED	SLE G7 LES15
FWHM / FWTM	34.0° / 84.0°
Efficiency	80 %
Peak intensity	1.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15859_HEKLA-SOCKET-I	





Light distribution files

XICATO

LED	XOB 14.5 mm
FWHM / FWTM	34.0° / 80.0°
Efficiency	80 %
Peak intensity	1.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15859_HEKLA-SOCKET-I	





Light distribution files

XICATO

LED	XOB 9.8 mm
FWHM / FWTM	25.0° / 53.0°
Efficiency	87 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15255_HEKLA-SOCKET-C	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

XICATO

LED	XTM - 19mm LES
FWHM / FWTM	36.0° / 108.0°
Efficiency	80 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White

Required components:

C16058_XTM-ADAPTER-50-C





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

bridgelux

LED	Vero SE 13
FWHM / FWTM	24.0° / 67.0°
Efficiency	69 %
Peak intensity	1.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
C16142_HEKLA-SOCKET-K	



Light distribution files

CITIZEN

LED	CLL03x/CLU03x
FWHM / FWTM	28.0° / 68.0°
Efficiency	82 %
Peak intensity	1.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15859_HEKLA-SOCKET-I	



Light distribution files

CREE LEDs

LED	CMA1840
FWHM / FWTM	30.0° / 68.0°
Efficiency	80 %
Peak intensity	1.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Bender Wirth: 637a Hekla



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs

LED	CMT14xx
FWHM / FWTM	16.0° / 50.0°
Efficiency	83 %
Peak intensity	3.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15255_HEKLA-SOCKET-C	



Light distribution files

CREE LEDs

LED	CMU15xx
FWHM / FWTM	29.0° / 69.0°
Efficiency	79 %
Peak intensity	1.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17438_HEKLA-G2-I	



LUMILEDS

LED	LUXEON CoB 1202/1203
FWHM / FWTM	26.0° / 58.0°
Efficiency	70 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F17437_HEKLA-G2-H	



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

NICHIA

LED	COB T-Type
FWHM / FWTM	19.0° / 38.0°
Efficiency	85 %
Peak intensity	5.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	
F15848_HEKLA-SOCKET-G	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Poznan, Poland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.