Product data sheet

Specifications



surge arrester, Multi9 PRD1 75r, 4P, 400/690 V

M9L57690

Main

Range	Multi9
Product name	Multi9 PRD1
product or component type	Surge arrester
Device short name	PRD1 75r
poles description	4P
Remote signalling	With
Signal contacts composition	1 SD (1 C/O)
Surge arrester type	Electrical distribution network

Complementary

Surge arrester class type	Type 1
Surge arrester technology	MOV
Wiring configuration	5-wire
Nominal discharge current	Common mode: 10 kA (L/PE) Common mode: 20 kA (N/PE) Differential mode: 10 kA (L/N)
Maximum discharge current	75 kA
[Iimp] impulse current	75 kA
[Uc] maximum continuous operating voltage	Common mode: 870 V AC L/PE Common mode: 550 V AC L/N Differential mode: 1100 V AC L/L Common mode: 320 V AC N/PE
Maximum [Up] voltage protection level	Common mode <2500 V L/PE Common mode <1500 V L/N Differential mode <3000 V L/L Common mode <1000 V N/PE
Disconnector device type	Associated circuit breaker
Short-circuit withstand	200 kA
Local signalling	Green mechanical indicator for operating Red mechanical indicator for end of life
mounting mode	Clip-on
mounting support	DIN rail
9 mm pitches	8
Height	91.7 mm
Width	70 mm
Depth	71.4 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

net weight	703 g
Colour	Grey (RAL 7035)
Response time	< 25 ns
Connections - terminals	Tunnel type terminal6…35 mm² (AWG 10...AWG 2) - rigid Tunnel type terminal6…25 mm² (AWG 10...AWG 4) - flexible Tunnel type terminal (dry contacts)0.5…1.5 mm²
Wire stripping length	10 mm for L/N connection 10 mm for PE connection 6 mm for dry contacts connection
Tightening torque	3 N.m L/N 3 N.m PE

Environment

Standards	UL 1449:ed. 4
IP degree of protection	NEMA 1 built-in:
Pollution degree	3
Relative humidity	0…95 %
Operating altitude	2000 m
Ambient air temperature for operation	-25…60 °C
Ambient air temperature for storage	-40…85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	9.0 cm
Package 1 Length	12.0 cm
Package 1 Weight	560.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	12
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	7.07 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Sustainable Packaging

Resource performance

- Sustainable Packaging

Well-being performance

- Reach Free Of Svhc
- Toxic Heavy Metal Free
- Mercury Free
- Rohs Exemption Information — Yes

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins