OLGA-M

~30° wide beam. Assembly with holder and installation tape.



SPECIFICATION:

Dimensions	Ø 32.0 mm
Height	19.1 mm
Fastening	tape, pin
ROHS compliant	yes

MATERIALS:

Component	Type	Material	Colour	Finish	Length
OLGA-M	Single lens	PMMA	clear		30.0
OLGA-HLD	Holder	PC	black		32.0
SPUTNIK-TAPE3	Tape	Acrylic foam	black		25.0

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
CA16128_OLGA-M » Box size: 476 x 273 x 292 mm	792	132	66	9.8

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



INDEX	PART	TYPE	MATERIAL	COLOR / COATING
1	C16123_OLGA-S	LENS	PMMA	CLEAR
1	C16124_OLGA-M	LENS	PMMA	CLEAR
1	C16125_OLGA-W	LENS	PMMA	CLEAR
1	C16307_OLGA-WAS	LENS	PMMA	CLEAR
1	C16671_OLGA-RS	LENS	PMMA	CLEAR
1	C16673_OLGA-O	LENS	PMMA	CLEAR
2	C16126_OLGA_HLD	HOLDER	PC	BLACK
3	C15177_SPUTNIK-TAPE3	TAPE	PU-FOAM	BLACK

This mechanical drawing can be used for following assembly codes	Dimension H
CA16127_OLGA-S	19.54
CA16128_OLGA-M	19.29
CA16129_OLGA-W	19.29
CA16308_OLGA-WAS	19.44
CA16672_OLGA-RS	19.46
C16673_OLGA-O	19.43

Notes

- LED location
- Ensure LED fitting from a product specific 3D model available from www.ledil.com
- For more details about installation please see LEDiL Installation Guide on www.ledil.com

MECHANICAL DRAWING

PRODUCT OLGA FAMILY

Plastic moulding general tolerances according to DIN 16901-130 and applies if not otherwise shown in the drawing. Silicone moulding general tolerances according to ISO 3302-1 Class M3 and applies if not otherwise shown in the drawing.

FIRST ANGLE PROJECTION:

This drawing is the property of LEDiL Oy. It may not be copied or otherwise distributed without prior written permission from LEDiL Oy.

SCALE 2:1 | WEIGHT - | A3 SHEET 1/1

See also our general installation guide: www.ledil.com/installation_guide

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CREE LEDs

LED	XD16
FWHM / FWTM	26.0° / 48.0°
Efficiency	80 %
Peak intensity	3.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

CREE LEDs

LED	XHP35 HD
FWHM / FWTM	32.0° / 58.0°
Efficiency	80 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

CREE LEDs

LED	XHP35 HI
FWHM / FWTM	28.0° / 51.0°
Efficiency	84 %
Peak intensity	2.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CREE LEDs

LED	XHP50
FWHM / FWTM	32.0° / 60.0°
Efficiency	81 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

CREE LEDs

LED	XHP50.2
FWHM / FWTM	31.0° / 58.0°
Efficiency	81 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

CREE LEDs

LED	XHP70
FWHM / FWTM	33.0° / 63.0°
Efficiency	82 %
Peak intensity	2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CREE LEDs

LED	XHP70.2
FWHM / FWTM	34.0° / 64.0°
Efficiency	81 %
Peak intensity	1.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

CREE LEDs

LED	XM-L
FWHM / FWTM	31.0° / 55.0°
Efficiency	83 %
Peak intensity	2.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

CREE LEDs

LED	XM-L3
FWHM / FWTM	33.0° / 57.0°
Efficiency	81 %
Peak intensity	2.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CREE LEDs

LED	XP-G2
FWHM / FWTM	30.0° / 53.0°
Efficiency	83 %
Peak intensity	2.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

CREE LEDs

LED	XP-G3
FWHM / FWTM	31.0° / 54.0°
Efficiency	82 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

CREE LEDs

LED	XP-L HI
FWHM / FWTM	28.0° / 50.0°
Efficiency	85 %
Peak intensity	3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CREE LEDs

LED	XP-L2
FWHM / FWTM	30.0° / 54.0°
Efficiency	81 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

CREE LEDs

LED	XQ-E HD
FWHM / FWTM	28.0° / 51.0°
Efficiency	76 %
Peak intensity	2.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

CREE LEDs

LED	XQ-E HI
FWHM / FWTM	27.0° / 49.0°
Efficiency	83 %
Peak intensity	3.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CREE LEDs

LED	XT-E
FWHM / FWTM	29.0° / 53.0°
Efficiency	79 %
Peak intensity	2.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LUMILEDS

LED	LUXEON 5050 Round LES
FWHM / FWTM	27.0° / 52.0°
Efficiency	86 %
Peak intensity	3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LUMILEDS

LED	LUXEON C
FWHM / FWTM	29.0° / 52.0°
Efficiency	76 %
Peak intensity	2.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LUMILEDS

LED	LUXEON CZ
FWHM / FWTM	26.0° / 47.0°
Efficiency	85 %
Peak intensity	3.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LUMILEDS

LED	LUXEON M/MX
FWHM / FWTM	31.0° / 59.0°
Efficiency	84 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LUMILEDS

LED	LUXEON MZ
FWHM / FWTM	26.0° / 50.0°
Efficiency	85 %
Peak intensity	3.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LUMILEDS

LED	LUXEON Rebel ES
FWHM / FWTM	28.0° / 51.0°
Efficiency	83 %
Peak intensity	3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LUMILEDS

LED	LUXEON TX
FWHM / FWTM	29.0° / 51.0°
Efficiency	83 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LUMILEDS

LED	LUXEON V
FWHM / FWTM	29.0° / 54.0°
Efficiency	82 %
Peak intensity	2.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LUMILEDS

LED	LUXEON V
FWHM / FWTM	28.0° / 53.0°
Efficiency	82 %
Peak intensity	2.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LUMILEDS

LED	LUXEON V2
FWHM / FWTM	29.0° / 51.0°
Efficiency	83 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LUMILEDS

LED	LUXEON Z
FWHM / FWTM	25.0° / 46.0°
Efficiency	85 %
Peak intensity	3.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LUMILEDS

LED	LUXEON Z ES
FWHM / FWTM	27.0° / 49.0°
Efficiency	85 %
Peak intensity	3.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

NICHIA

LED	NCSxE17A
FWHM / FWTM	23.0° / 44.0°
Efficiency	85 %
Peak intensity	4.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

NICHIA

LED	NVSW219D
FWHM / FWTM	31.0° / 54.0°
Efficiency	83 %
Peak intensity	2.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

NICHIA

LED	NVSW319B
FWHM / FWTM	34.0° / 56.0°
Efficiency	84 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

NICHIA

LED	NVSxE21A
FWHM / FWTM	23.0° / 44.0°
Efficiency	85 %
Peak intensity	4.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

NICHIA

LED	NVSxx19B/NVSxx19C
FWHM / FWTM	30.0° / 52.0°
Efficiency	84 %
Peak intensity	2.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

OSRAM
Opto Semiconductors

LED	Duris S8
FWHM / FWTM	27.0° / 53.0°
Efficiency	85 %
Peak intensity	3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

OSRAM
Opto Semiconductors

LED	OSCONIQ P 3737 (2W version)
FWHM / FWTM	26.0° / 49.0°
Efficiency	83 %
Peak intensity	3.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

OSRAM
Opto Semiconductors

LED	OSCONIQ P 3737 (3W version)
FWHM / FWTM	28.0° / 51.0°
Efficiency	84 %
Peak intensity	3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

OSRAM
Opto Semiconductors

LED	OSCONIQ P 7070
FWHM / FWTM	29.0° / 55.0°
Efficiency	83 %
Peak intensity	2.6 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

OSRAM
Opto Semiconductors

LED	OSLON Black Flat (LUW HWQP)
FWHM / FWTM	24.0° / 45.0°
Efficiency	85 %
Peak intensity	3.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

OSRAM
Opto Semiconductors

LED	OSLON Square CSSRM2/CSSRM3
FWHM / FWTM	30.0° / 52.0°
Efficiency	84 %
Peak intensity	2.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

OSRAM
Opto Semiconductors

LED	OSLON Square EC
FWHM / FWTM	28.0° / 51.0°
Efficiency	81 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

OSRAM
Opto Semiconductors

LED	OSLON Square PC
FWHM / FWTM	29.0° / 52.0°
Efficiency	82 %
Peak intensity	2.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

OSRAM
Opto Semiconductors

LED	OSLON SSL 150
FWHM / FWTM	30.0° / 51.0°
Efficiency	82 %
Peak intensity	2.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

OSRAM
Opto Semiconductors

LED	OSLON SSL 80
FWHM / FWTM	28.0° / 51.0°
Efficiency	82 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

OSRAM
Opto Semiconductors

LED	OSTAR Stage (S2WN)
FWHM / FWTM	26.0° / 50.0°
Efficiency	84 %
Peak intensity	3.2 cd/lm
LEDs/each optic	1
Light colour/type	RGBW
Required components:	





Light distribution files

SAMSUNG

LED	LH181A
FWHM / FWTM	22.0° / 44.0°
Efficiency	81 %
Peak intensity	4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

SAMSUNG

LED	LH181B
FWHM / FWTM	23.0° / 45.0°
Efficiency	85 %
Peak intensity	3.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

SAMSUNG

LED	LH231B
FWHM / FWTM	24.0° / 47.0°
Efficiency	86 %
Peak intensity	3.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

SAMSUNG

LED	LH351B
FWHM / FWTM	30.0° / 53.0°
Efficiency	84 %
Peak intensity	2.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

SAMSUNG

LED	LH351C
FWHM / FWTM	31.0° / 53.0°
Efficiency	85 %
Peak intensity	2.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

SAMSUNG

LED	LH351D
FWHM / FWTM	33.0° / 57.0°
Efficiency	83 %
Peak intensity	2.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

SAMSUNG

LED	LH508A
FWHM / FWTM	28.0° / 53.0°
Efficiency	85 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

SAMSUNG

LED	LM302A
FWHM / FWTM	25.0° / 48.0°
Efficiency	85 %
Peak intensity	3.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

SAMSUNG

LED	LM561B
FWHM / FWTM	27.0° / 51.0°
Efficiency	85 %
Peak intensity	3.2 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

SEOUL SEMICONDUCTOR

LED	WICOP 5050
FWHM / FWTM	33.0° / 60.0°
Efficiency	80 %
Peak intensity	2.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

SEOUL SEMICONDUCTOR

LED	Z5M3
FWHM / FWTM	28.0° / 52.0°
Efficiency	82 %
Peak intensity	2.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs

LED	J Series 5050 Round LES
FWHM / FWTM	25.0° / 46.0°
Efficiency	92 %
Peak intensity	4.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs

LED	XHP35.2 HI
FWHM / FWTM	26.0° / 46.0°
Efficiency	90 %
Peak intensity	3.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Light distribution files

CREE LEDs

LED	XHP50
FWHM / FWTM	28.0° / 49.0°
Efficiency	91 %
Peak intensity	3.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs

LED	XHP50.3 HD
FWHM / FWTM	31.0 + 30.0° / 52.0°
Efficiency	83 %
Peak intensity	2.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs

LED	XHP50.3 HI
FWHM / FWTM	28.0° / 48.0°
Efficiency	95 %
Peak intensity	3.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs

LED	XHP70.3 HD
FWHM / FWTM	33.0 + 32.0° / 58.0°
Efficiency	82 %
Peak intensity	2.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs

LED	XP-G2 HE
FWHM / FWTM	33.0° / 50.0°
Efficiency	89 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LUMILEDS

LED	LUXEON MZ
FWHM / FWTM	22.0° / 41.0°
Efficiency	91 %
Peak intensity	5.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LUMINUS

LED	SST-20
FWHM / FWTM	26.0° / 42.0°
Efficiency	91 %
Peak intensity	4.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

LUMINUS

LED	SST-70X-WCS
FWHM / FWTM	30.0° / 50.0 + 48.0°
Efficiency	85 %
Peak intensity	3.1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

NICHIA

LED	COB S-Type (LES 7)
FWHM / FWTM	32.0° / 58.0°
Efficiency	91 %
Peak intensity	2.5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

NICHIA

LED	COB T-Type
FWHM / FWTM	30.0° / 56.0°
Efficiency	91 %
Peak intensity	2.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

NICHIA

LED	NCSxE17A
FWHM / FWTM	24.0° / 44.0°
Efficiency	88 %
Peak intensity	4.5 cd/lm
LEDs/each optic	4
Light colour/type	White
Required components:	



Light distribution files

NICHIA

LED	NFMW48xA
FWHM / FWTM	25.0° / 47.0°
Efficiency	92 %
Peak intensity	4.3 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

NICHIA

LED	NV4WB35AM
FWHM / FWTM	25.0° / 44.0°
Efficiency	91 %
Peak intensity	4.4 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

NICHIA

LED	NV4x144A
FWHM / FWTM	31.0° / 54.0°
Efficiency	86 %
Peak intensity	2.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

OSRAM
Opto Semiconductors

LED	OSLON Pure 1414
FWHM / FWTM	24.0° / 40.0°
Efficiency	91 %
Peak intensity	5 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

OSRAM
Opto Semiconductors

LED	OSLON Pure 1414
FWHM / FWTM	25.0 + 21.0° / 44.0 + 42.0°
Efficiency	91 %
Peak intensity	5 cd/lm
LEDs/each optic	4
Light colour/type	RGBW
Required components:	



Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Poznan, Poland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.