




Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Feed-Through**

Modular Terminal Block Product Type: **Screw Clamp Terminal Block**

Primary Product Color: **Yellow**

Product Spacing: **22 mm [.866 in]**

Number of Positions: **2**

Features

Product Type Features

Modular Terminal Block Product Type	Screw Clamp Terminal Block
-------------------------------------	----------------------------

Configuration Features

Number of Levels	1
Gauge Type	B11
Number of Circuits	1
Block Function	Feed-Through
Number of Positions	2

Electrical Characteristics

Power Loss	6.1 W
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	1000 V
Impulse Withstanding Voltage Rating (IEC)	8000 V
Current Rating (IEC)	192 A
Current Rating (UL)	159 A
Dielectric Withstanding Voltage (Max)	2200 V



Voltage Rating (IEC)	1000 V
Short-Time Withstanding Current Rating @ 1s	8400 A

Body Features

Product Weight	158.1 g[6.224 oz]
Primary Product Color	Yellow

Mechanical Attachment

DIN Rail Mounting Type	TH35-15, TH35-7.5
Connector Mounting Type	DIN Rail

Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Product Depth	75.4 mm
Tool Size	6 mm[.236 in]
Wire Stripping Length	25 mm[.984 in]
Main Circuit Capacity - 2 Rigid Stranded Conductors per Screw Clamp	4 – 2 AWG
Main Circuit Capacity - Twin Ferrule per Screw Clamp	6 AWG
Main Circuit Capacity - 2 Flexible Conductors per Screw Clamp	4 – 2 AWG
Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	4 – 00 AWG
Main Circuit Capacity - 1 Non-Insulated Ferrule per Screw Clamp	16 – 50 mm²
Main Circuit Capacity - 1 Flexible Conductor per Screw Clamp	16 – 70 mm²
Main Circuit Capacity - 1 Insulated Ferrule per Screw Clamp	16 – 50 mm²
Product Length	75.35 mm[2.97 in]
Product Height	74 mm
Product Spacing	22 mm[.866 in]

Usage Conditions

Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Product Compliance



For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts



TE Part # 1SNK922310R0000
JB22-10



TE Part # 1SNK900611R0000
UMH




TE Part # 1SNA173220R0500
PR30




TE Part # 1SNK900102R0000
BAZH1




TE Part # 1SNK169999R0000
MC812PA



TE Part # 1SNA164800R0300
PR3.G2




TE Part # 1SNK160004R0000
MC812-YL



TE Part # 1SNA168700R2200
PR5



TE Part # 1SNK922302R0000
JB22-2




TE Part # 1SNA174300R1700
PR3.Z2



TE Part # 1SNK160000R0000
MC812



TE Part # 1SNK900613R0000
PROCAP8



TE Part # 1SNA168500R1200
PR4




TE Part # 1SNK922303R0000
JB22-3



TE Part # 1SNK922305R0000
JB22-5


Also in the Series | ENTRELEC SNK



Modular Terminal Blocks(319)



Terminal Block & Strip Conducting Accessories(67)



Terminal Block & Strip Insulating Accessories(31)

Customers Also Bought



TE Part #1SNK512010R0000
ZS25



TE Part #1SNK506010R0000
ZS6



TE Part #1SNA179726R0200
AJS9



TE Part #1SNK516030R0000
ZS35-OR



Documents

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_1SNK522060R0000_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SNK522060R0000_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SNK522060R0000_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[ZS70-YL](#)

English

[ENTRELEC Terminal Block - Master Catalog](#)

[ENTRELEC Terminal Block - Master Catalog](#)

English

[SNK SERIES TERMINAL BLOCKS](#)

English

[ENTRELEC Terminal Blocks Catalogue \(RUS\)](#)

Agency Approvals

[ZK-ZS_ATEX_1SND225112U1006-C-TE](#)

1SNK522060R0000

Screw Clamp Terminal Block, Feed-Through, Yellow, 22 mm [.866 in] Spacing, 2
Position, DIN Rail, -55 – 110 °C [-67 – 230 °F], ENTRELEC SNK



English