NCP4640

50 mA, Wide Input Range, Voltage Regulator

The NCP4640 is a CMOS 50 mA linear voltage regulator with high input voltage and ultra−low supply current. It incorporates multiple protection features such as peak current limit, short circuit current limit and thermal shutdown to ensure a very robust device.

A high maximum input voltage tolerance of 50 V and a wide temperature range make the NCP4640 suitable for a variety of demanding applications.

Features

- Operating Input Voltage Range: 4 V to 36 V
- Output Voltage Range: 2.0 to 12.0 V (0.1 steps)
- ±2% Output Voltage Accuracy
- Output Current: min 50 mA (V_{IN} = 8 V, V_{OUT} = 5 V)
- Line Regulation: 0.05%/V
- Peak Current Limit Circuit
- Short Current Limit Circuit
- Thermal Shutdown Circuit
- Available in SOT−89−5 and SOIC6−TL Package
- These are Pb−Free Devices

Typical Applications

- Power source for home appliances
- Power source for car audio equipment, navigation system
- Power source for notebooks, digital TVs, cordless phones and private LAN systems
- Power source for office equipment machines such as copiers, printers, facsimiles, scanners, projectors, etc.





Figure 1. Typical Application Schematic


ON Semiconductor™

http://onsemi.com

MARKING DIAGRAMS




SOIC6−TL
CASE 751BR





SOT−89 5
CASE 528AB



XXXX = Specific Device Code
MM = Date Code

(Note: Microdot may be in either location)

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 15 of this data sheet.

© Semiconductor Components Industries, LLC, 2011




Figure 2. Simplified Schematic Block Diagram

PIN FUNCTION DESCRIPTION

Pin No. SOT89	Pin No. SOIC6−TL	Pin Name	Description
5	6	VIN	Input pin
2	2	GND	Ground pin, all ground pins must be connected together when it is mounted on board
4	4	GND	Ground pin, all ground pins must be connected together when it is mounted on board
−	5	GND	Ground pin, all ground pins must be connected together when it is mounted on board
3	3	CE	Chip enable pin (“H” active)
1	1	VOUT	Output pin

ABSOLUTE MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Input Voltage	V_{IN}	−0.3 to 50	V
Peak Input Voltage (Note 1)	V_{IN}	60	V
Output Voltage	V_{OUT}	−0.3 to V_{IN} + 0.3 ≤ 50	V
Chip Enable Input	V_{CE}	−0.3 to V_{IN} + 0.3 ≤ 50	V
Output Current	I_{OUT}	150	mA
Power Dissipation SOT−89	P_D	900	mW
Power Dissipation SOIC6−TL		1700	
Junction Temperature	T_J	−40 to 150	°C
Storage Temperature	T_{STG}	−55 to 125	°C
ESD Capability, Human Body Model (Note 2)	ESD_{HBM}	2000	V
ESD Capability, Machine Model (Note 2)	ESD_{MM}	200	V

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. Duration time = 200 ms
2. This device series incorporates ESD protection and is tested by the following methods:
   ESD Human Body Model tested per AEC−Q100−002 (EIA/JESD22−A114)
   ESD Machine Model tested per AEC−Q100−003 (EIA/JESD22−A115)
   Latchup Current Maximum Rating tested per JEDEC standard: JESD78.

THERMAL CHARACTERISTICS

Rating	Symbol	Value	Unit
Thermal Characteristics, SOT−89 Thermal Resistance, Junction−to−Air	$R_{\theta JA}$	111	°C/W
Thermal Characteristics, SOIC6−TL Thermal Resistance, Junction−to−Air	$R_{\theta JA}$	59	°C/W

ELECTRICAL CHARACTERISTICS T_A = 25°C

Parameter	Test Conditions		Symbol	Min	Typ	Max	Unit
Operating Input Voltage			V_{IN}	4		36	V
Output Voltage	V_{IN} = V_{OUT} + 3 V, I_{OUT} = 1 mA		V_{OUT}	x0.98		x1.02	V
Output Voltage Temp. Coefficient	V_{IN} = V_{OUT} + 3 V, I_{OUT} = 1 mA, T_A = −40 to 105°C				±100		ppm/°C
Line Regulation	V_{IN} = V_{OUT} + 1.5 V to 36 V, I_{OUT} = 1 mA		$Line_{Reg}$		0.05	0.20	%/V
Load Regulation	V_{IN} = V_{OUT} + 3 V, I_{OUT} = 1 mA to 40 mA	2.0 V ≤ V_{OUT} < 5.0 V	$Load_{Reg}$		10	25	mV
		5.0 V ≤ V_{OUT} < 12.0 V			20	35	
Dropout Voltage	I_{OUT} = 20 mA	2.0 V ≤ V_{OUT} < 3.7 V	V_{DO}			(Note 3)	V
		3.7 V ≤ V_{OUT} < 4.0 V			0.35	0.60	
		4.0 V ≤ V_{OUT} < 5.0 V			0.25	0.40	
		5.0 V ≤ V_{OUT} < 12.0 V			0.20	0.35	
Output Current	V_{IN} = V_{OUT} + 3 V		I_{OUT}	50			mA
Short Current Limit	V_{OUT} = 0 V		I_{SC}		50		mA
Quiescent Current	V_{IN} = V_{OUT} + 3 V, I_{OUT} = 0 mA		I_Q		9	20	μA
Standby Current	V_{IN} = 36 V, V_{CE} = 0 V		I_{STB}		0.1	1	μA
CE Pin Threshold Voltage	CE Input Voltage “H”		V_{CEH}	1.5		V_{IN}	V
	CE Input Voltage “L”		V_{CEL}	0		0.3	
Thermal Shutdown Temperature			T_{SD}		150		°C
Thermal Shutdown Release Temperature			T_{SR}		125		°C
Power Supply Rejection Ratio	V_{IN} = 5.0 V, V_{OUT} = 2.0 V, $\Delta V_{IN\ PK-PK}$ = 0.2 V, I_{OUT} = 30 mA, f = 1 kHz		PSRR		30		dB
Output Noise Voltage	V_{OUT} = 2.0 V, I_{OUT} = 30 mA, f = 10 Hz to 100 kHz		V_N		80		μV_{rms}

3. Dropout voltage for 2.0 V ≤ V_{OUT} < 3.7 V can be computed by this formula: V_{DO} = 4 V − V_{OUTSET}

TYPICAL CHARACTERISTICS




Figure 3. Output Voltage vs. Output Current 2.0 V Version (T_J = 25°C)




Figure 4. Output Voltage vs. Output Current 3.3 V Version (T_J = 25°C)




Figure 5. Output Voltage vs. Output Current 8.0 V Version (T_J = 25°C)




Figure 6. Output Voltage vs. Output Current 12 V Version (T_J = 25°C)




Figure 7. Dropout Voltage vs. Output Current 8.0 V Version




Figure 8. Dropout Voltage vs. Output Current 12 V Version

TYPICAL CHARACTERISTICS




Figure 9. Output Voltage vs. Temperature, 2.0 V Version




Figure 10. Output Voltage vs. Temperature, 3.3 V Version




Figure 11. Output Voltage vs. Temperature, 8.0 V Version




Figure 12. Output Voltage vs. Temperature, 12 V Version




Figure 13. Supply Current vs. Temperature




Figure 14. Supply Current vs. Input Voltage

TYPICAL CHARACTERISTICS




Figure 15. Output Voltage vs. Input Voltage, 2.0 V Version




Figure 16. Output Voltage vs. Input Voltage, 3.3 V Version




Figure 17. Output Voltage vs. Input Voltage, 8.0 V Version




Figure 18. Output Voltage vs. Input Voltage, 12 V Version




Figure 19. PSRR, 2.0 V Version, V_{IN} = 5.0 V




Figure 20. PSRR, 3.3 V Version, V_{IN} = 6.3 V

TYPICAL CHARACTERISTICS




Figure 21. PSRR, 3.3 V Version, V_{IN} = 6.3 V




Figure 22. Output Voltage Noise, 2.0 V Version, V_{IN} = 5.0 V, I_{OUT} = 30 mA




Figure 23. Output Voltage Noise, 3.3 V Version, V_{IN} = 6.3 V, I_{OUT} = 30 mA




Figure 24. Output Voltage Noise, 8.0 V Version, V_{IN} = 11.0 V, I_{OUT} = 30 mA




Figure 25. Output Voltage Noise, 12.0 V Version, V_{IN} = 15.0 V, I_{OUT} = 30 mA

TYPICAL CHARACTERISTICS




Figure 26. Line Transients, 2.0 V Version, $t_R = t_F = 50$ μs, $I_{OUT} = 1$ mA




Figure 27. Line Transients, 3.3 V Version, $t_R = t_F = 50$ μs, $I_{OUT} = 1$ mA




Figure 28. Line Transients, 8.0 V Version, $t_R = t_F = 50$ μs, $I_{OUT} = 1$ mA

TYPICAL CHARACTERISTICS




Figure 29. Line Transients, 12.0 V Version, $t_R = t_F = 50$ μs, $I_{OUT} = 1$ mA




Figure 30. Load Transients, 2.0 V Version, $I_{OUT} = 1 – 20$ mA, $t_R = t_F = 50$ μs, $V_{IN} = 5.0$ V




Figure 31. Load Transients, 3.3 V Version, $I_{OUT} = 1 – 20$ mA, $t_R = t_F = 50$ μs, $V_{IN} = 6.3$ V

TYPICAL CHARACTERISTICS




Figure 32. Load Transients, 8.0 V Version, I_{OUT} = 1 – 20 mA, $t_R = t_F$ = 50 μs, V_{IN} = 11.0 V




Figure 33. Load Transients, 12.0 V Version, I_{OUT} = 1 – 20 mA, $t_R = t_F$ = 50 μs, V_{IN} = 15.0 V




Figure 34. Load Transients, 2.0 V Version, I_{OUT} = 20 – 50 mA, $t_R = t_F$ = 50 μs, V_{IN} = 5.0 V

TYPICAL CHARACTERISTICS




Figure 35. Load Transients, 3.3 V Version, I_{OUT} = 20 – 50 mA, t_R = t_F = 50 μs, V_{IN} = 6.3 V




Figure 36. Load Transients, 8.0 V Version, I_{OUT} = 20 – 50 mA, t_R = t_F = 50 μs, V_{IN} = 11.0 V




Figure 37. Load Transients, 12.0 V Version, I_{OUT} = 20 – 50 mA, t_R = t_F = 50 μs, V_{IN} = 15.0 V

TYPICAL CHARACTERISTICS




Figure 38. Start−up, 2.0 V Version, V_{IN} = 5.0 V




Figure 39. Start−up, 3.3 V Version, V_{IN} = 6.3 V




Figure 40. Start−up, 8.0 V Version, V_{IN} = 11.0 V

TYPICAL CHARACTERISTICS




Figure 41. Start−up, 12.0 V Version, V_{IN} = 15.0 V

APPLICATION INFORMATION

A typical application circuit for NCP4640 series is shown in Figure 42.




Figure 42. Typical Application Schematic

Input Decoupling Capacitor (C1)

The device is stable without any input capacitance, but if input line is long and has high impedance or if more stable operation is needed, input capacitor C1 should be connected as close as possible to the IC. Recommended range of input capacitor value is 100 nF to 10 μF.

Output Decoupling Capacitor (C2)

The NCP4641 can work stable without output capacitor, but if faster response and higher stability reserve is needed, output capacitor should be connected as close as possible to the device. Recommended range of output capacitance is 100 nF to 10 μF. Larger values of output capacitance and lower ESR improves dynamic parameters.

Enable Operation

The enable pin CE may be used for turning the regulator on and off. The device is activated when high level is connected to CE pin. Do not keep CE pin not connected or between VCEH and VCEL voltage levels. Otherwise output voltage would be unstable or indefinite and unexpected would flow internally.

Thermal

As a power across the IC increase, it might become necessary to provide some thermal relief. The maximum power dissipation supported by the device is dependent upon board design and layout. Mounting pad configuration on the PCB, the board material, and also the ambient temperature affect the rate of temperature increase for the part. When the device has good thermal conductivity through the PCB the junction temperature will be relatively low in high power dissipation applications.

The IC includes internal thermal shutdown circuit that stops operation of regulator, if junction temperature is higher than 150°C. After that, when junction temperature decreases below 125°C, the operation of voltage regulator would restart. While high power dissipation condition is, the regulator starts and stops repeatedly and protects itself against overheating.

PCB layout

Pins number 2 and 4 of SOT89−5 package and pins number 2, 4 and 5 of SOIC6−TL must be wired to the GND plane while it is mounted on board. Make VIN and GND lines sufficient. If their impedance is high, noise pickup or unstable operation may result. Connect capacitors C1 and C2 as close as possible to the IC, and make wiring as short as possible.

ORDERING INFORMATION

Device	Nominal Output Voltage	Description	Marking	Package	Shipping†
NCP4640H020T1G	2.0 V	Enable High	N020	SOT89−5 (Pb−Free)	1000 / Tape & Reel
NCP4640H030T1G	3.0 V	Enable High	N030	SOT89−5 (Pb−Free)	1000 / Tape & Reel
NCP4640H033T1G	3.3 V	Enable High	N033	SOT89−5 (Pb−Free)	1000 / Tape & Reel
NCP4640H080T1G	8.0 V	Enable High	N080	SOT89−5 (Pb−Free)	1000 / Tape & Reel
NCP4640H120T1G	12.0 V	Enable High	N120	SOT89−5 (Pb−Free)	1000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

*To order other package and voltage variants, please contact your ON Semiconductor sales representative.

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS


ON Semiconductor®

SOT−89, 5 LEAD
CASE 528AB−01
ISSUE O


DATE 23 NOV 2009




SCALE 2:1



TOP VIEW



SIDE VIEW




BOTTOM VIEW

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. LEAD THICKNESS INCLUDES LEAD FINISH.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.
5. DIMENSIONS L, L2, L3, L4, L5, AND H ARE MEASURED AT DATUM PLANE C.

	MILLIMETERS	
DIM	MIN	MAX
A	1.40	1.60
b	0.32	0.52
b1	0.37	0.57
c	0.30	0.50
D	4.40	4.60
D2	1.40	1.80
E	2.40	2.60
e	1.40	1.60
H	4.25	4.45
L	1.10	1.50
L2	0.80	1.20
L3	0.95	1.35
L4	0.65	1.05
L5	0.20	0.60


GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code
MM = Lot Number
▪ = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G”, may or not be present.

RECOMMENDED MOUNTING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	**98AON47037E**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**SOT−89, 5 LEAD**	**PAGE 1 OF 1**

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales