




Connectors > Rectangular Connectors > Standard Rectangular Connectors



Connector Product Type: **Housing**

Connector & Housing Type: **Plug**

Mating Retention Type: **Detent Latching**

Connector System: **Wire-to-Board**

UL Flammability Rating: **UL 94V-0**

Features

Product Type Features

Connector Product Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	12
Number of Rows	1

Electrical Characteristics

Dielectric Withstanding Voltage (Max)	600 VACrms
Operating Voltage	250 VAC

Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

Contact Layout	Inline
Contact Base Material	Phosphor Bronze
Contact Type	Pin
Contact Current Rating (Max)	3 A



Termination Features

Termination Method to Wire & Cable	Crimp, Insulation Displacement (IDC)
------------------------------------	--------------------------------------

Mechanical Attachment

Mating Retention Type	Detent Latching
Mating Retention	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Centerline (Pitch)	2.54 mm[.1 in]
Housing Material	Thermoplastic

Dimensions

Connector Height	6.6 mm[.26 in]
Connector Length	32.89 mm[1.29 in]
Row-to-Row Spacing	2.54 mm[.1 in]

Usage Conditions

Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

Glow Wire Rating	Standard Part - Not Glow Wire
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Method	Package
Packaging Quantity	1

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250)



Halogen Content	Does not contain REACH SVHC
Solder Process Capability	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 6-103958-1
2X12 MTE RCPT SR LATCH .100CL



TE Part # 5-104505-4
MTE PIN 22-26 AWG PLTD



TE Part # 5-104506-4
MTE PIN 28-32 AWG PLTD



TE Part # 5-104505-2
MTE PIN 22-26 AWG PLTD




TE Part # 1-104257-1
12 MTE RCPT HSG SR LATCH .100

Also in the Series | AMPMODU MTE



Connector Caps & Covers(18)




Connector Contacts(19)



Connector Hardware(1)



Insertion & Extraction Tools(1)



PCB Headers & Receptacles(330)



Rectangular Connector Housings(66)



Standard Rectangular Connectors(201)



Wire-to-Board Connector Assemblies & Housings(201)



Wire-to-Board Headers & Receptacles (330)


Customers Also Bought



TE Part #ANT-433-CW-QW
Antenna 1/4 Wave Whip 433MHz



TE Part #CONMMCX012
MMCX Jack 50 Ohm Cable Crimp



TE Part #5-100526-6
Z-PACK F.CODING KEY




TE Part #103653-1
02 MTE SHRD PIN HSG SR LATCH




TE Part #170262-4
EIS CONNECTOR FORMING



TE Part #1-338310-2
15POS.HD20 PLUG ASS'Y




TE Part #350968-2
MR PIN 26-24 AU/PHBZ



TE Part #5499910-3
A/L UNIV HDR 16P VERT SHT LAT



TE Part #5747301-7
37 RCPT SP/FMS INSRT



TE Part #167418-1
MOD-4 REC.CONT.SCP.

Documents

Product Drawings

12 MTE SHRD PIN HSG SR LATCH

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-103653-1_AM.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-103653-1_AM.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-103653-1_AM.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

AMP MODU MTE Section of Catalog 1307819

English

AMPMODU_INTERCONNECTION_SYSTEM_SECTION5_CONT

English

AMPMODU MTE INTERCONNECT SYSTEM

English

Product Specifications

Application Specification

English