



Connectors > Terminal Blocks & Strips > Terminal Block & Strip Accessories > Terminal Block & Strip Marking Accessories



Marking Product Type: **Marker Card**
Pre-Printed Mark Details: **V1 (x100)**
Primary Product Color: **White**
Product Orientation: **Vertical**
Operating Temperature Range: **-55 - 110 °C [-67 - 230 °F]**

Features

Product Type Features

Marking Product Type	Marker Card
----------------------	-------------

Configuration Features

Number of Cards per Package	1
Number of Digits per Marker - Horizontal	3
Number of Digits per Marker - Vertical	8
Pre-Printed Mark Details	V1 (x100)

Body Features

Primary Product Material	Polyamide
Product Weight	10 g[.353 oz]
Primary Product Color	White
Product Orientation	Vertical

Dimensions

Product Depth	4.8 mm
Product Width	5.2 mm[.205 in]
Product Length	5 mm[.197 in]
Product Height	12 mm[.472 in]

Usage Conditions

Operating Temperature Range	-55 - 110 °C[-67 - 230 °F]
-----------------------------	----------------------------



Industry Standards

UL Flammability Rating	UL 94V-2
------------------------	----------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Customers Also Bought



 TE Part # 1-222246-0 CONTACT,PLUG,COML BNC PLATED	 TE Part # 227079-9 COMM. BNC-PLUG	 TE Part # 924309-000 55PC0141-24-2/5/6/9	 TE Part # 1532177-1 M83513/04-G01N, MCKS-N1-B-51S6G1-18.0
 TE Part # 2836167-1 OCEAN_2.0_Applicator-S-045F-RSM	 TE Part # 2844982-1 CCII TYPE VI MLTIMATE PIN/SKT 22-18 ASSY	 TE Part # 589597-000 55A0831-24-9/93/96CS2275	 TE Part # 86147-8 MOD I POST PLTD 30 AU
 TE Part # YDTS20F21-16AC0000 SQUARE FLANGE RECEPTACLE	 TE Part # 225094-1 N SER BHD JACK WEATHERPROOF		

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SNK148132R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SNK148132R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNK148132R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ENTRELEC Terminal Block - Master Catalog

ENTRELEC Terminal Block - Master Catalog

English

1SNK148132R0000

Terminal Block & Strip Marking Accessories, Marker Card, V1 (x100) Mark Details,
White, Vertical, -55 - 110 °C [-67 - 230 °F], UL 94V-2



[MC512PA V1 \(x100\) Vertical](#)

English

[SNK SERIES TERMINAL BLOCKS](#)

English

[ENTRELEC Terminal Blocks Catalogue \(RUS\)](#)