41532 ✔ ACTIVE

FASTON | FASTON 250

TE Internal #: 41532

Quick Disconnect Receptacle, Uninsulated, 18 – 12 AWG, .82 – 3.31 mm² Wire, 6.35 mm [.25 in] Tab Width, Tab-Lok, Flag, Brass, Tin Plating, FASTON 250

View on TE.com >

Terminals & Splices > Quick Disconnects

Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.82 – 3.31 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Flag
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	Tab-Lok
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Product Length	17.02 mm[.67 in]
Compatible Insulation Diameter Range	2.79 – 5.33 mm[.11 – .21 in]
Terminal Material Thickness	.43 mm[.017 in]
Wire Size	.82 – 3.31 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL

Packaging Features

Packaging Quantity	4000
Packaging Method	Strip/Reel

Other

Line	Premier

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

TE Part # 1596697-5
HB APPL,AOM

TE Part # 2088156-2
MINI APPLICATOR, HINGE BAR END FEED



TE Part # 7-1855041-7
SPARE PART KIT

TE Part # 1855041-1
HINDGE BAR F.A. EMPO160TAB180O LM & G

TE Part # 1596696-2
HB APPL,AOL

TE Part # 2232111-3
250 FASTON,FLAG,REC.,12-20 AWG, TPBR

TE Part # 1852633-1
EAPOHB160TABLOCK180O LM/G-HINGE BAR

TE Part # 2232111-1
250 FASTON,FLAG,REC.,12-20 AWG, TPBR

Also in the Series | FASTON 250

Compression Connectors(4)



Crimp Terminal Housings(115)

Insertion & Extraction Tools(6)

Insulation Boots & Sleeves(16)



Magnet Wire Terminals(1)

PCB Terminals(133)

Quick Disconnects(417)

Splices(4)

Customers Also Bought

TE Part #NB-PTCO-163
Pt1000, 2.0x2.3, Class C, PTFC102C1A0



TE Part #42776-1
SPLC AMVAR 1500-5000 020BR



TE Part #238005-1
ANVIL

TE Part #3-1625999-7
HSC100 4K7 5%

TE Part #2213847-1
GASKET, SEALING ROT DIM RECEPT

TE Part #2238197-3
250 FASTON,FLAG,REC.,18-12 AWG, TPBR

TE Part #2238200-3
187 FASTON,FLAG,REC.,20-16 AWG, PTBR

TE Part #465468-1
INSERTION TOOL TIP

TE Part #1-1743216-1
GAS VALVE 2P HSG

TE Part #1-1743217-1
GAS VALVE 3P HSG

Documents

Product Drawings

250 FASTON FLAG REC 18-12 AWG TPBR

English

CAD Files

Customer View Model

ENG_CVM_CVM_41532_DS.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_41532_DS.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_41532_DS.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

1654742_HOUSEHOLD_APPLIANCES_RAST5

English

FASTIN_FASTON_Product_Line

English

82004 FASTON Terminals (Insulated and Uninsulated) Catalog - FASTON Receptacles Section

English

Product Specifications

Engineering Report

English

Agency Approvals

Agency Approval Document

English