




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.32 – .82 mm²**

Mating Tab Width: **2.8 mm [.11 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Product Length	13.97 mm[.55 in]
Compatible Insulation Diameter Range	2.03 – 3.05 mm[.08 – .12 in]
Terminal Material Thickness	6.35 mm[.25 in]
Wire Size	.32 – .82 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	9000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 63580-1
FF 125 REC 22-18AWG TPBR

TE Part # 2150769-1
OCEAN_2.0_Applicator-E-070F140F-REM

TE Part # 2150769-2
OCEAN_2.0_Applicator-E-070F140F-REA

TE Part # 7-2150769-7
OCEAN_2.0_SPARE_PART_KIT-070F140F

Also in the Series | FASTIN-FASTON 110

Automotive Housings(6)

Automotive Signal & Power Connector Housings(6)

Automotive Terminals(5)

Crimp Terminal Housings(34)

Insertion & Extraction Tools(3)

Quick Disconnects(78)

Customers Also Bought

TE Part #K1125921
Batt Disconnecter 35-524-231-R-A2-900

TE Part #DT06-4S-CE01
PLG, 4P, GRY, E, CAP

TE Part #DT04-4P-CE04
REC, 4P, GRY, E, XCAP

TE Part #42281-1
FF 250 REC 18-14AWG BR





TE Part #185793-1
90 DEG CAP CORRUGTD TUBE



TE Part #8-968971-1
MCP2.8 GEH 9P



TE Part #6-1393292-3
V23074A2002A403-EV-CBOX



TE Part #1622461-1
LR1 1% 3K3



TE Part #1-1718484-2
CARRIER FOR RECEPTACLE INSERTS



TE Part #1989879-1
.250 SRS FASTIN-ON REC.

Documents

Product Drawings
FF 110 REC 22-18AWG BR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_63241-1_V_c-63241-1-v.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_63241-1_V_c-63241-1-v.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_63241-1_V_c-63241-1-v.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications
Application Specification

English

Application Specification

English