



A circular stamp with a thick black border. The text is arranged in four horizontal sections separated by thin lines. The top section contains 'ALTW' in a large, stylized font. The second section contains 'DCC. DEPT.' in a smaller font. The third section contains 'CONFIDENTIAL' in a bold, sans-serif font. The fourth section contains the date '2015.12.14' in a large, bold, sans-serif font. The bottom section contains the word 'ISSUED' in a large, bold, sans-serif font.



Pin Assignments

Front View前視圖

Red	紅	2
Green	綠	1
Wire Color		Conn.
Pin Out		



BB-02BFMM-SL7AXX

XX:01~99Meter

01:01Meter

02:02Meters

-
-
-
-

99:99Meters

Cable Length(L):01~99Meters

Note:

- * @C Important Dimension To Check.
- * Waterproof Rate: IP67
- * Housing: Nylon+GF, Black
- * Male Pin: Copper Alloy, Gold Plated
- * Screw Nut: Nylon+GF, Black
- * Cable: Black, UL2464 20AWG*2C+Drain+Al/My, PVC Jacket, UV Resistant, OD=5.8mm
- * Cable Length Tolerance: 01M:±40mm
02M~05M:±60mm
06M~10M:±100mm
11M~30M:±200mm
31M~99M:±500mm

UNIT:mm		TITLE		Amphenol LTW 安費諾亮泰企業股份有限公司	ITEM NO	DRAWN BY	DATE
TOLERANCE ±0.5 mm		Standard,Cable Screw 2Pin F Conn M Pin			DWG NO	CHECKED BY	DATE
		SCALE Free SHEET 1 OF 1			BB-02BFMM-SL7AXX	Rita	2015/12/04
		REV. B SIZE A4 QC :Inspection Item			CUSTOMER	APPROVED BY	DATE
					ALTW	Lisa	2015/12/04